


Tube Hex Hangers

Hex Hanger with Nitrile Grommets - B24RG


- Nitrile grommets maximum temperature: **230°F**
- All hex and round style hangers can be equipped with the following coupler options:
 - 3/8 NPT
 - all thread: 3/8-16 or 1/2-13



Tube OD	A	B	304 Stainless Steel Part Number
½" - ¾"	3.425	1.450	B24RG-G75
1"	3.425	1.450	B24RG-G100
1½"	4.000	2.125	B24RG-G150
2"	4.500	2.500	B24RG-G200
2½"	4.950	3.125	B24RG-G250
3"	5.500	3.750	B24RG-G300
4"	6.950	4.750	B24RG-G400
5"	8.000	5.625	B24RG-G500
6"	9.250	6.625	B24RG-G600
8"	11.500	8.625	B24RG-G800
10"	14.500	10.500	B24RG-G1000
12"	16.750	12.625	B24RG-G1200

Hex Hanger with Viton® Grommets - B24RGSFY


- Viton® grommets maximum temperature: **392°F**
- All hex and round style hangers can be equipped with the following coupler options:
 - 3/8 NPT
 - all thread: 3/8-16 or 1/2-13



Tube OD	A	B	304 Stainless Steel Part Number
½"	3.625	2.125	B24RGSFY-G50
¾"	3.625	2.125	B24RGSFY-G75
1"	3.625	2.125	B24RGSFY-G100
1½"	3.625	2.125	B24RGSFY-G150
2"	4.313	2.625	B24RGSFY-G200
2½"	4.875	3.125	B24RGSFY-G250
3"	5.375	3.625	B24RGSFY-G300
4"	6.563	4.750	B24RGSFY-G400
6"	9.000	6.625	B24RGSFY-G600
8"	11.250	8.750	B24RGSFY-G800
10"	14.500	10.500	B24RGSFY-G1000
12"	16.750	12.625	B24RGSFY-G1200

Hex Hanger with Nitrile Grommets and Coupler - B24RGC

- Nitrile grommets maximum temperature: **230°F**
- Coupler has 3/8 NPT



Tube OD	A	B	C	304 Stainless Steel Part Number
½" - ¾"	3.425	1.450	.750	B24RGC-G75
1"	3.425	1.450	.750	B24RGC-G100
1½"	4.000	2.125	.750	B24RGC-G150
2"	4.500	2.500	.750	B24RGC-G200
2½"	4.750	3.125	.750	B24RGC-G250
3"	5.500	3.750	.750	B24RGC-G300
4"	6.750	4.750	.750	B24RGC-G400
6"	9.250	6.625	.750	B24RGC-G600
8"	11.500	8.625	.750	B24RGC-G800