

Stub Out Bracket

Copper-Plated

- Extruded models provide four times the soldering surface for extra strength
- Heat the tube, not the bracket

Galvanized

- For use with Pipe Eye insert grommets

SUPPLY



521-118

ACCESS



521-810

DRAINAGE



521-318

TESTING



521-360



521-3725B



Related Products

Pipe Eye

Suspensulator

Secure-All

For a better bracket

p 276

p 275

p 313

Item No.	Dimensions	Holes	Extruded Holes	Gauge	Pkg	Min. Qty	Case Qty	List Price
COPPER-PLATED								
521-118	1¼" × 20"	½" CTS, 2" O.C. (8)		16	B	50	50	3.25 EA
521-118R	1¼" × 20"	½" CTS, 2" O.C. (7)	✓	16	B	25	25	3.45 EA
521-126	1¼" × 26"	½" CTS, 2" O.C. (11)		16	B	50	50	4.95 EA
521-810	1¾" × 20"	½" CTS, 2" O.C. (7) ¾" CTS, 4" O.C. (4) 1" CTS, 4" O.C. (4)		16	B	50	50	3.85 EA
521-810PK	1¾" × 20"	½" CTS, 2" O.C. (7) ¾" CTS, 4" O.C. (4) 1" CTS, 4" O.C. (4)		16	C*	50	50	4.20 EA
521-820	1¾" × 20"	½" CTS, 2" O.C. (7) ¾" CTS, 4" O.C. (4) 1" CTS, 4" O.C. (3)	✓	24	B	50	50	3.65 EA
GALVANIZED								
521-318	2" × 20"	1½/32", 2" O.C. (7)		14	B	50	50	2.73 EA
521-360	2" × 26"	1½/32", 2" O.C. (11)		14	B	50	50	3.30 EA
521-3725B	3" × 4¾"	1½/32", 2" O.C. (2)		14	B	100	100	1.45 EA




SUPPORT

Stub Out Bracket with Stud Guard

Copper-Plated

- 16-gauge with built-in stud guard
- Ideal for water closets and hose bibb applications
- Positions ½" CTS at 2¼", 4¾" or 6" from floor for water closets and ¾" CTS at 3½" from floor or side rough for other piping needs

SPECIALTIES



521-6415



521-6416

TOOLS

Item No.	Holes	Self-nailing Tabs	Gauge	Pkg	Min. Qty	Case Qty	List Price
521-6415	½" CTS (3) ¾" CTS (1)	✓	16	B	25	25	2.71 EA
521-6416	½" CTS (3) ¾" CTS (1)		16	B	25	25	2.71 EA

