



557-2



557F3

EZ Glide™ Suspension Clamp

- Ribs allow pipe to glide easier and more silently when the pipe expands and contracts
- Split design allows for use after piping run
- Available in alternative material for plenum-safe installation requirements
- Compatible with copper, PEX or CPVC
- No way for tube to escape
- Plenum Safe™ models meet ASTM E84 25/50 Flame/Smoke Spread and UL94 V-0 flame rating



Related Products

Suspensulator p 275
Dual purpose Suspensulators reduce SKUs.

Item No.	Description	Pkg	Min. Qty	Case Qty	List Price
STANDARD					
557-2	1/2" CTS	B	100	1000	0.22 EA
557-2PK2	1/2" CTS, 5/bag	C*	10	10	1.50 BG
557-3	3/4" CTS	B	100	1000	0.23 EA
557-3PK2	3/4" CTS, 5/bag	C*	10	10	1.58 BG
557-4	1" CTS	B	50	500	0.52 EA
NEW 557-4PK2	1" CTS, 5/bag	C*	10	10	2.80 BG
557-5	1 1/4" CTS	B	25	250	0.96 EA
NEW 557-5PK2	1 1/4" CTS, 5/bag	C*	10	10	5.00 BG
557-6	1 1/2" CTS	B	25	250	1.08 EA
NEW 557-6PK2	1 1/2" CTS, 5/bag	C*	10	10	5.60 BG
557-7	2" CTS	B	25	250	1.40 EA
NEW 557-7PK2	2" CTS, 5/bag	C*	10	10	7.20 BG
PLENUM SAFE™					
557F2	E84 1/2" CTS	B	100	1000	1.25 EA
557F3	E84 3/4" CTS	B	50	500	1.50 EA
557F4	E84 1" CTS	B	50	500	2.05 EA
557F5	E84 1 1/4" CTS	B	10	10	2.85 EA
557F6	E84 1 1/2" CTS	B	10	10	3.50 EA
557F7	E84 2" CTS	B	10	10	4.20 EA



EZ Glide™ Tube Insulator

- Ribs allow pipe to glide easier and more quietly when the pipe expands and contracts
- Split design allows for use after piping run
- Fits both 1 11/32" or 1 3/8" hole in metal or wood stud
- Compatible with copper, PEX or CPVC



558-2



Related Products

BiFolator p 275

Item No.	Description	Pkg	Min. Qty	Case Qty	List Price
558-2	1/2" CTS	B	50	500	0.36 EA
558-2PK2	1/2" CTS, 5/bag	C*	10	10	1.92 BG
558-3	3/4" CTS	B	50	500	0.37 EA
558-3PK2	3/4" CTS, 5/bag	C*	10	10	1.97 BG
558-4	1" CTS	B	25	250	0.38 EA

