

Bullet™**Stub Out & Air Chamber**

- Reduce job-site and shop costs such as measuring, cutting, cleaning, fluxing, assembling and soldering
- Precision spin closed ends are guaranteed leakproof
- Turn your variable job site costs into fixed job costs
- 1¼"-2" CTS Bullets available for quote
- Press-fitting compatible

Polished Nickel Plated

- Eliminates the need for sleeving or tinning
- Solders with standard flux and solder

Bracketed Stub Out

- Perfect for stubbing up through the floor for closets or lavs
- Square O Strap is crimped to tube 12" from each end

Item No.	Copper Type	CTS	Length	Pkg	Min. Qty	Case Qty	List Price
STANDARD							
622-M06	M	½"	6"	B	100	100	1.71 EA
622-M06PK	M	½"	6"	C*	20	20	2.09 EA
622-M08	M	½"	8"	B	100	100	2.23 EA
622-M08PK2	M	½"	8"	C*	10	10	2.56 EA
622-M10	M	½"	10"	B	100	100	2.85 EA
622-M12	M	½"	12"	B	100	100	3.22 EA
622-M12PK2	M	½"	12"	C*	10	10	3.58 EA
622-M15	M	½"	15"	B	100	100	3.92 EA
622-M18	M	½"	18"	B	100	100	4.78 EA
622-M24	M	½"	24"	B	50	50	6.65 EA
622-L06	L	½"	6"	B	100	100	2.21 EA
622-L06PK	L	½"	6"	C*	100	100	2.44 EA
622-L08	L	½"	8"	B	100	100	2.84 EA
622-L08PK	L	½"	8"	C*	100	100	3.13 EA
622-L10	L	½"	10"	B	100	100	3.58 EA
622-L12	L	½"	12"	B	100	100	4.25 EA
622-L15	L	½"	15"	B	100	100	5.25 EA
622-L18	L	½"	18"	B	100	100	6.20 EA
622-L24	L	½"	24"	B	50	50	8.76 EA
623-L06	L	¾"	6"	B	50	50	4.66 EA
623-L08	L	¾"	8"	B	50	50	5.88 EA
623-L12	L	¾"	12"	B	50	50	8.35 EA
623-L15	L	¾"	15"	B	50	50	10.31 EA
623-L18	L	¾"	18"	B	50	50	11.71 EA
623-L24	L	¾"	24"	B	50	50	18.21 EA
624-L08	L	1"	8"	B	30	30	8.75 EA
624-L12	L	1"	12"	B	30	30	12.29 EA
624-L15	L	1"	15"	B	30	30	15.48 EA
624-L18	L	1"	18"	B	30	30	17.73 EA
624-L24	L	1"	24"	B	30	30	24.41 EA
NICKEL PLATED							
622-L08N	L	½"	8"	B	25	25	8.84 EA
BRACKETED							
622-L24E	L	½"	24"	B	20	20	9.52 EA

Packaging Codes || B: bulk C: cut-case box *: individually bar-coded



622-L08



622-L08N



622-L24E



Bullets save time and reduce on-the-job costs. Perfect for any stub out or air chamber application.

Guaranteed Leakproof

Spin closed ends have **five** times the wall thickness of the copper tube. Each fitting is factory inspected.



SUPPLY

ACCESS

DRAINAGE

TESTING

SUPPORT

SPECIALTIES

TOOLS