

Vic®-End II End of Run Fitting

SERIES 67



SEE VICTAULIC PUBLICATION 10.01 FOR DETAILS



The No. 67, Vic®-End II, End of Run Fitting is the fast, easy, economical way to end a branch line. The fitting installs easily with standard FireLock® couplings and allows direct head connection, sprigs or drops.

Available in 1 ¼, 1 ½, 2 and 2 ½"/32-65 mm sizes, the fittings can be supplied with ½, ¾, or 1"/15, 20 or 25 mm female threaded (NPT) outlet (BSPT option available).

The 90° reducing outlet fitting is UL/ULC Listed and FM Approved for a maximum rated working pressure of 500 psi/3450 kPa.

MATERIAL SPECIFICATIONS

Housing: Ductile iron conforming to ASTM A-536, grade 65-45-12, painted Orange Enamel. Ductile iron conforming to ASTM A-395, grade 65-45-15, is available upon special request.

- **Optional:** Galvanized – hot dipped.

Outlet: NPT

- **Optional:** BSPT

DIMENSIONS, PERFORMANCE

| Nominal Size Inches/mm | | C to E Inches/mm | Approx. Weight Ea Lbs./Kg | Equivalent Feet/meters of pipe |
|---------------------------|---------|---------------------|------------------------------|-----------------------------------|
| 1 ¼ 32 | × ½ NPT | 2.38 | 1.4 | 2.8 |
| | | 61 | 0.6 | 0.9 |
| | × ¾ NPT | 2.38 | 1.4 | 2.8 |
| | | 61 | 0.6 | 0.9 |
| | | 2.38 | 1.4 | 2.8 |
| 1 ½ 40 | × ½ NPT | 2.50 | 1.6 | 2.9 |
| | | 64 | 0.7 | 0.9 |
| | × ¾ NPT | 2.50 | 1.6 | 2.9 |
| | | 64 | 0.7 | 0.9 |
| | | 2.50 | 1.6 | 2.9 |
| 2 50 | × ½ NPT | 2.75 | 1.7 | 4.0 |
| | | 70 | 0.8 | 1.2 |
| | × ¾ NPT | 2.75 | 1.7 | 4.0 |
| | | 70 | 0.8 | 1.2 |
| | | 2.75 | 1.7 | 4.0 |
| 2 ½ 65 | × ½ NPT | 3.00 | 2.0 | 5.7 |
| | | 76 | 0.9 | 1.7 |
| | × ¾ NPT | 3.00 | 2.0 | 5.7 |
| | | 76 | 0.9 | 1.7 |
| | | 3.00 | 2.0 | 5.7 |

JOB/OWNER

System No. _____
Location _____

CONTRACTOR

Submitted By _____
Date _____

ENGINEER

Spec Sect _____ Para _____
Approved _____
Date _____