AF-Ti/T Rod to Z Purlin Clip – AF146TI



- Used to support 1/4" and 3/8" threaded rod from purlin beam flanges 1/16" thru 1/4" thick
- Hammer-on or install from the floor with the VAFT tool
- Provides method for attaching rod to Z purlin





Part Number	AF146TI
Material	Spring Steel
Finish	CADDY ARMOUR
Hole Size (HS)	3/8"
Hole Type	Threaded
Flange Thickness (FT)	1/16" – 1/4"
Static Load (F)	100 lb
Certifications	cULus
Standard Packaging Quantity	100 рс
UPC	78285636406

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2016 Pentair All rights reserved Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.



