

larger image

- Standard coupling, Schedule 40
   National pipe threads in accordance with ANSI/ASME B1.20.1
   Fittings are right-hand threaded
- The fittings have a general conformance with dimensional standard MIL-DTL-52618-E
- Fittings are random tested at 120 pounds of air pressure under water, for a normal surface condition rating of 150 pounds of pressure
  Individual fittings are not marked with alloy or pressure data
  Fittings are not anodized
  Note: Extra-heavy couplings cannot be tested or certified for pressure rating

Dimensions available upon request

Please contact us for pricing information

Results 1 - 16 of 16

Item#	<u>Material</u>	Size	Threads/Inch	<u>Drill</u>	Outer Diameter (0.D.)	Length
1/8" Full Coupling: Standard, Schedule 40	6061-T6	1/8 in	27	R (0.339")	0.59 in	0.94 in
1/4" Full Coupling: Standard, Schedule 40	6061-T6	1/4 in	18	7/16" (0.438")	0.75 in	1.03 in
3/8" Full Coupling: Standard, Schedule 40	6061-T6	3/8 in	18	37/64" (0.578")	0.91 in	1.16 in
1/2" Full Coupling: Standard, Schedule 40	6061-T6	1/2 in	14	23/32" (0.719")	1.06 in	1.31 in
3/4" Full Coupling: Standard, Schedule 40	6061-T6	3/4 in	14	59/64" (0.922")	1.34 in	1.56 in
1" Full Coupling: Standard, Schedule 40	6061-T6	1 in	11-1/2	1-5/32" (1.156")	1.62 in	1.81 in
1-1/4" Full Coupling: Standard, Schedule 40	6061-T6	1-1/4 in	11-1/2	1-1/2" (1.5")	1.97 in	2.06 in
1-1/2" Full Coupling: Standard, Schedule 40	6061-T6	1-1/2 in	11-1/2	1-47/64" (1.734")	2.23 in	2.31 in
2" Full Coupling: Standard, Schedule 40	6061-T6	2 in	11-1/2	2-7/32" (2.219")	2.72 in	2.56 in
2-1/2" Full Coupling: Standard, Schedule 40	6061-T6	2-1/2 in	8	2-5/8" (2.625")	3.31 in	2.88 in
3" Full Coupling: Standard, Schedule 40	6061-T6	3 in	8	3-1/4" (3.25")	3.94 in	3.06 in
3-1/2" Full Coupling: Standard, Schedule 40	6061-T6	3-1/2 in	8	3-3/4" (3.75")	4.44 in	3.44 in
4" Full Coupling: Standard, Schedule 40	6061-T6	4 in	8	4-1/4" (4.25")	4.94 in	3.44 in
5" Full Coupling: Standard, Schedule 40	6061-T6	5 in	8	5-3/8" (5.375")	6.06 in	4.13 in
6" Full Coupling: Standard, Schedule 40	6061-T6	6 in	8	6-7/16" (6.4375")	7.19 in	4.13 in
8" Full Coupling: Standard, Schedule 40	6061-T6	8 in	8	8-7/16" (8.4375")	9.31 in	4.63 in