

SPF SERIES POLYESTER PLEATED FILTER

- MANUFACTURED FROM DURABLE POLYESTER
- WASHABLE AND REUSABLE
- BACTERIA AND CHEMICAL RESISTANCE

SPF SERIES POLYESTER PLEATED FILTER

LIQUATEC SPF SERIES POLYESTER PLEATED FILTER

Are manufactured from durable polyester to provide you with a superior pleated filter that is washable, reusable and durable. SPF Series Pleated filters are chemical and bacteria resistant, have a great dirt holding capacity and extend the time between filter changes.

LIQUATEC SPF SERIES POLYESTER PLEATED FILTER

Filters are suitable for a variety of uses and can be used in residential, commercial and industrial applications. The media is pleated around a polypropylene core for added strength and the ends are immersed in a thermo setting vinyl plastisol. Embedding and sealing each end of the pleat in this fashion fuses the three components together forming a unified end cap and gasket.



Liquatec



SPF SERIES POLYESTER PLEATED FILTER

MATERIALS OF CONSTRUCTION

• FILTER MEDIA	NON-WOVEN POLYESTER
• END CAPS	VINYL PLASTISOL
• CORE	POLYPROPYLENE
• TEMPERATURE RATING	40°F TO 125°F (4.4°C TO 51.7°C)


2.5" DIAMETER

ITEM #	DESCRIPTION	MICRON RATING NOMINAL	INITIAL ΔP (psi) @ FLOW RATE (GPM)
SPF-25-1001	2.5" X 9 7/8"	1	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-1005	2.5" X 9 7/8"	5	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-1010	2.5" X 9 7/8"	10	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-1020	2.5" X 9 7/8"	20	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-1030	2.5" X 9 7/8"	30	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-1050	2.5" X 9 7/8"	50	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-2001	2.5" X 20"	1	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-2005	2.5" X 20"	5	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-2020	2.5" X 20"	20	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-2030	2.5" X 20"	30	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-25-2050	2.5" X 20"	50	1 psi @ 10 gpm (0.1 bar @ 38 L/min)

4.5" DIAMETER

ITEM #	DESCRIPTION	MICRON RATING NOMINAL	INITIAL ΔP (psi) @ FLOW RATE (GPM)
SPF-45-1001	4.5" X 9 7/8"	1	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-45-1005	4.5" X 9 7/8"	5	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-45-1010	4.5" X 10"	10	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-45-1020	4.5" X 10"	20	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-45-1030	4.5" X 10"	30	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-45-1050	4.5" X 10"	50	1 psi @ 10 gpm (0.1 bar @ 38 L/min)
SPF-45-2001	4.5" X 20"	1	1 psi @ 20 gpm (0.1 bar @ 76 L/min)
SPF-45-2005	4.5" X 20"	5	1 psi @ 20 gpm (0.1 bar @ 76 L/min)
SPF-45-2010	4.5" X 20"	10	1 psi @ 20 gpm (0.1 bar @ 76 L/min)
SPF-45-2020	4.5" X 20"	20	1 psi @ 20 gpm (0.1 bar @ 76 L/min)
SPF-45-2030	4.5" X 20"	30	1 psi @ 20 gpm (0.1 bar @ 76 L/min)
SPF-45-2050	4.5" X 20"	50	1 psi @ 20 gpm (0.1 bar @ 76 L/min)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.



DISTRIBUTED BY:

Liquatec

P.O. Box 2637 Chino Hills, CA 91709 USA
sales@Liquatec.com
www.Liquatec.com