

high temperature

A TASTEFUL ADDITION TO ANY HOME

High Temperature and Stainless Steel

American Plumber[®] high temperature housings are available in many sizes and styles. Our housings are manufactured from durable materials with proven performance, including glass-reinforced nylon and stainless steel.

high temperature

- ★ Low-cost alternative to stainless and carbon steel housings
- ★ Durable glass-reinforced nylon construction
- ★ .75" NPT inlet/outlet and 10" length
- ★ Install unit after hot water heater to reduce suspended sediment

stainless steel

- ★ Ideal for a wide range of residential, commercial and industrial high temperature and high-pressure applications
- ★ Brushed 304 stainless steel sump with cast brass/nickel plated cap
- ★ .75" NPT inlet/outlet
- ★ Available in 10", 20" and 30" lengths

housings

						high temperature specifications					
model #	part #	sump	сар	I/O	overall dimensions	operating pressure (psi)	operating temp (deg. F)	optional accessories model #			
WH34	152009	red	red	.75" NPT	5.125" x 12.125"	30-125	30-160	WMB34, WW34			

stainless steel specifications

model #	part #	sump	сар	I/O	overall dimensions	operating pressure (psi)	operating temp (deg. F)	optional accessories model #
ST-1	156017-02	304 stainless steel	brass/nickel plated	.75" NPT	4.125" x 12.875"	30-250	40-300	156037
ST-2	156018-02	304 stainless steel	brass/nickel plated	.75" NPT	4.125" x 22.75"	30-250	40-300	156037
ST-3	156019-02	304 stainless steel	brass/nickel plated	.75" NPT	4.125" x 32.375"	30-250	40-300	156037

NOTE: Uses standard 10" double open end cartridges. One cartridge for 10" length, two cartridges for 20" length and three cartridges for 30" length.





5730 NORTH GLEN PARK ROAD MILWAUKEE, WISCONSIN 53209 Phone 800.645.5428 • Fax 888.588.9388 www.americanplumber.com