


PRODUCT SPECIFICATIONS

Malleable Iron Screwed Fittings - Class 150

BLACK

GALVANIZED



COUPLING

Nominal Size	Dimension A	Approx. Wt. Each
<i>In. (mm)</i>	<i>In. (mm)</i>	<i>Lbs. (kg)</i>
1/8	0.96	0.05
6	24.38	0.02
1/4	1.06	0.08
8	26.92	0.04
3/8	1.16	0.12
10	29.46	0.05
1/2	1.34	0.17
15	34.04	0.08
3/4	1.52	0.27
20	38.61	0.12
1	1.67	0.43
25	42.42	0.20
1 1/4	1.93	0.65
32	49.02	0.29
1 1/2	2.15	0.86
40	54.61	0.39
2	2.53	1.35
50	64.26	0.61
2 1/2	2.88	2.33
65	73.15	1.06
3	3.18	3.36
80	80.77	1.52
4	3.69	5.59
100	93.73	2.54

MATERIAL SPECIFICATIONS

Dimensional: Fittings: ASME B16.3
Unions: ASME B16.39
Bushings/Plugs: ASME B16.14

Material: ASTM A-197

Galvanizing: ASTM A-153 (Hot Dip Galvanizing)

Threading*: ASME B1.20.1

Pressure Rating: Fittings: ASME B16.3
Unions: ASME B16.39
Bushings/Plugs: ASME B16.14

Pressure Testing: All malleable iron fittings are tested for through wall porosity using an air under water process.

Agency Approvals: All malleable iron fittings and unions are UL Listed and FM Approved.

* British Standard threading per BS 21 available upon request.



For Listings/Approval Details and Limitations, visit our website at www.anvilintl.com or contact an Anvil® Sales Representative.

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.