


PRODUCT
SPECIFICATIONS

Malleable Iron Screwed Fittings - Class 150

BLACK

GALVANIZED



CAP

Nominal Size	Dimension A	Approx. Wt. Each
In. (mm)	In. (mm)	Lbs. (kg)
1/4▲ 6	0.53 13.46	0.03 0.01
1/4▲ 8	0.63 16.00	0.05 0.02
3/8▲ 10	0.74 18.80	0.07 0.03
1/2 15	0.87 22.10	0.11 0.05
3/4 20	0.97 24.64	0.18 0.08
1 25	1.16 29.46	0.30 0.14
1 1/4 32	1.28 32.51	0.44 0.20
1 1/2 40	1.33 33.78	0.55 0.25
2 50	1.45 36.83	0.85 0.39
2 1/2 65	1.70 43.18	1.49 0.68
3 80	1.80 45.72	2.20 1.00
3 1/2 90	1.90 48.26	3.02 1.37
4 100	2.08 52.83	3.79 1.72
6 150	2.55 64.77	8.77 3.98

▲ - Supplied in Steel only (Black and Galvanized).

MATERIAL SPECIFICATIONS

Dimensional: Fittings: ASME B16.3

Unions: ASME B16.39

Bushings/Plugs: ASME B16.14

Material: ASTM A-197

Galvanizing: ASTM A-153 (Hot Dip Galvanizing)

Threading*: ASME B1.20.1

Pressure Rating: Fittings: ASME B16.3

Unions: ASME B16.39

Bushings/Plugs: ASME B16.14

Pressure Testing: All malleable iron fittings are tested for through wall porosity using an air under water process.

Agency Approvals: All malleable iron fittings and unions are UL Listed and FM Approved.

* British Standard threading per BS 21 available upon request.



For Listings/Approval Details and Limitations,
visit our website at www.anvilintl.com or
contact an Anvil® Sales Representative.

PRODUCT SPECIFICATIONS

Steel Screwed Fittings

All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.

BLACK



GALVANIZED



Nominal Pipe Size		Cap Length		Nominal Width Across Flats		Unit Weight	
NPS	DN	in	mm	in	mm	lbs	kg
1/8	6	0.563	14	0.560	14	0.02	0.01
1/4	8	0.844	22	0.625	16	0.03	0.01
3/8	10	0.813	21	0.870	22	0.06	0.03



For Listings/Approval Details and Limitations,
visit our website at www.anvilint.com or
contact an Anvil® Sales Representative.