




4515 East 139th Street
Grandview, MO 64030
(800) 362-9055
Fax (800) 362-1463
www.PRIER.com

C-134/234 Series Freezeless Wall Hydrant

Application

Original Heavy Duty Style



- Residential
- Freezeless
- Slim Seat
- Satin Nickel Plated



PRIER C-134 provides a year round source of water to areas of structures that are subject to freezing temperatures. The hydrant valve is connected to the supply piping in the heated portion of the structure, eliminating the possibility of freezing. Ordering the C-234 gives you the same style hydrant but with a vandal proof extended lockshield with operating key.

The PRIER C-134 is the original freezeless hydrant that is made in the same heavy pattern fashion that made it famous. It is available from stock in lengths from Close Coupled to 24". Longer sizes are available upon request.

Features

- C-UPC approved
- Integral cast flange with built-in drainage pitch
- Enclosed screw holes easily secure mounting screws
- Solid brass body, valve stem cap, seat and stem ends
- Satin nickel plated body maintains attractive finish
- Stainless steel seat washer screw and handle screw
- Powder coated cast aluminum handle
- Durable ACME threads secure stem at seat end
- Lock shield cap for stronger valve design
- AFG teflon with graphite packing for easy maintenance
- Standard "OO" size seat washer
- Spout aligning mark
- Slim seat inlet for easier installation

Ordering

C-134D10

Operator
1- Handle Operated
2- Vandal Proof Lockshield

Inlet

D- $\frac{1}{2}$ " MPT x $\frac{1}{2}$ " SWT
F- $\frac{3}{4}$ " MPT x $\frac{3}{4}$ " SWT
S- $\frac{1}{2}$ " SWT x $\frac{3}{4}$ " Push-On
T- $\frac{3}{4}$ " MIP x $\frac{1}{2}$ " FIP
W- $\frac{1}{2}$ " Wirsbo PEX®
C- $\frac{1}{2}$ " CPVC Glue-In
X- $\frac{1}{2}$ " Crimp PEX
FX- $\frac{3}{4}$ " Crimp PEX
FW- $\frac{3}{4}$ " Wirsbo PEX®

Length
CC- Close Coupled
04- 4" Insertion
06- 6" Insertion
08- 8" Insertion
10- 10" Insertion
12- 12" Insertion
14- 14" Insertion
16- 16" Insertion
18- 18" Insertion
20- 20" Insertion
22- 22" Insertion
24- 24" Insertion
XX- Special Size

Inlet Styles



D Style
1/2" MIP x 1/2" SWT



S Style
1/2" SWT x 3/4" Push-On




X Style
1/2" Crimp PEX



W Style
1/2" Wirsbo® PEX



C Style
1/2" CPVC Glue-In



T Style
3/4" MIP x 1/2" FIP



F Style
3/4" MIP x 3/4" SWT



FX Style
3/4" Crimp PEX




FW Style
3/4" Wirsbo® PEX



4515 East 139th Street
Grandview, MO 64030
(800) 362-9055
Fax (800) 362-1463
www.PRIER.com

Replacement Parts

Replacement Stems



ID	Part No.	Description
1	See Below	Stem Assembly, Contains: 1, 4
2	300-1008	Valve Stem Cap
3	C-134KT-805	Oval Handle and Screw Kit
4	C-134KT-802	Seat Washer Replacement Kit (00 Beveled)
5	C-134KT-803	Stem Packing Replacement Kit
6	310-1015	Valve Stem Cap for Loose Key
7	390-1001	Stem Packing Only
8	C-108KT-808	Oval Style Key on Lanyard
	C-134KT-804	Loose Key Conversion Kit Contains: 5, 6, 8
	C-134KT-807	C-134 Overhaul Kit Contains: 3, 4, 5



G Style Manufactured April 2013 - Present

Part No.	Style	Description	Stem Length
P-231-11CC	G	Close Coupled Stem for C-134 Hydrant	4 $\frac{3}{8}$ " OAL
P-231-1104	G	Stem for 4" C-134 Hydrant	6 $\frac{7}{8}$ " OAL
P-231-1106	G	Stem for 6" C-134 Hydrant	8 $\frac{7}{8}$ " OAL
P-231-1108	G	Stem for 8" C-134 Hydrant	10 $\frac{7}{8}$ " OAL
P-231-1110	G	Stem for 10" C-134 Hydrant	12 $\frac{7}{8}$ " OAL
P-231-1112	G	Stem for 12" C-134 Hydrant	14 $\frac{7}{8}$ " OAL
P-231-1114	G	Stem for 14" C-134 Hydrant	16 $\frac{7}{8}$ " OAL
P-231-1116	G	Stem for 16" C-134 Hydrant	18 $\frac{7}{8}$ " OAL
P-231-1118	G	Stem for 18" C-134 Hydrant	20 $\frac{7}{8}$ " OAL
P-231-1120	G	Stem for 20" C-134 Hydrant	22 $\frac{7}{8}$ " OAL
P-231-1122	G	Stem for 22" C-134 Hydrant	24 $\frac{7}{8}$ " OAL
P-231-1124	G	Stem for 24" C-134 Hydrant	26 $\frac{7}{8}$ " OAL
P-231-11US	G	*Universal Replacement Stem for C-134 Hydrant	Up to 16 $\frac{7}{8}$ " OAL

****For the old style C-134 Series** wall hydrant stems, see C-134 Series retired style spec sheet at www.PRIER.com. PRIER universal stems are replacement stems for any size from close coupled to 14". They require cutting the rod to proper length and soldering the brass stem end to the rod as directed in instructions.