C-534 Commercial Wall Hydrant

With Integral P-004 Vacuum Breaker • Commercial • Freezeless • Anti-Siphon • Double Check Valve

PRIER C-534 provides a year round source of water to areas of structures that are subject to freezing tempera tures. The hydrant valve is connected to the supply piping in the heated portion of the structure, eliminatin the possibility of freezing. To assure freeze protection, the hydrant will drain even with the hose attached an under pressure without sprayback!

The C-534 combines freezeless hydrant features with self-draining, anti-siphon and two backflow check valves. The vacuum breaker/backflow presenter provides protection against cross-connection of the potable wate supply, while venting to eliminate any vacuum. The C-534 has an extended vandal proof lockshield with loos key. Upon closure, valve drains even with closed end hose attached. No special installation tools are required

XX- Special Size

- ASSE 1052 and C-UPC approved
- Double check valve and anti-siphon vacuum breaker
- Drains automatically with hose attached
- Integral cast flange with built-in drainage pitch
- Solid brass body, valve stem cap, seat and stem ends
- Satin nickel plated body, cap and vacuum breaker
- Durable ACME threads secure stem at seat end
- Compact and powder coated cast aluminum handle
- Metal collar covers drainage holes and protects against insect nesting while closing under pressure
- Multiple vent holes ensure proper draining
- Cycle tested to simulate 25 years minimum service
- Patent protected
- Field testable as required by ASSE 1052

C-534D10 Length Inlet D- ½" MPT x ½" SWT CC- Close Coupled 04-4" Insertion F- 1/4" MPT x 1/4" SWT 06-6" Insertion T-34" MIP x 35" FIP 08-8" Insertion X- 1/2" Crimp PEX 10-10" Insertion 12-12" Insertion 14-14" Insertion 16-16" Insertion 18-18" Insertion 20-20" Insertion 22-22" Insertion 24-24" Insertion

