

FIBERGLASS

300 lbs. TYPE IA
load capacity*

TWIN FRONT LADDER FM1500 SERIES



FM1506

SHOX

SHOX™ - superior
impact absorption

Da Boot™
Patent # 7,000,731 B2

**Inside spreader
braces**

**Double-rivet step
construction**

**Heavy gauge
steel hinges**



MODEL	LADDER SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FM1503	3'	3"	18 1/16"	30 1/8"	16	3.4'
FM1504	4'	3"	19 1/16"	37 1/2"	19	4.9'
FM1505	5'	3"	21 1/16"	44 7/8"	22	6.5'
FM1506	6'	3"	22 3/16"	52 3/8"	27	8.4'
FM1507	7'	3"	24 1/16"	59 1/16"	30	10.2'
FM1508	8'	3"	25 3/16"	67 1/8"	34	12.3'
FM1510	10'	3"	28 3/16"	81 1/16"	44	17.3'
FM1512	12'	3"	31 3/16"	96 3/4"	62	23.1'



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



BOTH SIDES of twin front ladders can be used simultaneously by one person plus materials.
Therefore the duty rating for this ladder is PER SIDE.

FIBERGLASS

250 lbs. TYPE I
load capacity*

TWIN FRONT LADDER FM2000 SERIES



FM2006

**Aluminum angle
slip-resistant
rubber feet**

**Heavy gauge
steel hinges**

**Double-rivet
step construction**

**Pinch-resistant
spreader braces**



MODEL	LADDER SIZE	STEP SIZE	BOTTOM WIDTH	APPROX. SPREAD	APPROX. WT. (LBS)	APPROX. CUBES
FM2004	4'	3"	18 3/4"	37 1/4"	17	4.6'
FM2006	6'	3"	21 3/4"	52"	24	8.1'
FM2008	8'	3"	24 3/4"	66 13/16"	34	12'
FM2010	10'	3"	27 3/4"	81 5/8"	45	16.8'
FM2012	12'	3"	30 3/4"	96 7/16"	55	22.1'



ANSI
Meets or exceeds requirements
of American National Standards Institute
ANSI A14.5



BOTH SIDES of twin front ladders can be used simultaneously by one person plus materials.
Therefore the duty rating for this ladder is PER SIDE.