

1/4" One Way Shut-Off

3 Series



INDUSTRIAL INTERCHANGE

See Specifications & Performance Data on Page 8.

PLUGS



FEMALE THREAD

CAT. NO.

1/8 FPT
1/4 FPT
3/8 FPT


13-3 ■
11-3 ■ ●
15-3



MALE THREAD

1/8 MPT
1/4 MPT
3/8 MPT

12-3 ■ ●
10-3 ■ ●
14-3 ■



HOSE STEM (Require Hose Clamps)

1/4 I.D.
5/16 I.D.
3/8 I.D.

16-3 ■
165-3
17-3 ■



PUSH-ON HOSE STEM

1/4 I.D.
3/8 I.D.

51-3
71-3



REUSABLE HOSE CLAMP

ID OD
3/16 x 3/8
3/16 x 7/16



1/4 x 1/2
1/4 x 9/16
1/4 x 5/8
1/4 x 11/16

PB3-3 ■
PB5-3 ■
PB7-3 ■ ●
PB9-3 ■

5/16 x 9/16
5/16 x 5/8

PC5-3
PC7-3

3/8 x 5/8
3/8 x 11/16
3/8 x 3/4
3/8 x 13/16

PD7-3
PD9-3
PD11-3
PD13-3

SOCKETS

NEW!



MANUAL
SLEEVE GUARD



MANUAL
INDUSTRIAL



AUTOMATIC
COMPLIES WITH A-A-59439



SAFETY

CAT. NO.

CAT. NO.

CAT. NO.

CAT. NO.

SG2803
SG3003
SG3203

2803 ●
3003 ●
3203 ●

FM2803
FM3003
FM3203

SV3003
SV3203

SG2903
SG3103
SG3303

2903 ●
3103 ●
3303 ●

FM2903
FM3103
FM3303

SV3103
SV3303

SG3603
SG3703

3603 ●
3653
3703 ●

FM3603
FM3653
FM3703

SV3603
SV3703

SG1513
SG1713

1513
1713

FM1513
FM1713

SAA-3
SAO-3

FMSAA-3
FMSAO-3

SB3-3
SB5-3
SB7-3 ●
SB9-3

FMSB3-3
FMSB5-3
FMSB7-3
FMSB9-3

SC5-3
SC7-3

FMSC5-3
FMSC7-3

SD7-3
SD9-3
SD11-3
SD13-3

FMSD7-3
FMSD9-3
FMSD11-3
FMSD13-3

SERIES 3
PLUG
ACTUAL SIZE

SERIES 3
SOCKET
ACTUAL SIZE

BALL CHECK

1/4 MPT
3/8 MPT

10-3G ■ ●
14-3G ■



Ball check plugs eliminate hose whip at disconnect by checking the rapid flow of downstream exhaust air.

VALVE CORE

1/4 MPT

10-3D ■



Sockets with modified valves are recommended for use with valve core plugs. Suffix-D to socket Cat. No.

SWIVEL (Free Swivel Under Pressure)

1/8 MPT
1/4 MPT
3/8 MPT

12S-3
10S-3
14S-3



NEW!

■ Available In Brass – Suffix B
● Available In 303 Stainless – Suffix S/S

FOSTER
MANUFACTURING COMPANY