

data sheet



STORZ CONNECTIONS

FUNCTION: Used as an auxiliary inlet connection to supplement the fire protection water supply.

Provides a range from 500 /1892 to 1000 /3785 GPM/lpm per inlet.

A Storz connection provides a means of rapid supply through large diameter hose.

FURNISHED: Hard coated aluminum with Storz on one end and female national pipe thread on the other.

STRAIGHT RIGID STORZ




Lightweight aluminum alloy - hardcoated to reduce corrosion and abrasion

Lever type lock to prevent fittings from twisting apart during use

500 to 1000 GPM per inlet

Available with screen



STRAIGHT RIGID THREAD WITH ROCKER LUG

6510252: 4" storz x 2.5" NPT (F) rocker lug

6510220: 4" storz x 4" NPT (F) rocker lug

6510233: 5" storz x 4" NPT (F) rocker lug

6510222: 5" storz x 6" NPT (F) rocker lug

**Meets NFPA 1963 edition
1998 Standard for fire hose
connections**

size	depth	height
4" x 4"	2-1/4"	6-1/8"
5" x 4"	3-1/8"	7-11/16"
5" x 6"		

Installation

Installation of a Storz fitting is accomplished with normal installation methods used in the fire sprinkler industry.

Make sure the female threads of the Storz fitting and the male pipe end are free of contaminants and debris.

Apply a suitable thread sealant to the threads of the male pipe end such as Tuf-Glide or Superdope.

Thread the Storz fitting on to the male pipe end until hand tight.

Tighten the Storz type fitting one additional turn using a specially designed spanner wrench to prevent damage to the outer surfaces of the fitting.

STORZ CAP WITH CHAIN




Lightweight aluminum alloy - hardcoated to reduce corrosion and abrasion

6510290: 4" storz cap with chain

6510291: 5" storz cap with chain

6510293: 6" storz cap with chain

size	depth	height
4"	2-1/8"	6-1/8"
5"	2-1/2"	7-11/16"



STORZ SCREEN

Stainless steel mesh screen

Prevents vandalism & plugging



6510220S: 4" storz x 4" NPT (F) with screen

6510221S: 5" storz x 4" NPT (F) with screen

6510232S: 4" storz x 4" 30° degree elbow with screen

6510233S: 5" storz x 4" 30° elbow with screen

6510229S: 6" storz x 5" 30° elbow with screen

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 800-854-1015
OR LOG ONTO ARGCO.COM**

data sheet



STORZ CONNECTIONS

FUNCTION: Used as an auxiliary inlet connection to supplement the fire protection water supply.

Provides a range from 500 /1892 to 1000 /3785 GPM/lpm per inlet.

A Storz connection provides a means of rapid supply through large diameter hose.

FURNISHED: Hard coated aluminum with Storz on one end and female national pipe thread on the other.




30° ELBOW STORZ

6510232: 4" storz x 4" swivel IPT (F) 30 degree elbow

6510233: 5" storz x 4" swivel IPT (F) 30 degree elbow

6510230: 5" storz x 6" swivel IPT (F) 30 degree elbow

size	length	height
4" x 4"	7-12"	7-5/8"
5" x 4"	9-5/32"	8-3/8"
5" x 6"	8-5/8"	8"



Installation

Installation of a Storz fitting is accomplished with normal installation methods used in the fire sprinkler industry.

Make sure the female threads of the Storz fitting and the male pipe end are free of contaminants and debris.

Apply a suitable thread sealant to the threads of the male pipe end such as Tuf-Glide or Superdope.

Thread the Storz fitting on to the male pipe end until hand tight.

Tighten the Storz type fitting one additional turn using a specially designed spanner wrench to prevent damage to the outer surfaces of the fitting.

STORZ CAP WITH CHAIN




Lightweight aluminum alloy - hardcoated to reduce corrosion and abrasion

6510290: 4" storz cap with chain

6510291: 5" storz cap with chain

6510293: 6" storz cap with chain

size	depth	height
4"	2-1/8"	6-1/8"
5"	2-1/2"	7-11/16"



STORZ SCREEN

Stainless steel mesh screen

Prevents vandalism & plugging



6510220S: 4" storz x 4" NPT (F) with screen

6510221S: 5" storz x 4" NPT (F) with screen

6510232S: 4" storz x 4" 30° degree elbow with screen

6510233S: 5" storz x 4" 30° elbow with screen

6510229S: 6" storz x 5" 30° elbow with screen

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

**FOR MORE INFORMATION CALL ARGCO AT 800-854-1015
OR LOG ONTO ARGCO.COM**