data sheet

<u>ARGCO</u>




Fire Sprinkler Pressure Gauges



0-300 psi water

0-300 psi air

0-300 psi air/water



Application: Fluid medium which does not clog connection port or corrode copper alloy.

Specifically designed for the fire sprinkler industry.

Size: 4" (100 mm)

Accuracy $\pm 3/2/3\%$ of span (ASME B40.1 Grade B)

Working Range

Steady: 3/4 of full scale value Fluctuating: 2/3 of full scale value Short time: full scale value

Operating Temperature

Ambient: -40°F to 140°F (-40°C to 60°C)

Media: max. 140°F (+60°C)

Temperature Error

Additional error when temperature changes from reference temperature of 68°F (20°C) +0.4% for every 18° F (10°C) rising or falling. Percentage of span.

Standard Features

Connection Material: copper alloy

Lower mount (LM) - not available for 11/2" size

1/4" NPT limited to wrench flat area

Bourdon Tube: Material: copper alloy C-type **Movement:** Copper alloy, silicone dampened

Dia: White plastic with stop pin - black & red lettering

Pointer: Black aluminum **Case**: Black polycarbonate

Approvals

UL listed (UL-393) FM approved

Meets NFPA 25 Standards

Standard Scale

PSI

Window

Acrylic, ultrasonically welded to case

Standard Series • Type 110.10sp

Order Options

water air/water air

The information contained herein is produced in good faith and is believed to be reliable but is for guidance only. ARGCO and its agents cannot assume liability or responsibility for results obtained in the use of its product by persons whose methods are outside or beyond our control. It is the user's responsibility to determine the suitability of any of the products, methods of use, or preparation prior to use, mentioned in our literature. It is the user's responsibility to observe and adapt such precautions as may be advisable for the protection of personnel and property in the handling and use of any of our products.

CERTIFICATE OF COMPLIANCE

Wika Instrument, LP Certifies that the products specified herein have been manufactured in accordance with established technical standards, and comply with the requirements of ANSI/ASME B40.100



Tel: (+1) 770-513 8200 Fax: (+1) 770-338 5118 http://www.wika.com info@wika.com

CUSTOMER Allied Rubber & Gasket Co

5400 S 66 St

FORT SMITH, AR 72903

CUSTOMER P.O. NO. 41945

ORDER NO. 2018647

ORDER DATE 04/14/2015

CUSTOMER P/N 6510161

WIKA P/N 4276192

DESCRIPTION 111.10SP 4 300IPS 1/4 L WATER ARGCO

QUANTITY 4,800

AUTHORIZED SIGNATURE Burnadette & Biggs

DATE 04/15/2015

