



COPPER COATED GROUND RODS

Copper Coated Ground Rods



- Galvan's copper coated rods have a heavy, uniform coating of copper metallurgically bonded to a rigid steel core.
- Color-coded to reduce errors.
- UL Listed rods have 10-mil minimum copper plating. UL/RUS models have 13-mil minimum of copper but 10-mil coating is acceptable.
- Galvan manufactures copper-coated rods under patent 6,527,934.
- Rods less than eight feet or less than 10 mils of copper, do not meet UL requirements, nor the NEC Code.
- RUS now accepts 10 mils of copper. Please see page 5.
- Made in USA.

Catalog Number	Diameter X Length	Actual Diameter Inches	Matching Threadless Coupling	Sub & Master Bundle	Wt. Per 100	NAED UPC No. 632591-	Color Code
5005	1/2" x 5'	0.471-0.481	—	5 / 100	275	61125-1	Green
5006	1/2" x 6'	0.471-0.481	—	5 / 100	330	61126-8	Green
5008L*	1/2" x 8'	0.500-0.510	50-TC	5 / 100	550	61138-1	Orange
5009L*	1/2" x 9'	0.500-0.510	50-TC	5 / 100	—	—	N/A
5010L*	1/2" x 10'	0.500-0.510	50-TC	5 / 100	690	61130-5	Orange
6254-10M	5/8"x4'	.555-.565	60-TC	5/100	340	—	Copper
6255-10M	5/8" x 5'	0.555-0.565	60-TC	5 / 100	430	61585-3	Red
6256	5/8" x 6'	0.539-0.549	—	5 / 100	510	61586-0	Red
6256-10M	5/8" x 6'	0.555-0.565	60-TC	5 / 100	510	—	Copper
6258*	5/8" x 8'	0.555-0.565	60-TC	5 / 100	680	61588-4	Copper
6258G13**	5/8" x 8'	0.561-0.571	60-TC	5 / 100	700	61217-3	Yellow
6260G13**	5/8" x 10'	0.561-0.571	60-TC	5 / 100	860	61218-0	Yellow
6260*	5/8" x 10'	0.555-0.565	60-TC	5 / 100	860	61580-8	Copper
6260-CFE*	5/8" x 10'	0.625-0.635	—	—	—	—	Copper
6262*	5/8" x 12'	0.555-0.565	60-TC	5	1030	61474-0	Copper
6265*	5/8" x 15'	0.555-0.565	60-TC	5	1290	61475-7	Copper
7508*	3/4" x 8'	0.673-0.683	70-TC	5 / 50	1000	61548-8	Black
7510*	3/4" x 10'	0.673-0.683	70-TC	5 / 50	1255	61340-8	Black
7512*	3/4" x 12'	0.673-0.683	70-TC	5	1506	61476-4	Black
7515*	3/4" x 15'	0.673-0.683	70-TC	5	1880	61477-1	Black
1010*	1" x 10'	0.907-0.917	GRC-100GP	3 / 50	2248	61440-5	N/A

Notes: * These rods are UL Listed

** These rods meet UL & RUS (13 mils minimum of copper). RUS now accepts 10 mils of copper. Refer to page 5 for NEC, NESC and RUS code requirements.

Copper Coated Sectional Ground Rods



- Threaded on both ends.
- Listed to UL-467 specification.
- RUS now accepts 10 mils of copper. Please see page 5.
- Rods less than eight feet or less than 10 mils of copper, DO NOT meet UL requirements, nor the NEC Code.
- Made in USA.

Catalog Number	Diameter X Length	Actual Diameter Inches	Matching Threadless Coupling	Sub & Master Bundle	Wt. Per 100	NAED UPC No. 632591-	Color Code
5008LS*	1/2" x 8'	0.500-0.510	50-LC	5 / 100	550	63138-9	Orange
5010LS*	1/2" x 10'	0.500-0.510	50-LC	5 / 100	690	63130-3	Orange
6258S*	5/8" x 8'	0.555-0.565	60-C	5 / 100	680	63588-2	Copper
6258G13S**	5/8" x 8'	0.555-0.565	60-C	5 / 100	—	—	Copper
6260S*	5/8" x 10'	0.555-0.565	60-C	5 / 100	860	63580-6	Copper
6260G13S**	5/8" x 10'	0.555-0.565	60-C	5 / 100	—	—	Copper
7505S	3/4" x 5'	0.673-0.683	70-C	—	—	—	N/A
7506S	3/4" x 6'	0.673-0.683	70-C	—	—	—	N/A
7506G13S**	3/4" x 6'	0.673-0.683	70-C	—	—	—	N/A
7508S*	3/4" x 8'	0.673-0.683	70-C	5-50	1000	63348-2	Black
7510S*	3/4" x 10'	0.673-0.683	70-C	5-50	1255	63340-6	Black
1010S*	1" x 10'	0.907-0.917	80-C	25	2250	63440-3	N/A

Notes: * These rods are UL Listed

** These rods meet UL & RUS (13 mils minimum of copper). RUS now accepts 10 mils of copper. Refer to page 5 for NEC, NESC and RUS code requirements.