



TEMP. RANGE:  
-40F TO 392F (-40C TO 200C)

INCLUDES:  
(1) 1.5V BATTERY

**MA-PDT392B (1/PKG.)**  
**DIGITAL POCKET THERMOMETER**  
**MA-PDT392B-12 (12/CS)**  
**DIGITAL POCKET THERMOMETER**

F/C SWITCHABLE - STAINLESS STEEL STEM - ON/OFF SWITCH -  
AUTO OFF - HIGH/LOW TEMPERATURE RECALL -  
DATA HOLD - WATER RESISTANCE



INCLUDES:  
(1) 1.5V BATTERY

TEMP. RANGE:  
-40F TO 392F  
(-40C TO 200C)

**MA-RT818**  
**DIGITAL POCKET THERMOMETER**  
**WITH LARGE DISPLAY**

F/C SWITCHABLE - STAINLESS STEEL STEM - ON/OFF SWITCH -  
AUTO OFF - HIGH/LOW TEMPERATURE RECALL -  
DATA HOLD - WATER RESISTANCE



INCLUDES:  
(1) AAA BATTERY

TEMP. RANGE:  
32F TO 122F (0 TO 50C)  
HUMIDITY:  
20% TO 95% RH

**MA-RT819**  
**BIG DIGIT PEN SHAPE**  
**HYGRO THERMOMETER**

F/C SWITCHABLE - MAX/MIN READING MEMORY -  
DUAL DISPLAY FOR TEMPERATURE & HUMIDITY



**ADJUSTABLE POCKET**  
**THERMOMETERS**  
WITH CASE AND 5" STEM

**MA-PT160** (12/CASE)

**MA-PT160B** (1/PKG)

1" DIAL -40F TO 160F

**MA-PT220** (12/CASE)

**MA-PT220B** (1/PKG)

1" DIAL 0 TO 220F

**MA-PT550** (12/CASE)

1" DIAL 50F TO 550F

**MA-PT70C** (12/CASE)

1" DIAL -40C TO 70C

**MA-PT110C** (12/CASE)

1" DIAL -10C TO 110C

**MA-PT138160** (12/CASE)

1-3/8" DIAL -40F TO 160F

**MA-PT138220** (12/CASE)

1-3/8" DIAL 0 TO 220F

**MA-PT134160** (1/PKG)

1-3/4" DIAL -40F TO 160F

**MA-PT134220** (1/PKG)

1-3/4" DIAL 0 TO 220F



**MA-ST200**  
**PIPING THERMOMETER**

TEMPERATURE RANGE:  
-50F TO 250F (-40C TO 120C)

2 DIAL SPRING MOUNTED OR  
SURFACE THERMOMETER

DESIGNED TO MEASURE SURFACE  
TEMPERATURES OF PIPES,  
CYLINDERS, SPINDLES, ETC. BETWEEN  
3/4"OD TO 6"OD

KIT INCLUDES:  
2 CLASP AND 3 DIFFERENT SIZES OF  
HIGHLY RESILIENT STAINLESS STEEL

**POCKET STICK THERMOMETER**



**MA-PS120** -40F TO 160F (12/CTN)

**MA-PS220** 0F TO 220F (12/CTN)

FAHRENHEIT SCALE - 5" IN LENGTH - SPIRIT FILLED