


Tube to Female Pipe



Female Elbow (FE)

Griplok Part #	T Tube O.D.	P-NPT Female Pipe Size	A	Bx	By	C	D	E Minimum Opening	F	G	H
G2FE2	1/8	1/8	1.03	0.71	0.75	0.66	0.56	0.09	0.41	7/16	1/2
G2FE4	1/8	1/4	1.14	0.82	0.88	0.66	0.56	0.09	0.59	7/16	3/4
G3FE2	3/16	1/8	1.05	0.74	0.75	0.68	0.59	0.12	0.39	1/2	1/2
G4FE2	1/4	1/8	1.10	0.77	0.75	0.74	0.64	0.19	0.39	9/16	1/2
G4FE4	1/4	1/4	1.21	0.88	0.88	0.74	0.64	0.19	0.59	9/16	3/4
G4FE6	1/4	3/8	1.29	0.96	0.88	0.74	0.64	0.19	0.59	9/16	7/8
G4FE8	1/4	1/2	1.40	1.07	1.12	0.74	0.64	0.19	0.78	9/16	1
G5FE2	5/16	1/8	1.13	0.84	0.75	0.73	0.64	0.25	0.39	5/8	9/16
G5FE4	5/16	1/4	1.20	0.91	0.88	0.73	0.64	0.25	0.59	5/8	3/4
G6FE2	3/8	1/8	1.25	0.91	0.75	0.81	0.71	0.28	0.39	11/16	5/8
G6FE4	3/8	1/4	1.28	0.94	0.88	0.81	0.71	0.28	0.59	11/16	3/4
G6FE6	3/8	3/8	1.36	1.02	0.88	0.81	0.71	0.28	0.59	11/16	7/8
G6FE8	3/8	1/2	1.47	1.13	1.12	0.81	0.71	0.28	0.78	11/16	1
G8FE4	1/2	1/4	1.49	1.02	0.88	0.93	0.97	0.41	0.59	7/8	13/16
G8FE6	1/2	3/8	1.49	1.02	0.88	0.93	0.97	0.41	0.59	7/8	7/8
G8FE8	1/2	1/2	1.60	1.13	1.12	0.93	0.97	0.41	0.78	7/8	1
G10FE6	5/8	3/8	1.54	1.10	0.88	0.90	1.00	0.50	0.59	1	15/16
G10FE8	5/8	1/2	1.61	1.17	1.12	0.90	1.00	0.50	0.78	1	1-1/16
G12FE8	3/4	1/2	1.61	1.17	1.12	0.90	1.00	0.62	0.78	1-1/8	1-1/16
G12FE12	3/4	3/4	1.80	1.36	1.25	0.90	1.00	0.62	0.81	1-1/8	1-3/8
G14FE12	7/8	3/4	1.80	1.36	1.25	0.90	1.06	0.72	0.81	1-1/4	1-3/8
G16FE12	1	3/4	2.01	1.45	1.25	1.12	1.31	0.88	0.81	1-1/2	1-3/8
G16FE16	1	1	2.19	1.63	1.50	1.12	1.31	0.88	1.00	1-1/2	1-5/8

Finger-tight assembly dimensions (shown in inches) are for reference only and subject to change.

When ordering specify material designator with part number (see page 3 for complete ordering information).