



Schedule 40 Fittings & Accessories PVC Clear Sch 40 Pipe & Fittings

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Coupling Soc



429-002L	1/4	25	150	039	6.17
429-003L	3/8	50	300	039	6.17
429-005L	1/2	50	300	039	4.59
429-007L	3/4	50	200	039	6.18
429-010L	1	50	0	039	10.74
429-012L	1-1/4	25	150	039	14.62
429-015L	1-1/2	25	0	039	15.74
429-020L	2	10	60	039	24.53
429-025L	2-1/2	10	0	039	53.75
429-030L	3	10	0	039	84.33
429-040L	4	6	0	039	121.74
429-060L	6	5	0	039	219.15
429-080L	8	6	0	039	394.44

Female Adapter Soc x SR Fipt



435-002SRL	1/4	25	450	039	12.95
435-003SRL	3/8	25	300	039	12.95
435-005SRL	1/2	25	300	039	7.67
435-007SRL	3/4	25	300	039	9.60
435-010SRL	1	25	200	039	11.09
435-012SRL	1-1/4	10	80	039	17.04
435-015SRL	1-1/2	10	80	039	19.99
435-020SRL	2	10	0	039	26.92
435-025SRL	2-1/2	5	0	039	55.95
435-030SRL	3	10	0	039	91.33
435-040SRL	4	6	0	039	151.06

Male Adapter Mipt x Soc



436-003L	3/8	50	300	039	8.28
436-005L	1/2	50	300	039	6.18
436-007L	3/4	50	400	039	6.94
436-010L	1	50	300	039	12.18
436-012L	1-1/4	25	0	039	14.71
436-015L	1-1/2	25	0	039	19.97
436-020L	2	25	0	039	26.04
436-025L	2-1/2	10	0	039	77.24
436-030L	3	10	0	039	112.84
436-040L	4	5	0	039	143.91

Reducer Bushing Spig x Soc



437-101L	3/4X1/2	50	300	039	7.14
437-131L	1X3/4	50	200	039	13.13
437-168L	1-1/4X1	25	150	039	17.29
437-211L	1-1/2X1	25	100	039	18.26
437-212L	1-1/2X1-1/4	25	100	039	18.26
437-251L	2X1-1/2	10	80	039	30.24
437-292L	2-1/2X2	10	40	039	48.64
437-338L	3X2	10	0	039	72.17
437-339L	3X2-1/2	10	0	039	72.17
437-422L	4X3	6	0	039	161.25
437-532L	6X4	5	0	039	324.51
437-585L	8X6	4	0	039	522.47

Part Number	Size	Std Pk	Mstr Ctn	Disc Code	Price Each
-------------	------	--------	----------	-----------	------------

Cap Soc



447-002L	1/4	25	150	039	8.28
447-003L	3/8	50	300	039	8.28
447-005L	1/2	50	300	039	6.18
447-007L	3/4	50	300	039	7.14
447-010L	1	50	200	039	11.31
447-012L	1-1/4	25	100	039	15.74
447-015L	1-1/2	25	0	039	17.29
447-020L	2	10	80	039	20.84
447-025L	2-1/2	10	0	039	66.68
447-030L	3	10	0	039	65.65
447-040L	4	6	0	039	149.31
447-060L	6	4	0	039	268.76
447-080L	8	3	0	039	483.75

Wyes & Reducing Wyes Soc



1/2" - 2" - 235 psi Maximum Internal Pressure Rating @ 73°F (23°C)
2-1/2" - 6" - 150 psi Maximum Internal Pressure Rating @ 73°F (23°C)

475-015L	1-1/2	20	0	039	45.67
475-020L	2	10	0	039	67.23
475-030L	3	4	0	039	280.03
475-040L	4	4	0	039	509.85
475-060L	6	3	0	039	871.62
475-532L	6X4	5	0	039	871.62