

NOKORODE® PASTE FLUXES

Continued

Nokorode® Regular

Multi-purpose paste flux

| Code | Description | Qty. |
|-------|----------------|------|
| 14000 | 1.7 oz. | 48 |
| 14010 | 4 oz. | 24 |
| 14020 | 8 oz. tool box | 24 |
| 14030 | 1 lb. | 12 |



FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Safe for potable water systems
- Certified to NSF/ANSI 61-G
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • All purpose, soft soldering paste flux with a special oil base that protects the solder against corrosive attack

- Non-aggressive formula. Ideal for copper and brass fittings

Recommended for

- All solder alloys including 95/5 and lead free solders



Nokorode® Hot Weather

Does not liquefy in hot temperatures

| Code | Description | Qty. |
|-------|----------------|------|
| 14800 | 1.7 oz. | 48 |
| 14820 | 8 oz. tool box | 24 |
| 14830 | 1 lb. | 12 |

FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • Formulated to remain firm and stable in higher temperatures • Non-aggressive formula for use on copper and brass fittings

Recommended for

- All solder alloys including 95/5 and lead free solders



Nokorode® Cold Weather

Does not harden in cold temperatures

| Code | Description | Qty. |
|-------|-------------|------|
| 14700 | 1.7 oz. | 48 |
| 14720 | 8 oz. | 24 |
| 14730 | 1 lb. | 12 |

FEATURES

- Lead Free
- Cleans & fluxes all at one time
- Meets O-F-506 Type 1A & A-A-51145, MIL-F-4995-2 specs

Application • Formulated to stay soft and sticky in cold weather • Low corrosivity, scorching and spattering. Works to deliver a strong, leak-free joint

Recommended for

- All solder alloys including 95/5 and lead free solders

