


# 455 Malleable Split Ring Hanger



## Features

- Recommended for the suspension of stationary non-insulated pipe lines
- Allows for piping runs close to ceiling or walls
- Conforms with Federal Specification WW-H-171 (Type 25), Manufacturers Standardization Society (MSS) SP-58 and SP-69 (Type 12)

## Specifications

Material: Cast iron

| Part Number                | Pipe Size | Outer Diameter OD | Rod Size RS | A       | B      | Static Load F |
|----------------------------|-----------|-------------------|-------------|---------|--------|---------------|
| Finish: Electro-galvanized |           |                   |             |         |        |               |
| 4550037EG                  | 3/8"      | 0.675"            | 3/8"        | 1 5/16" | 3/8"   | 180 lb        |
| 4550050EG                  | 1/2"      | 0.840"            | 3/8"        | 1 1/2"  | 3/8"   | 180 lb        |
| 4550075EG                  | 3/4"      | 1.050"            | 3/8"        | 1 3/4"  | 7/16"  | 180 lb        |
| 4550100EG                  | 1"        | 1.315"            | 3/8"        | 2"      | 7/16"  | 180 lb        |
| 4550125EG                  | 1 1/4"    | 1.660"            | 3/8"        | 2 3/8"  | 1/2"   | 180 lb        |
| 4550150EG                  | 1 1/2"    | 1.900"            | 3/8"        | 2 5/8"  | 1/2"   | 180 lb        |
| 4550200EG                  | 2"        | 2 3/8"            | 3/8"        | 3 1/8"  | 1/2"   | 180 lb        |
| 4550250EG                  | 2 1/2"    | 2 7/8"            | 1/2"        | 3 1/4"  | 5/8"   | 300 lb        |
| 4550300EG                  | 3"        | 3 1/2"            | 1/2"        | 4 3/8"  | 5/8"   | 300 lb        |
| 4550400EG                  | 4"        | 4 1/2"            | 1/2"        | 5 3/8"  | 11/16" | 300 lb        |
| Finish: Plain              |           |                   |             |         |        |               |
| 4550037PL                  | 3/8"      | 0.675"            | 3/8"        | 1 5/16" | 3/8"   | 180 lb        |
| 4550050PL                  | 1/2"      | 0.840"            | 3/8"        | 1 1/2"  | 3/8"   | 180 lb        |
| 4550075PL                  | 3/4"      | 1.050"            | 3/8"        | 1 3/4"  | 7/16"  | 180 lb        |
| 4550100PL                  | 1"        | 1.315"            | 3/8"        | 2"      | 7/16"  | 180 lb        |
| 4550125PL                  | 1 1/4"    | 1.660"            | 3/8"        | 2 3/8"  | 1/2"   | 180 lb        |
| 4550150PL                  | 1 1/2"    | 1.900"            | 3/8"        | 2 5/8"  | 1/2"   | 180 lb        |
| 4550200PL                  | 2"        | 2 3/8"            | 3/8"        | 3 1/8"  | 1/2"   | 180 lb        |
| 4550250PL                  | 2 1/2"    | 2 7/8"            | 1/2"        | 3 1/4"  | 5/8"   | 300 lb        |
| 4550300PL                  | 3"        | 3 1/2"            | 1/2"        | 4 3/8"  | 5/8"   | 300 lb        |
| 4550400PL                  | 4"        | 4 1/2"            | 1/2"        | 5 3/8"  | 11/16" | 300 lb        |

Bolt and rivet are carbon steel.

