


Tube to Female Pipe



Female Connector (FC)

Griplok Part #	T Tube O.D.	P-NPT Female Pipe Size	A	B	C	D	E Minimum Opening	F	G	H
G1FC1	1/16	1/16	0.99	0.78	0.49	0.40	0.05	0.39	5/16	7/16
G1FC2	1/16	1/8	1.02	0.81	0.49	0.40	0.05	0.41	5/16	9/16
G2FC2	1/8	1/8	1.19	0.87	0.66	0.56	0.09	0.41	7/16	9/16
G2FC4	1/8	1/4	1.38	1.06	0.66	0.56	0.09	0.59	7/16	3/4
G3FC2	3/16	1/8	1.22	0.91	0.68	0.59	0.12	0.39	1/2	9/16
G4FC2	1/4	1/8	1.27	0.94	0.74	0.64	0.19	0.39	9/16	9/16
G4FC4	1/4	1/4	1.45	1.12	0.74	0.64	0.19	0.59	9/16	3/4
G4FC6	1/4	3/8	1.52	1.19	0.74	0.64	0.19	0.59	9/16	7/8
G4FC8	1/4	1/2	1.71	1.38	0.74	0.64	0.19	0.78	9/16	1-1/16
G5FC2	5/16	1/8	1.26	0.97	0.73	0.64	0.25	0.39	5/8	9/16
G5FC4	5/16	1/4	1.45	1.16	0.73	0.64	0.25	0.59	5/8	3/4
G6FC2	3/8	1/8	1.34	1.00	0.81	0.71	0.28	0.39	11/16	5/8
G6FC4	3/8	1/4	1.53	1.19	0.81	0.71	0.28	0.59	11/16	3/4
G6FC6	3/8	3/8	1.59	1.25	0.81	0.71	0.28	0.59	11/16	7/8
G6FC8	3/8	1/2	1.78	1.44	0.81	0.71	0.28	0.78	11/16	1-1/16
G8FC12	3/8	3/4	1.93	1.59	0.81	0.71	0.28	0.81	11/16	1-5/16
G8FC4	1/2	1/4	1.66	1.19	0.93	0.97	0.41	0.59	7/8	13/16
G8FC6	1/2	3/8	1.72	1.25	0.93	0.97	0.41	0.59	7/8	7/8
G8FC8	1/2	1/2	1.91	1.44	0.93	0.97	0.41	0.78	7/8	1-1/16
G8FC12	1/2	3/4	1.97	1.50	0.93	0.97	0.41	0.81	7/8	1-5/16
G10FC6	5/8	3/8	1.69	1.25	0.90	1.00	0.50	0.59	1	1-5/16
G10FC8	5/8	1/2	1.88	1.44	0.90	1.00	0.50	0.78	1	1-1/16
G12FC8	3/4	1/2	1.88	1.44	0.90	1.00	0.62	0.78	1-1/8	1-1/16
G12FC12	3/4	3/4	1.94	1.50	0.90	1.00	0.62	0.81	1-1/8	1-5/16
G14FC12	7/8	3/4	2.00	1.56	0.90	1.06	0.72	0.81	1-1/4	1-5/16
G16FC12	1	3/4	2.18	1.62	1.12	1.31	0.88	0.81	1-1/2	1-3/8
G16FC16	1	1	2.53	1.97	1.12	1.31	0.88	1.00	1-1/2	1-5/8

Finger-tight assembly dimensions (shown in inches) are for reference only and subject to change.
When ordering specify material designator with part number (see page 3 for complete ordering information).