

Tubular Gage Glasses

SCHOTT DURAN®

► SCHOTT DURAN® Red Line

Applications: Tanks, reservoirs, low pressure boilers.

Benefits: The red line shaded with white lines make it easier to read the liquid level.

End Finish: Firepolish

SCHOTT DURAN® Red Line				Maximum Recommended Working Pressure, psi	
Size	Length* In.	Code No.	Pcs. Per Case	Temperatures Up To 150°F No Corrosion**	Steam Boiler Service Up To 425°F
1/2" OD	8	624010	12	390	300
+0, -1/32"	10	624030	12	370	295
	12	624050	12	360	295
	14	624070	12	345	290
	16	624090	12	335	285
	18	624110	12	325	280
	20	624130	12	310	280
5/64" Wall	24	624170	12	280	270
± 1/64"	30	624180	12	250	***
	36	624190	12	215	***
	48	624210	12	175	***
	60	624211	12	135	***
	72 (Max.)	624212	12	100	***
5/8" OD	8	624310	12	370	285
+0, -1/32"	10	624330	12	345	280
	12	624350	12	335	280
	14	624370	12	325	275
	16	624390	12	315	270
	18	624410	12	305	265
	20	624430	12	290	265
3/32" Wall	24	624470	12	265	255
± 1/64"	30	624480	12	235	***
	36	624490	12	205	***
	48	624510	12	165	***
	60	624220	12	125	***
	72 (Max.)	624221	12	90	***

* Intermediate lengths are available upon request.

** See Corrosives, page 3.

*** Maximum recommended length in this service is 24".