

Tubular Gage Glasses SCHOTT DURAN®

► SCHOTT DURAN® Standard

Applications: Low pressure boilers, restaurant equipment, closed tanks, liquid level gages, sight flow, film rolls, hydraulic equipment.

Benefits: Economical, low pressure applications, long service life.

End Finish: Saw cut, no firepolish.

SCHOTT DURAN® Standard			Maximum Recommended Working Pressure, psi		
Size	Length* In.	Code No.	Pcs. Per Case	Temperatures Up To 150°F No Corrosion**	Steam Boiler Service Up To 425°F
5/8" OD +0, -3/64"	8	620310	12	210	100
	10	620330	12	210	100
	12	620350	12	205	100
	14	620370	12	200	100
	16	620390	12	195	100
	18	620410	12	190	100
	20	620430	12	185	100
5/64" Wall	24	620470	12	180	100
± 1/64"	30	620480	12	175	***
	36	620490	12	165	***
	48	620510	12	140	***
	60	620530	12	120	***
	72 (Max.)	620550	12	100	***
3/4" OD +0, -3/64"	8	620610	12	210	100
	10	620630	12	210	100
	12	620650	12	205	100
	14	620670	12	200	100
	16	620690	12	195	100
	17	620700	12	190	100
	18	620710	12	190	100
3/32" Wall	20	620730	12	185	100
± 1/64"	24	620770	12	180	***
	30	620780	12	175	***
	36	620790	12	165	***
	48	620810	12	140	***
	60	620830	12	120	**
	72 (Max.)	620850*	12	100	***

* Intermediate lengths are available upon request.

** See Corrosives, page 3.

*** Maximum recommended length in this service is 24".

SCHOTT
DURAN®