

Tubular Gage Glasses SCHOTT DURAN®

► SCHOTT DURAN® Red Line

Applications: Tanks, reservoirs, low pressure boilers.

Benefits: The red line shaded with white lines make it easier to read the liquid level.

End Finish: Firepolish

SCHOTT DURAN® Red Line				Maximum Recommended Working Pressure, psi	
Size	Length* In.	Code No.	Pcs. Per Case	Temperatures Up To 150°F No Corrosion**	Steam Boiler Service Up To 425°F
1/2" OD +0, -1/32"	8	624010	12	390	300
	10	624030	12	370	295
	12	624050	12	360	295
	14	624070	12	345	290
	16	624090	12	335	285
	18	624110	12	325	280
	20	624130	12	310	280
5/64" Wall	24	624170	12	280	270
± 1/64"	30	624180	12	250	***
	36	624190	12	215	***
	48	624210	12	175	***
	60	624211	12	135	***
	72 (Max.)	624212	12	100	***
5/8" OD +0, -1/32"	8	624310	12	370	285
	10	624330	12	345	280
	12	624350	12	335	280
	14	624370	12	325	275
	16	624390	12	315	270
	18	624410	12	305	265
	20	624430	12	290	265
3/32" Wall	24	624470	12	265	255
± 1/64"	30	624480	12	235	***
	36~	624490	12	205	***
	48	624510	12	165	***
	60	624220	12	125	***
	72 (Max.)	624221	12	90	***

* Intermediate lengths are available upon request.

** See Corrosives, page 3.

*** Maximum recommended length in this service is 24".