Location:



Kitchen Faucet S-23 Series

Specification Submittal

Feature Highlights

- Single lever kitchen faucet with red & blue indicators on handle
- Handle limit stops
- 8-3/4 inch swing spout with aerator
- Ceramic control components
- Supply has 3/8 inch copper tubing, 8-inch centers
- Metal contruction, polished chrome finish
- 2.2 gpm (8.3 L/min) standard flow rate





Model S-23-2-SM

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime to the original end purchaser in consumer installations.
- 5 years for commercial installations



	of hose and spray (not available in low fl
S-23-2	Faucet with hose and spray
S-23-3	Faucet with hose and spray mounted on
	escutcheon

Finish Options / Modifications

 \Box

Append appropriate -suffix to model number.

-STN Radiance[®] satin finish⊁

- Polished chrome (standard finish)

Handle	Options	/ Modific	cations
		~	

Append appropriate -suffix to model number.

- -LP Loop handle
- -W Lever handle 6 inch (152mm) chrome only

	-LST	18 inch copper supply tubing
	-BH	20 inch (508 mm) braided hose supplies (not available with -SM option)
	-10	10-7/8 inch swing spout with aerator
	-IPS	1/2 inch IPS connections
	-0.35	Vandal resistant, 0.35 gpm (1.3 L/min) flow restrictor
	5	Vandal resistant, .5 gpm (1.9 L/min) flow restrictor
	-1.0	1.0 gpm (3.8 L/min) flow restrictor
	-1.5	1.5 gpm (5.7 L/min) flow restrictor
	-VP	Vandal resistant, standard 2.2 gpm aerator
	-NA	Non-aerated , laminar flow outlet
	-SM	Single hole mounting (not available with -BH option)







Symmons Industries, Inc. • 31 Brooks Drive • Braintree, MA 02184 (800) 796-6667, (781) 848-2250 • Fax (800) 961-9621, (781) 664-1300 Website: www.symmons.com • Email: customerservice@symmons.com

