

SPVC LINE SET TAPE

TYPICAL APPLICATIONS

- Floor, lane and aisle marking
- Color-coding
- Identification

ADVANTAGES AND BENEFITS

- Resistant to moisture and humidity
- UV resistant
- Non-corrosive adhesive
- Available in many colors
- Flexible backing
- Meets OSHA color-coding requirements – Brown (oil), Green (water), Gray (steam), Light Blue (air), Orange (electrical), Red (fire/flammable), Purple (acids/radiation), Yellow (gases), Black and White (miscellaneous)

CONSTRUCTION










Overall Grade/Function: General Purpose

Backing: Clear and colored, stabilized, plasticized, soft polyvinylchloride film (SPVC)

Adhesive: Natural rubber



COLOR(S)

 Black (BLK)	 Purple (PRP)	 White (WHI)	 Green (GRN)	 Orange (ORG)
 Red (RED)	 Yellow (YEL)	 Brown (BRN)	 Dark Blue (DBL)	

STANDARD WIDTH(S)

25 mm 50 mm 75 mm

STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	13 lbs/in width	22.8 N/10 mm
Adhesion to Stainless Steel	20 oz/in width	2.19 N/10 mm
Thickness	5.25 mils	0.13 mm
Elongation	200%	200%
Service Temperature Range	20 F to 140 F	-7 C to 60 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE STANDARDS

PPP-T-66E, Type I, Class 2*; CID A-A-1689B, Type I, Class 2

*Standard is obsolete, and provided only as reference

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

*Shurtape® is a registered trademark of Shurtape Technologies, LLC

Form# TDS-VP-410-11/20/2013