



**WILLIAM H. HARVEY COMPANY**  
4334 South 67<sup>th</sup> Street  
Omaha, NE 68117  
**TECHNICAL SUBMITTAL**  
PH: 1-800-321-9532  
FAX: 1-800-321-9535

## **HARVEY'S PLUMBER'S PUTTY**

**TECHNICAL SPECIFICATION:** Harvey's Plumber's Putty provides a waterproof seal between two rigid surfaces. It is easy to use, long lasting, and remains flexible without hardening, shrinking, cracking or crumbling. Will not support bacteria. Putty is professional grade and is widely used for setting bowls, rims, strainers, faucets, etc.



### **PHYSICAL/CHEMICAL PROPERTIES**

Specific Gravity	2.0
Solubility in Water	Insoluble
Flash Point	650°F
Drying Time	No wait required
Shelf Life	1 year from manufacture date
Appearance	Beige putty
Odor	Mild petroleum scent

### **DIRECTIONS FOR USE**

All surfaces must be dry and free from hardened putty, dirt, wax oil and grease. Remove debris by wiping with cloth, scraper or wire brush as needed and dry surface. Knead putty in hands and form a long cord-like shape. Lay out the cord-like putty on the surface to be sealed, overlapping the ends. Place the fixture over the bead, attach and secure the fixture in place. Excess putty should squeeze out from around the fixture ensuring sufficient putty has been applied and a continuous seal has been made. Remove excess with a putty knife.

### **PRECAUTIONS**

Read all cautions and directions carefully before using this product. **DO NOT USE PLUMBER'S PUTTY ON MARBLE, GRANITE, LIMESTONE OR ANY OTHER DIMENSIONAL STONE. DO NOT USE ON PLASTIC.** Consult manufacturer these materials for recommended sealants. Keep container closed when not in use. **DO NOT REUSE EMPTY CONTAINER. KEEP OUT OF REACH OF CHILDREN AND PETS.**

Refer to material safety data sheet for more information. For emergency first aid help, call 1-303-623-5716 COLLECT.

### **COMMON APPLICATIONS**

Harvey's Plumber's Putty can be used for setting frames, faucets and basket strainers.

Consult Harvey Technical Service department for applications not specified above.

### **NON-HAZARDOUS INGREDIENTS**

Hydrocarbon Oils (64742-52-5)  
Limestone (1317-65-3)  
Talc (14807-96-6)  
Clays (68953-58-2)  
Fish Oils (68082-77-9)

### **APPROVALS AND LISTINGS**

Meets Federal Specification TT-P-1536.

PRODUCT NUMBER	SIZE	PACK	CARTON WEIGHT
043005	7 oz. net wt. (plastic cup)	24	13 lbs.
043010	14 oz. net wt. (plastic cup)	24	26 lbs.
043050	48 oz. net wt. (plastic cup)	6	23 lbs.
043105	80 oz. net wt. (plastic cup)	6	35 lbs.
043280	54 In. (strip)	6	2 lbs.