



Lubricants

Thread Cutting Oil

clear or dark

Thread Cutting Oil is specially formulated to give sharp, clean threads and to extend die life. A superior quality cutting oil that can be used on most metals. Use for heavy duty cutting, threading, tapping and broaching of steel.



Product	Item Number	U.P.C. Number	Case Pack	Carton Wt. (Lbs.)
8 fl. oz. (1/2 pint) in plastic bottle, clear	016035	078864 160352	12	7
16 fl. oz. (1 pint) in plastic bottle, clear	016050	078864 160505	12	14
16 fl. oz. (1 pint) in plastic bottle, dark	016215	078864 162158	12	14
32 fl. oz. (1 quart) in plastic bottle, clear	016100	078864 161007	12	26
32 fl. oz. (1 quart) in plastic bottle, dark	016265	078864 162653	12	26
1 gallon in plastic jug, clear	016150	078864 161502	6	49
1 gallon in plastic jug, dark	016325	078864 163254	6	49
5 gallons in pail with handle, clear	016190	078864 161908	1	38
5 gallons in pail with handle, dark	016365	078864 163650	1	38
55 gallons in drum, clear	016205	078864 162059	1	460
55 gallons in drum, dark	016390	078864 163902	1	460

Silicone Grease

Silicone Grease is a 90% pure silicone product which contains no petroleum additives and offers greater heat resistance, than lithium based greases. Non-staining and odor-free. Apply to rubber and synthetic "O" rings. If you sell "O" rings, you need this product!



1/2 fl. oz. cup in blister card	050090	078864 500905	12	1
1/2 fl. oz. cup in blister card on clip strip	050090-C	078864 500905	6	1
1 gallon in plastic pail	050098	078864 500981	1	8

Pipe Joint Lubricant

ready to use



Certified to NSF/ANSI #1

Pipe Joint Lubricant is ideal for assembly of push-on type joints with rubber or synthetic rubber type gaskets. Does not support the growth of bacteria. Can be spread easily and thinly to give superior lubrication. Adheres well to wet or dry pipe. Can be used at 10°F to 120°F. For potable water, drain, waste, vent and sewer systems.



32 fl. oz. (1 quart) in plastic cup	050210	078864 502107	12	27
§ 1 gallon in pail with handle	050250	078864 502503	4	34
§ 3.5 gallons in pail with handle	050265	078864 502657	1	32
§ 5 gallons in pail with handle	050275	078864 502756	1	47

Faucet and Valve Grease

heat proof

Faucet and Valve Grease is a waterproof grease that resists high temperatures. Apply to metal parts of faucets and valves. Use on hot water or steam to 350°F.



1/2 fl. oz. in plastic cup	050005-30	078864 500059	30	1
1 fl. oz. in glamine tube				
in clip strip display	050050-C	078864 500509	12	1
in 12-pack display	050050-12	078864 500509	12	1
in four 12-pack displays	050050-48	078864 500509	48	5
in corrugated display box	050050-D	078864 500509	54	5
1.7 fl. oz. tin in 12-pack display	050115	078864 501155	12	3
1 gallon in pail	050190	078864 501902	1	9

Boldface U.P.C. number indicates U.P.C. symbol printed on package. § indicates Spanish/English packaging.