

Product information presented here reflects conditions at time of publication. Consult factory regarding discrepancies or inconsistencies.

MAIL TO: P.O. BOX 16347 • Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road • Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP • FAX (502) 774-3624

visit our web site:
www.zoeller.com



THE "FULL-FLOW" UNICHECKS

30-0163

1 1/4" CAST IRON NPT

30-0164

1 1/2" CAST IRON NPT



30-0163
Pictured

Outside dimensions
5 1/16" W x 4" W x 6 1/4" H



- Vertical or horizontal installation.
- Full flow design - no restrictions.
- Stops backflow of water.
- Standard, 1 1/4", 1 1/2", 2", 3" female NPT pipe.
- Neoprene polyester reinforced flapper - smooth edge design, with cast iron and noncorrosive metal backing plates & stainless steel fastener.
- Corrosion resistant powder coated epoxy finish.
- Rated at 50 PSI (115 feet of head) at 130°F
- Stainless steel bolts.
- 1 per carton.
- Weight: 30-0163, 7.5 lbs.; 30-0164, 7.5 lbs.;
- 30-0152, 10 lbs.; 30-0160, 18 lbs.
- Suitable for installation below basin cover.

30-0152

2" CAST IRON NPT

30-0160

3" CAST IRON NPT



30-0160
Pictured

Outside dimensions
6 5/8" W x 6 5/8" W x 8" H

30-0021

2" PLASTIC SLIP X SLIP UNIONS

30-0151

2" CAST IRON SLIP X SLIP UNIONS

- Full 2" flow design - meets BOCA (P.604.2) 2" Full Flow Pump Code.
- Checks backflow of water and sewer gas.
- Simple to install (no threading of pipe required). Save time & material costs.
- Neoprene gasket and flapper, weighted with heavy stainless steel metal backing plates and stainless steel rivet.
- Can be installed on vertical or horizontal line.
- Slips over ABS, PVC, steel pipe or copper piping.
- Reduces motor and pump noise from plumbing system.
- Meets requirements of Wisconsin Uniform Plumbing Code.
- Flexible neoprene slip x slip union includes

stainless steel clamps for low pressure systems. Avoid more than 10 ft. static head above the check valve. 4.3 PSI at 130°F.

- Stainless steel screws.
- Extra wide hinge to reduce hinge stress.
- Plastic check has PVC body and can be installed with solvent welded couplings for pressure systems to 25 PSI (57 ft. of Head). (P/N 30-0023)
- Model 30-0151 has corrosion resistant powder coated epoxy finish.
- Stainless Steel sleeves available to meet Illinois plumbing code. C.I. 30-0201 / PVC 30-0202.
- Plastic check individual rack pack Model 30-0022.
- 6 per carton.



30-0151
CAST IRON



30-0021
PVC PLASTIC

30-0181 / 30-0200

1 1/2" or 1 1/4" SLIP X SLIP UNION

- Flapper bends over a radius, no sharp 90° edges—lengthens life of flapper hinge.
- PVC plastic check body, ultrasonically welded and can be solvent welded for rigid pressure rated piping systems to 25 PSI - (57 ft. of Head) at 130°F. (30-0182).
- Vertical or horizontal installation.
- Available in individual packages for pegboard display (30-0191).
- All stainless steel screws, nuts and clamps on model 30-0200 only.
- Slip x Slip for 4.3 PSI (10 ft. of Head) at 130°F. Avoid more than 10 ft. static head above the check valve.
- Designed to reduce water hammer.
- 10 per carton.



HIGH TEMPERATURE "FULL-FLOW" UNICHECKS

30-0214 1¼" CAST IRON NPT

30-0215 1½" CAST IRON NPT


30-0216 2" CAST IRON NPT



30-0214
Pictured

- Use with 2000 & 3000 Series High Temperature Pumps.
- Vertical or horizontal installation.
- Full flow design - no restrictions.
- Stops backflow of water.
- Standard, 1¼", 1½", 2" female NPT pipe.
- EPDM strand reinforced flapper - smooth edge design, with cast iron and noncorrosive metal backing plates & stainless steel fastener.
- Corrosion resistant powder coated epoxy finish.
- Rated at 50 PSI (115 feet of head) at 200°F
- Stainless steel bolts.
- 1 per carton.
- Weight: 30-0214, 7.5 lbs.; 30-0215, 7.5 lbs.; 30-0216, 10 lbs.

Tri-Check®



30-0100

1½" PVC CHECK VALVE / BALL VALVE / UNION COMBINATION

30-0101

2" PVC CHECK VALVE / BALL VALVE / UNION COMBINATION

FEATURES:

- Full flow check valve design.
- Threaded union allows pump to be removed without disrupting discharge piping.
- Saves time and money - Easy to install.
- Neoprene gasket and flapper, weighted with stainless steel backing plates and stainless steel rivet.
- Can be installed on vertical or horizontal pipe.
- Meets plumbing codes requiring a ball valve installed in conjunction with a check valve.
- All stainless steel screws.
- Replaceable flapper in the check valve.
- Extra wide hinge to reduce stress.
- Rated for 25 psi (58 ft. of head).
- 6 Per carton (30-0100 & 30-0101).
- 9 Per carton (30-0102 & 30-0103).

The "Combo"



30-0102

1½" PVC CHECK VALVE / UNION COMBINATION

30-0103

2" PVC CHECK VALVE / UNION COMBINATION

ZOELLER®
PUMP CO.

www.zoeller.com

MAIL TO: P.O. BOX 16347
Louisville, KY 40256-0347
SHIP TO: 3649 Cane Run Road
Louisville, KY 40211-1961
(502) 778-2731 • 1 (800) 928-PUMP
FAX (502) 774-3624

Manufacturers of..

"QUALITY PUMPS SINCE 1939"