



# Z5755-U

TAG \_\_\_\_\_

## Omni-Flo™ Top Spud Urinal 0.125 gpf to 1.0 gpf



Z5755 Series

### Recommended Trim:

- ZTR6203-ULF-LL**  
Sensor Long Life Battery Operated Urinal  
Flush Valve. 0.125 gpf [0.5 Lpf]
- ZTR6203-EWS-LL**  
Sensor Long Life Battery Operated Urinal  
Flush Valve. 0.5 gpf [1.9 Lpf]
- ZTR6203-WS1-LL**  
Sensor Long Life Battery Operated Urinal  
Flush Valve. 1.0 gpf [3.8 Lpf]

*These dimensions and specifications are subject to change without notice.*

*Fixture dimensions meet ANSI/ASME standard A112.19.2 and CAN/CSA B45 requirements.*

*Meets the American Disabilities Guidelines and ANSI A117.1 requirements when urinal is installed 432mm (17") from finished floor.*



ZURN INDUSTRIES, LLC. ♦ COMMERCIAL BRASS OPERATION  
5900 ELWIN BUCHANAN DRIVE ♦ SANFORD NC 27330  
Phone: 1-800-997-3876 ♦ Fax: 919-775-3541  
www.zurn.com

In Canada: ZURN INDUSTRIES LIMITED  
3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2  
Phone: 905-405-8272 Fax: 905-405-1292

### Z5755 Urinal Series

- Zurn Ultra Low Consumption Urinal designed for optimal performance when paired with Zurn flush valve to save water while exceeding industry performance standards
- Based on flush valve it can flush 0.125 gpf [0.5 Lpf] to 1.0 gpf [3.8 Lpf]
- Vitreous china
- Asymmetric backwall resulting in reduced splash back
- Patent Pending
- High efficiency washdown flushing action
- Oversized footprint to make retrofit easy
- 3/4" top spud
- 2" I.P.S. outlet flange and rubber gasket with integral trap
- 14" extended rim for handicap compliance when installed at proper height
- Vandal resistant outlet strainer included

### Engineering Specification:

- Z5755 EcoVantage® Urinal**  
0.125 gpf [0.5 Lpf] to 1.0 gpf [3.8 Lpf] vitreous china, wall hung, integral trap, washdown urinal complete with 3/4" top spud connection, concealed universal retrofit wall bracket, 2" outlet connection and vandal resistant outlet strainer.

Architectural/Engineering Approval

See Zurn One Systems for suggested packages.

The information contained in this document is subject to change without notice.  
Please contact Zurn for most up to date information.




# Z5755-U

TAG \_\_\_\_\_

## Omni-Flo™ Top Spud Urinal 0.125 gpf to 1.0 gpf

Rough-in dimensions for Z5755-U Series



These dimensions and specifications are subject to change without notice.

Fixture dimensions meet ANSI/ASME standard A112.19.2 and CAN/CSA B45 requirements.

Meets the American Disabilities Guidelines and ANSI A117.1 requirements when urinal is installed 432mm (17") from finished floor.



ZURN INDUSTRIES, LLC. ♦ COMMERCIAL BRASS OPERATION  
 5900 ELWIN BUCHANAN DRIVE ♦ SANFORD NC 27330  
 Phone: 1-800-997-3876 ♦ Fax: 919-775-3541  
 www.zurn.com  
 In Canada: ZURN INDUSTRIES LIMITED  
 3544 Nashua Drive ♦ Mississauga, Ontario L4V1L2  
 Phone: 905-405-8272 Fax: 905-405-1292