



HIRSCHMANN

A BELDEN BRAND

Product information BAT-ANT-N-MiMo5-9N-IP65

Industrial Ethernet:Industrial Wireless LAN:Accessories:Antenna:BAT-ANT-N-MiMo5-9N-IP65

<http://e-catalog.hirschmann.com/link/57078-24455-49859-24498-24499-65378/en/conf/uistate>

Name		BAT-ANT-N-MiMo5-9N-IP65
		
		5 GHz MiMo antenna for sectoral illumination
Delivery informations		
Availability		available
Product description		
Description		5 GHz MiMo antenna for sectoral illumination
Type		BAT-ANT-N-MiMo5-9N-IP65
Order No.		943 981-013
Cable length		3 x 90 cm directly attached
Cable specification		N-plug
Radio technology		
Range		please refer to the antenna distance calculator
Frequency band		5150 MHz - 5875 MHz
Polarisation		triple linear, 45° slant
Elevation, Azimuth		3 dB beam width 60° / 60°
VSWR		1.5
Gain		9 dBi
Antenna connector		N male
Ambient conditions		
Operating temperature		-40 °C to +80 °C
Storage/transport temperature		-40 °C to +80 °C
Wind load		15 N at 160 km/h
Mechanical construction		
Dimensions (W x H x D)		101 mm x 80 mm x 35 mm
Mounting		wall, mast
Protection class		IP65
Material		LEXAN EXL 9330
Weight		0.11 kg
Scope of delivery and accessories		
Scope of delivery		antenna, mounting material, 3x pigtail N to RP-SMA

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect. The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.