

Anybus Communicator – Serial Master to PROFIBUS IO-Device ATEX

Item number: ABC3000EX-A

The Anybus Communicator Serial Master to PROFIBUS IO-Device ATEX enables you to connect any RS-232/485 device or equipment to PROFIBUS control systems. Anybus Communicators ensure reliable, secure, and high-speed data transfers between different industrial networks. Thanks to our intuitive web-based user interface, they're also incredibly easy to use.



*A protocol converter that connects serial devices to
PROFIBUS control systems*

Features and benefits

✓ Certified for hazardous locations

The Communicator is certified for ATEX Zone 2 and UL hazardous location Class 1 Division 2.

✓ Instant data transfer

Instant data transfer lets you take advantage of high-speed industrial networks.

✓ Intuitive user interface

Use the intuitive web-based user interface to easily configure the Communicator via the drag-and-drop functionality or to analyze live data and generate support packages.

✓ Optimized hardware design

The Communicator has forward-facing ports and is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

✓ 5-year warranty

Thanks to carefully selected industrial components the Communicator operates reliably in harsh environments, ensuring uptime and longevity. Our confidence in quality is reflected in a 5-year warranty.

✓ High performance

Powered by the award-winning NP40 network processor, it enables instant transfer of up to 1500 bytes (network dependent) between networks, totaling 3000 bytes.

✓ Endian conversion

The Communicator provides hardware-accelerated endian conversion (byte swap), saving processing time on the PLC.

✓ Cybersecurity

Despite advanced security, human error often causes breaches. Our Communicator's physical security switch can lock configurations and block web interface access, enhancing security.

✓ Diagnostics

The user interface displays real-time connection status and I/O data mapping for easy troubleshooting. Easily generate a support file containing all the necessary information.

✓ Life cycle management

HMS maintains every part of the Communicator, including network updates, throughout the product's lifecycle.

Anybus Communicator – Serial Master to PROFIBUS IO-Device ATEX



General

Net Width (mm)	27
Net Height (mm)	144
Net Depth (mm)	98
Net Weight (g)	150
Packed Width (mm)	35
Packed Height (mm)	170
Packed Depth (mm)	115
Packed Weight (g)	185
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Connector	3-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO
Packaging Material	Cardboard
Warranty (years)	5

Anybus Communicator – Serial Master to PROFIBUS IO-Device ATEX



Identification and Status

Product ID	ABC3000EX-A
Model Code	40-SER-PDP-A-EX
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.1

Physical Features

Push Buttons	Factory reset
Contains Battery	No

Modbus-RTU Features

Modbus-RTU Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600,115200,128000 bit/s
Modbus-RTU Input Data Size	1500 bytes
Modbus-RTU Output Data Size	1500 bytes

PROFIBUS Features

PROFIBUS Mode	DP Device
PROFIBUS Baud Rate	9600 bit/s - 12 Mbit/s
PROFIBUS Input Data Size	244 bytes
PROFIBUS Output Data Size	244 bytes

Serial Features

Baud Rate	1200,1800,2400,4800,7200,9600,14400,19200,35700,38400,57600,115200,128000 bit/s
Supported Functionality	RS-232; RS485; Standard Modbus RTU Master; Custom Request / Response commands; Custom Produce / Consume transactions; Trigger initiated transactions; 7 or 8 data bit; None, Odd, Even Parity; 1 or 2 stop bit; Clear/Freeze

Certifications and Standards

Protection Class IP	IP20
---------------------	------

Anybus Communicator – Serial Master to PROFIBUS IO-Device ATEX



Certifications and Standards

UL	Yes
ATEX	Yes
ATEX Information	II 3 G Ex ec IIC T4 Gc, EN IEC 60079-0, 60079-7, IEC 60664-1
EMC	Yes
Environment	EN 55016-2-3 Class A, EN 55032 Class A, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-7
WEEE Category	IT and telecommunications equipment