



Anybus X-gateway - Modbus TCP Client - Modbus RTU Slave

The Anybus X-gateway allows you to seamlessly inter-connect PLC control systems and their connected devices between Modbus TCP and Modbus RTU networks.

FAST COPYING OF I/O DATA

The X-gateways primary function is with the fast transfer of cyclic I/O data between the two networks. This offloads your PLC from working with additional calculations. The gateway acts as a Slave on the Modbus RTU network and as a full Master/Client on the Modbus TCP network. The data transmission between the two networks is completely transparent with a maximum I/O data capacity of 256 bytes in each direction.

EASY CONFIGURATION - NO PROGRAMMING REQUIRED!

Configuration is made via Ethernet and a built-in web page. The configuration page is used to configure Ethernet TCP/IP settings, Modbus-TCP client/server configuration and I/O data size transfer between Modbus TCP and the chosen network.



Features and benefits

- Fast copying of cyclic I/O data between a Modbus TCP and a Modbus RTU network (5 ms)
- Allows for the integration of Modbus TCP based server/slave devices into other PLC control systems
- Full Modbus TCP Client/Master functionality, eliminates the need for an PLC controller on the Modbus TCP network
- Connects up to 64 Modbus Servers/Slave devices
- Max I/O data capacity of 256 bytes in each direction

Possibility to build web pages displaying and controlling a factory floor process with data from the other connected network

SD memory card slot allows for backup, configuration and easy module replacement

- Robust stand-alone housing for use in harsh industrial environments
- Global free technical support and consultancy

Modbus TCP Client/Master interface

Modbus TCP Client and Server setup is made via an included visual web configuration interface without the need for any programming.

- Modbus TCP Client functionality according to Modbus specification V1.1B
- Support for Modbus TCP functions 1, 2, 3, 4, 5, 6, 15, 16, 23
- Connects up to 64 Modbus TCP servers/slaves
- Supports up to max 256 bytes of Input and 256 bytes of Output data
- 10/100Mbit operation in full or half-duplex
- Integrated FTP server provides easy file management using standard FTP clients
- Web server with dynamic data capability and Server Side Include (SSI) capability
- Email client with dynamic data capability and Event-triggered email handling
- Downlink Live List providing Modbus-TCP transaction status to uplink PLC
- Control and Status words for downlink network control/status
- Individual Modbus TCP server port number setting
- Byte Swap feature
- Full Modbus address range (1-65536)
- Dual Modbus TCP RJ-45 ports available simultaneously

Modbus RTU Slave interface

Modbus RTU network address settings made via on-board configuration switches

- Complete Modbus RTU slave functionality
- Max 512 bytes of Input and 512 bytes of Output data
- Modbus diagnostics support
- Configuration via on-board DIP switches
- Modbus RTU baudrate 12-57,6 kbit/s
- 1x D-sub 9-pin female network connector

Technical specifications

Dimensions (L•W•H)	110 x 35 x 101 mm or 4,33 x 1,38 x 3,98"	
--------------------	--	--

Weight	160g or 0,35 lbs	
Operating temperature	-25 to +70 °C or -13 to +158 °F	
Storage temperature	-40 to +85 °C or -40 to +185 °F	
Power supply	24 VDC +/- 10 %	
Current consumption	Typical 150 mA	
USB port	For firmware upgrades	
SD memory card slot	For backup, configuration and easy replacement	
Modbus TCP connector	2x RJ45	
Fieldbus/Ethernet connector	(See the secondary network interface details above)	
Galvanic isolation	On both BUS/Ethernet side	
Mechanical rating	IP20, NEMA rating 1	
Mounting	DIN-rail (EN 50022 standard) or Wall Mount (optional)	
Certifications	CE, CULUS, ATEX (zone 2), CULUS Haz.Loc (class 1 div 2)	

File	Version	Size	Read online
------	---------	------	-------------

Ordering information

Order Code	AB9005
Included components	Gateway Quick start documentation Connector terminals Power supply not included PLEASE NOTE: SD-card not included. Configuration software is available for download.

Accessories	021520: Wall mount option 021530: SD-memory card (industrial grade)
--------------------	--

3 year guarantee. For purchasing instructions and terms and conditions, see: [How to buy](#).

Copyright © 2020 HMS Industrial Networks - All rights reserved.