


Wireless Bridge II™

Anybus Wireless Bridge enables you create a robust wireless connection in an industrial Ethernet network. This second generation of the proven and trusted product can communicate via both Bluetooth and Wireless LAN and is ideal for communication through hazardous areas or hard-to-reach locations where cables are not desirable.



EXAMPLE 1: Point-to-point



EXAMPLE 2: Access point



Availability

AWB3000

Ethernet bridge via Bluetooth and WLAN.
2.4 GHz/5 GHz. Internal antennas.

AWB3010

Ethernet bridge via Bluetooth and WLAN.
2.4 GHz/5 GHz. External antenna.

Accessories

023040

Cable kit. 1.5m Ethernet cables M12/RJ45 and power supply (world).

024700

M12 Connector Kit with screw terminals.

024701

DIN Clip kit with screws.

024702

Extra external antenna. Foldable, dual band. RP-SMA connector.

1.04.0085.00000

Magnetic antenna foot with 1,5 m cable and RP-SMA connector, excl. antenna.

1.04.0085.00003

Screw-mount antenna base with 2 m cable and RP-SMA connector, excl. antenna)



HMS provides a full 3 year product guarantee

Wirelessly bridge industrial Ethernet networks

Use the Anybus Wireless Bridge to create a wireless connection in a PROFINET, EtherNet/IP, Modbus-TCP or BACnet/IP network. You can use the same hardware for both Bluetooth or WLAN communication.

Point-to-point or multipoint

Anybus Wireless Bridge is often used as an Ethernet cable replacement (point-to-point communication). But it can also be used as an access point for several WLAN/Bluetooth nodes within range.

Features and benefits

- Three built in antennas for higher performance and better robustness.
- Operation with Bluetooth Low Energy.
- Range up to 400 meters.
- Rugged design with IP65-classed housing.
- Easy setup via push button or via web configuration pages.
- Full compatibility with Anybus Wireless Bolt — a wireless product for machine mounting.
- Connects to your machine via Ethernet.
- Simultaneous operation of Bluetooth and WLAN allowing for bridging between the two.

Which wireless standard?

Use WLAN (aka WiFi) if:

- Interaction with other devices is needed, e.g. Bolt/AWB II to tablet/PC/phone or WLAN infrastructure.
- WLAN channel frequency planning is possible.
- Higher data throughput speed is necessary.
- Larger file transfers are expected.

Use Bluetooth if:


- The wireless link has Anybus products in both ends, e.g. Bolt to Bolt, AWB II to AWB II or Bolt to AWB II.
- A robust and reliable link without interruptions is important e.g. in an industrial environment with lots of disturbances, and maybe has been proven not to work well using WLAN.
- A Profinet or EtherNet/IP I/O cycle time of 64ms or higher is acceptable.
- The data throughput speed need is on the lower side.





TECHNICAL SPECIFICATIONS

Type of wired interface	Ethernet	
Order code	AWB3000	AWB3010
Antenna	Three internal antennas: 1. 2.4 GHz 2. 2.4 GHz MIMO 3. 5 GHz	One external antenna: 1. 2.4/5 GHz dual band
	(The external antenna does not provide better range, but allows connectivity if the Wireless Bridge needs to be placed inside a radio-secure environment such as a steel cabinet)	
Range	400 meters (WLAN and Bluetooth)	
Operating Temperature	-40 to +65 °C (Storage temp: -40 to +85 °C)	
Weight	120 g	
Housing	Plastic PC/ABS (Bayblend FR3010)	
Protection class	IP65	
Dimensions	93 x 68 x 33 mm	
Mounting	With two screws (Ø 4 mm) on flat surface. DIN rail mount option available (optional accessory).	
Connectors	AWB3000+AWB3010: M12 for Ethernet (4-pin, D-coded), M12 for Power (5-pin, A-coded). AWB3010: RPSMA for external antenna.	
Power	9-30 VDC (-5% +20%), Cranking 12V (ISO 7637-2:2011 pulse 4). Reverse polarity protection. (Consumption: 0.7W idle, 1.7W max.)	
Configuration	Three different methods: <ul style="list-style-type: none">• Accessing the built-in web pages in the product• Using Easy Config modes (via push button or inside web interface)• Sending AT-commands via Telnet/Raw TCP	
Vibration compatibility:	Sinusoidal vibration test according to IEC 60068-2-6:2007 and with extra severities; Number of axes: 3 mutually perpendicular (X:Y:Z), Duration: 10 sweep cycles in each axis, Velocity: 1 oct/min, Mode: in operation, Frequency: 5-500 Hz. 5-8,4Hz=±3.5mm; 8,4-40,7Hz=1g; 40,7-57Hz=±0,15mm;57-500Hz=2g. Shock test according to IEC 60068-2-27:2008 and with extra severities; Wave shape: half sine, Number of shocks: ±3 in each axis, Mode: In operation, Axes ± X,Y,Z, Acceleration: 30 m/s ² , Duration: 11 ms.	
Humidity compatibility:	EN 600068-2-78: Damp heat, +40°C, 93% humidity for 4 days.	
WIRELESS STANDARDS		
Wireless LAN	Wireless standards: WLAN 802.11 a, b, g, n, d. Operation modes: Access point or Client WiFi channels: 2.4 GHz, channel 1-11 + 12-13 depending on regulatory domain scan. 5 GHz Access Point: 36-48 (U-NII-1), 5 GHz Client: 100-116 + 132-140 and 120-128 depending on regulatory domain scan. (U-NII-1, U-NII-2, U-NII-2e). RF output power: 18 dBm EIRP (including max antenna gain 3dBi) Max number of slaves for access point: 7 Power consumption: 54mA@24VDC Net data throughput: 20 Mbps. Link speed: max 130 Mbps (802.11n 2x2 MIMO) Security: WEP 64/128, WPA, WPA-PSK and WPA2, TKIP and AES/CCMP, LEAP, PEAP.	
Classic Bluetooth	Wireless standards (profiles): PAN (PANU & NAP) Operation modes: Access point or Client RF output power: 14 dBm EIRP (including max antenna gain 3dBi) Max number of slaves for access point: 7 Power consumption: 36 mA@24VDC Net data throughput: ~1 Mbps Bluetooth version support: Classic Bluetooth v2.1 Security: Authentication & Authorization, Encryption & Data Protection, Privacy & Confidentiality, NIST Compliant, FIPS Approved	
Bluetooth Low Energy	Wireless standards (profiles): GATT Operation modes: Central or Peripheral (pending) RF output power: 10 dBm EIRP (including max antenna gain 3dBi) Max number of simultaneous Peripheral connections: 7 Max number of Peripherals is virtually unlimited by multiplexing. Power consumption: 36 mA@24VDC Net data throughput: ~200 kbps Bluetooth version support: Bluetooth 4.0 dual-mode Security: AES-CCM cryptography	
CERTIFICATIONS		
Europe	ATEX: ATEX Category 3, zone 2 according to EN60079-15, product marking: EX II 3 G nA IIC T4. CE, 2014/53/EU Radio Equipment Directive (RED)	
U.S.	FCC 47 CFR part 15, subpart B. UL: Ind. Cont. Eq. also Listed Ind. Cont. Eq. for Haz. Loc. CL1, DIV 2, GP A,B,C,D,T4. UL file: E203225	
Canada	ICES-003	
Japan	MIC	
Other countries	Argentina, Australia, Colombia, Turkey, Malaysia, Peru, Mexico Pending: Brazil, Chile, India, Philippines, South Africa	



Configuration

You can configure the Anybus Wireless Bridge by accessing the built-in web pages in the product. You can also use the push-button. Pressing sequences will configure the product. Instructions included.



Order a Starter Kit!

Includes: Two Wireless Bridges (AWB3000), Two Power Supplies (world), cabling, Quick Start Guide. Part number: AWB3300