



HIRSCHMANN

A BELDEN BRAND

Product information MACH1000, Full Gigabit Ethernet switch 16 ports - MAR1040-4C4C4C4C9999SM9HPHH08.0.

Industrial Ethernet:Ruggedized Switches:Fast/Gigabit Ethernet Control Cabinet Switches:Full Gigabit Ethernet Control Cabinet Switches:with Firmware Release 8:MACH1000, Full Gigabit Ethernet switch 16 ports

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49846-49997-82828-373311-373318/en/MAR1040-4C4C4C4C9999SM9HPHH08.0./uistate>

Name		MACH1000, Full Gigabit Ethernet switch 16 ports
		
		Ethernet/Fast Ethernet/Gigabit Ethernet switch, managed, Industrial Switch 19" rack mount, fanless design
Delivery informations		
Availability		available
Product description		
Description		Ethernet/Fast Ethernet/Gigabit Ethernet switch, managed, Industrial Switch 19" rack mount, fanless design
Port type and quantity		16 x combo ports (10/100/1000BASE TX RJ45 plus related FE/GE-SFP slot)
Type		MAR1040-4C4C4C4C9999SM9HPHH08.0.
Order No.		942 004-001
More Interfaces		
Power supply/signaling contact		power supply 1: power supply, 3 pin plug-in terminal block, signal contact, 2 pin plug-in terminal block;
V.24 interface		1 x RJ11 socket
USB interface		1 x USB to connect the AutoConfiguration Adapter ACA21-USB
Network size - length of cable		
Twisted pair (TP)		0 m ... 100 m
Multimode fiber (MM) 50/125 µm		cf. Gigabit and Fast Ethernet SFP modules
Multimode fiber (MM) 62.5/125 µm		cf. Gigabit and Fast Ethernet SFP modules
Single mode fiber (SM) 9/125 µm		cf. Gigabit and Fast Ethernet SFP modules
Single mode fiber (LH) 9/125 µm (long haul transceiver)		cf. Gigabit and Fast Ethernet SFP modules
Network size - cascading		
Line - / star topology		any
Ring structure (HIPER-Ring) quantity switches		up to 10 ms (10 switches), up to 30 ms (50 switches), up to 40 ms (100 switches), up to 60 ms (200 switches)
Power requirements		
Operating voltage		power supply 1: 120/250 V DC; 110/230 V AC
Current consumption at 24 V DC		power supply 1: n/a;
Current consumption at 230 V AC		power supply 1: 110 mA (26 W) max., if all ports are equipped with SFP (100 W PoE option);
Power output in Btu (IT) h		90 max (350 PoE option)
Software		
Management		Serial interface, web-interface, SNMP V1/V2, HiVision file transfer SW HTTP/TFTP, LLDP-MED
Diagnostics		LEDs, log-file, syslog, relay contact, RMON, port mirroring 1:1 and n:1, egress/ingress traffic configurable, topology discovery 802.1AB, cable tester (TX), address conflict detection, network error detection, SFP diagnostic [temperature, optical input and output power (µW and dBm)], Trap for configuration saving and changing, duplex mismatch detection, disable learning, Port Monitor
Configuration		Command line interface (CLI), TELNET, BootP, DHCP, DHCP option 82, HiDiscovery, easy device exchange with auto-configuration adapter ACA21-USB (automatic software and/or configuration upload), automatic script load from ACA21, integrated DHCP server per port, DHCP relay, automatic invalid configuration undo, Offline Configuration, SFP Whitelist, ARC automatic ring configuration (MRP), automatic port shutdown (link flapping), configuration signature (water marking), overload detection
Security		Port Security (IP und MAC) with multiple addresses (MAC 50 per port), SNMP V3, SSHv2, Authentication (IEEE802.1x), 802.1x Multi Client Authentication, Guest VLAN and Unauthenticated VLAN, Port based Radius VLAN assignment, MAC notification
Redundancy functions		HIPER-Ring, Fast HIPER-Ring, MRP, MSTP, RSTP - IEEE802.1D-2004, MRP and RSTP in parallel, link aggregation, multiple rings
Filter		QoS 8 classes, prioritisation (IEEE 802.1D/p), VLAN (IEEE 802.1Q), Voice VLAN, shared VLAN learning, Q-in-Q double VLAN tagging, multicast IGMP v1/v2/v3 (snooping/querier), multicast detection unknown multicast, broadcast-, unicast-, multicast limiter, fast aging, GMRP IEEE 802.1D, Jumbo Frame Support



HIRSCHMANN

A BELDEN BRAND

Industrial Ethernet: Ruggedized Switches: Fast Gigabit Ethernet Control Cabinet Switches: Full Gigabit Ethernet Control Cabinet Switches: with Firmware Release 8: MACH1000, Full Gigabit Ethernet switch 16 ports

<http://www.e-catalog.beldensolutions.com/link/57078-24455-49846-49997-82828-373311-373318/en/MAR1040-4C4C4C9999SM9HPH08.0./uistate>

Industrial Profiles	EtherNet/IP and PROFINET (2.2 PDEV, GSDML Stand-alone generator, automatic device exchange) profiles included, configuration and diagnostic via automation software tools like e.g. STEP7, or Control Logix IEC61850 protocol (MMS Server, Switch Model)
Time synchronisation	PTP IEEE 1588 v1/v2 Boundary and Transparent Clock hardware time stamping with accuracies of 30ns, IEEE 1588 Power Profile (C37.238-2011), SNTP server, realtime clock with energy buffer
Flow control	Flow Control 802.3x, Port Priority 802.1D/p, Priority (TOS/DIFFSERV), Prio (MAC/IP), Prio Mapping (TOS Layer2), Traffic Shaping (Unicast, Multicast, Broadcast) Ingress / Egress
Ambient conditions	
Operating temperature	0 °C ... 60 °C
Storage/transport temperature	-40 °C ... 85 °C
Relative humidity (non-condensing)	5 % ... 95 %
MTBF	13.6 years (MIL-HDBK-217F)
Protective paint on PCB	No
Mechanical construction	
Dimensions (W x H x D)	445 mm x 44 mm x 345 mm
Mounting	19" control cabinet
Weight	5600 g
Protection class	IP30
Mechanical stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	1 mm, 2 Hz-13.2 Hz, 90 min.; 0.7g, 13.2 Hz-100 Hz, 90 min.; 3.5 mm, 3 Hz-9 Hz, 10 cycles, 1 octave/min.; 1 g, 9 Hz-150 Hz, 10 cycles, 1 octave/min.
EMC interference immunity	
EN 61000-4-2 electrostatic discharge (ESD)	8 kV contact discharge, 15 kV air discharge
EN 61000-4-3 electromagnetic field	35 V/m (80-2700 MHz); 1 kHz, 80% AM
EN 61000-4-4 fast transients (burst)	4 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 1 kV data line, IEEE1613: power line 5 kV (line/earth)
EN 61000-4-16 mains frequency voltage	30 V, 50 Hz continuous; 300 V, 50 Hz 1 s
EMC emitted immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508
Hazardous locations	ISA 12.12.01 Class 1 Div. 2
Shipbuilding	Germanischer Lloyd
Railway norm	EN 50121-4, EN50155 (pending), NEMA TS
Substation	IEC 61850-3, IEEE 1613
Transportation	EN 50121-4, EN50155 (pending), NEMA TS
Scope of delivery and accessories	
Scope of delivery	device, operating manual

For more information please contact:

Hirschmann Automation and Control GmbH

Stuttgarter Strasse 45-51

72654 Neckartenzlingen

Germany

Phone: +49 7127/14-1809

E-Mail: inet-sales@belden.com

The information published in the websites has been compiled as carefully as possible. It is subject to alteration without notice in technical as well as in price-related/commercial respect.
The complete information and data were available on user documentation. Mandatory information can only be obtained by a concrete query.