



Product: [OSP6AF](#) 

Category 6A Outside Plant F/UTP Cable

Product Description

CAT6A (500 MHz), 4 Pair, F/UTP-Foil Shielded, Outdoor OSP, Premise Horizontal Cable, 23 AWG Solid Bare Copper Conductors, Polyolefin Insulation, Patented X-Spline, Gel-Filled, UV resistant LLDPE Inner Jacket, Overall Beldfoil® Shield with Drain Wire, Ripcord, UV Resistance LLDPE Outer Jacket

Technical Specifications

Product Overview

Suitable Applications:	OSP-Outside Plant, 10 Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Audio, AES51, RS-422, Noisy Environments, PoE, PoE+
------------------------	---

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material	No. of Pairs
23	Solid	BC - Bare Copper	4

Conductor Count:	8
Total Number of Pairs:	4

Insulation

Material	
Polyolefin	
Bonded-Pair:	N/A

Color Chart

Number	Color
1	White & Blue
2	White & Orange
3	White & Green
4	White & Brown

Inner Jacket Material

Material	Nominal Diameter	Ripcord
PE - Polyethylene	0.26 in	No

Water Penetration:	GR 421CORE para. 4.3.5.1, ANSI/ICEA S107704 para. 8.2.1, ANSI/ICEA S-99-689
--------------------	---

Outer Shield Material

Type	Material	Material Trade Name	Coverage [%]	Drainwire Material	Drainwire AWG
Tape	Alum / Poly	Beldfoil®	100.0 %	TC - Tinned Copper	26

Outer Jacket Material

Material	Nominal Diameter	Ripcord
PE - Polyethylene	0.360 in	Yes

Electrical Characteristics

Conductor DCR

Max. Conductor DCR	Max. DCR Unbalance	Max DCR Unbalanced Between Pairs [%]
--------------------	--------------------	--------------------------------------

82 Ohm/km	3.0 %	5.0 %
-----------	-------	-------

Capacitance

Max. Capacitance Unbalance	Nom.Mutual Capacitance
45 pF/100m	17 pF/ft

Delay

Frequency [MHz]	Max. Delay	Max. Delay Skew	Nominal Velocity of Propagation (VP) [%]
100 MHz	537.6 ns/100m	45 ns/100m	64.0 %

High Freq

Frequency [MHz]	Max. Insertion Loss (Attenuation)	Min. NEXT [dB]	Min. PSNEXT [dB]	Min. ACR [dB]	Min. PSACR [dB]	Min. ACRF (ELFEXT) [dB]	Min. PSACRF (PSELFEXT) [dB]	Min. RL (Return Loss) [dB]	Max./Min. Input Impedance (unFitted)	Max./Min. Fitted Impedance	Min. PSANEXT	Min. PSAACRF	Min. TCL [dB]	Min. ELTCTL [dB]
1 MHz	2.1 dB/100m	74.3 dB	72.3 dB	72.2 dB	70.2 dB	67.8 dB	64.8 dB	20.0 dB	105 +/- 10	115 +/- 15	67.0 dB	67.0 dB	40.0 dB	35.0 dB
4 MHz	3.8 dB/100m	65.3 dB	63.3 dB	61.5 dB	59.5 dB	55.8 dB	52.8 dB	23.0 dB	105 +/- 10	100 +/- 7	67.0 dB	66.2 dB	40.0 dB	23.0 dB
8 MHz	5.3 dB/100m	60.8 dB	58.8 dB	55.4 dB	53.4 dB	49.7 dB	46.7 dB	24.5 dB	100 +/- 22	100 +/- 7	67.0 dB	60.1 dB	40.0 dB	16.9 dB
10 MHz	5.9 dB/100m	59.3 dB	57.3 dB	53.4 dB	51.4 dB	47.8 dB	44.8 dB	25.0 dB	100 +/- 22	100 +/- 7	67.0 dB	58.2 dB	40.0 dB	15.0 dB
16 MHz	7.5 dB/100m	56.2 dB	54.2 dB	48.8 dB	46.8 dB	43.7 dB	40.7 dB	25.0 dB	100 +/- 22	100 +/- 7	67.0 dB	54.1 dB	38.0 dB	10.9 dB
20 MHz	8.4 dB/100m	54.8 dB	52.8 dB	46.4 dB	44.4 dB	41.8 dB	38.8 dB	25.0 dB	100 +/- 22	100 +/- 7	67.0 dB	52.2 dB	37.0 dB	9.0 dB
25 MHz	9.4 dB/100m	53.3 dB	51.3 dB	44.0 dB	42.0 dB	39.8 dB	36.8 dB	24.3 dB	100 +/- 22	100 +/- 7	67.0 dB	50.2 dB	36.0 dB	7.0 dB
31.25 MHz	10.5 dB/100m	51.9 dB	49.9 dB	41.4 dB	39.4 dB	37.9 dB	34.9 dB	23.6 dB	100 +/- 22	100 +/- 7	67.0 dB	48.3 dB	35.1 dB	5.1 dB
62.5 MHz	15.0 dB/100m	47.4 dB	45.4 dB	32.4 dB	30.4 dB	31.9 dB	28.9 dB	21.5 dB	100 +/- 22	100 +/- 7	65.6 dB	42.3 dB	32.0 dB	
100 MHz	19.1 dB/100m	44.3 dB	42.3 dB	25.2 dB	23.2 dB	27.8 dB	24.8 dB	20.1 dB	100 +/- 22	100 +/- 7	62.5 dB	38.2 dB	30.0 dB	
200 MHz	27.6 dB/100m	39.8 dB	37.8 dB	12.2 dB	10.2 dB	21.8 dB	18.8 dB	18.0 dB	100 +/- 22	100 +/- 7	58.0 dB	32.2 dB	27.0 dB	
250 MHz	31.1 dB/100m	38.3 dB	36.3 dB	7.3 dB	5.3 dB	19.8 dB	16.8 dB	17.3 dB	100 +/- 32	100 +/- 7	56.5 dB	30.2 dB	26.0 dB	
300 MHz	34.3 dB/100m	37.1 dB	35.1 dB	2.9 dB	0.9 dB	18.3 dB	15.3 dB	16.8 dB	100 +/- 32	100 +/- 7	55.3 dB	28.7 dB	25.2 dB	
350 MHz	37.2 dB/100m	36.1 dB	34.1 dB			16.9 dB	13.9 dB	16.3 dB	100 +/- 32	100 +/- 7	54.3 dB	27.3 dB	24.6 dB	
400 MHz	40.1 dB/100m	35.3 dB	33.3 dB			15.8 dB	12.8 dB	15.9 dB	100 +/- 32	100 +/- 7	53.5 dB	26.2 dB	24.0 dB	
450 MHz	42.7 dB/100m	34.5 dB	32.5 dB			14.7 dB	11.7 dB	15.5 dB	100 +/- 32	100 +/- 7	52.7 dB	25.1 dB	23.5 dB	
500 MHz	45.3 dB/100m	33.8 dB	31.8 dB			13.8 dB	10.8 dB	15.2 dB	100 +/- 32	100 +/- 7	52.0 dB	24.2 dB	23.0 dB	

Segregation class according EN50174-2:	a
--	---

Voltage

UL Voltage Rating
300 V RMS

Temperature Range

Installation Temp Range:	-40°C To +60°C
Non-UL Temp Rating:	+75°C
Storage Temp Range:	-40°C To +75°C
Operating Temp Range:	-40°C To +75°C

Mechanical Characteristics

Cold Bend Test:	-40°C Compliance Per UL 1581
Bulk Cable Weight:	49 lbs/1000ft
Max Recommended Pulling Tension:	25 lbs
Min Bend Radius During Installation:	3.75 in
Min Bend Radius/Minor Axis:	3.0 in

Standards

NEC/(UL) Specification:	N/A
ISO/IEC Compliance:	11801 ed 2.2 (2011) Class EA
Data Category:	Category 6A
ANSI Compliance:	S-116-732-2013 Category 6A, ANSI/NEMA WC-66 Category 6A
Telecommunications Standards:	ANSI/TIA 568-C.2 Category 6A
IEEE Specification:	IEEE 802.3bt Type 1, Type 2, Type 3, Type 4
Other Specification:	Outdoor Use ANSI/CEA S-56-434, Broadband Outdoor Use ANSI/CEA S-99-689, Verified Channel/Category 6A

Applicable Environmental and Other Programs

Environmental Space:	Outdoor
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	Yes
EU CE Mark:	No
EU REACH SVHC Compliance (yyyy-mm-dd):	2017-07-10
EU RoHS Compliance Date (yyyy-mm-dd):	2016-03-02

Suitability

Suitability - Aerial:	Yes - When supported by messenger wire
Suitability - Burial:	Yes - Engineered burial only
Suitability - Hazardous Locations:	No
Suitability - Indoor:	No
Suitability - Non-Halogenated:	No
Suitability - Oil Resistance:	No
Suitability - Outdoor:	Yes
Suitability - Sunlight Resistance:	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	300 V RMS
--------------------	-----------

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Putup Type	Length	UPC
OSP6AF 0101000	Black	Reel	1,000 ft	612825378839

Patent:	http://www.belden.com/p
---------	---

Product Notes

Notes:	Electrical values are expected performance based on cable testing and representative performance within a typical Belden system. Print Includes Descending Footage/Meter Markings from Max. Put-Up Length to 0. Not Suitable for Direct Burial. Belden recommends using an entrance demarcation point when transitioning inside buildings with gel-filled OSP cables due to the cable design containing gel specific for wet outdoor environments. The suggested transition point is the REVConnect core coupler, part number RVACPKUBK-S1.
--------	---

History

Update and Revision:	Revision Number: 0.150 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.