

Rittal – The System.

Faster – better – everywhere.

► Blue e Top Therm air conditioners

Guaranteed eco-efficiency, guaranteed output

High output combines with energy efficiency in TopTherm Blue e air conditioners. Eco-mode precision adjustment with the Comfort Controller keeps cooling rates steady. Nano-coated condenser coils and integrated condensate evaporator resist corrosion and reduce maintenance time and cost while maintaining reliable cooling capacity.

- Save up to 45% in energy consumption
- May be used with or without filter
- Multiple mounting positions
- UL Type, 12, 3R/4
- 1,000 – 15,000 BTU
- Available in carbon steel or 316 stainless steel
- Available in both wall mount and roof-mount versions



ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

www.rittal.us



Roof-mounted air conditioner

RAL 7035 Part No.	Total Cooling Output L95 L95 BTU (w)	Dimensions H x W x D inches (mm)	Voltage V, Hz	
3382.500	2115 (620)	16 x 24 x 15 (417 x 597 x 380)	230, 50/60	
3382.510			115, 50/60	
3359.500	2695 (790)		230, 50/60	
3359.510			115, 50/60	
3359.540			400, 2~, 50/60	
3383.500	3719 (1090)	16 x 24 x 19 (417 x 597 x 475)	230, 50/60	
3383.510			115, 50/60	
3383.540			400, 2~, 50/60	
3384.500	5630 (1650)		230, 50/60	
3384.510			115, 50/60	
3384.540			400, 2~, 50/60	
3385.500	7302 (2140)		19 x 31 x 23 (470 x 796 x 580)	230, 50/60
3385.510				115, 50/60
3385.540				400, 2~, 50/60
3386.540	11260 (3300)	19 x 31 x 23 (470 x 796 x 580)	400, 3~, 50 460, 3~, 60	
3387.540	13649 (4000)		400, 3~, 50 460, 3~, 60	

Wall-mounted air conditioner

RAL 7035 Part No.	Total Cooling Output L95 L95 BTU (w)	Dimensions H x W x D inches (mm)	Voltage V, Hz
3302.100	1296 (380)	22 x 11 x 6 (550 x 280 x 140)	230, 50/60
3302.110			115, 60
3303.500	2252 (660)	22 x 11 x 8 (550 x 280 x 200)	230, 50/60
3303.510			115, 50/60
3361.500	3037 (890)	22 x 11 x 11 (550 x 280 x 280)	230, 50/60
3361.510			115, 50/60
3361.540			400, 2~, 50/60
3304.500	4265 (1250)	37 x 16 x 10 (950 x 400 x 260)	230, 50/60
3304.510			115, 50/60
3304.540			400, 3~, 50 460, 3~, 60
3305.500	6005 (1760)		230, 50/60
3305.510			115, 50/60
3305.540			400, 3~, 50 460, 3~, 60
3328.500	8735 (2560)	62 x 16 x 11 (1580 x 400 x 295)	230, 50/60
3328.510			115, 50/60
3328.540			400, 3~, 50 460, 3~, 60
3329.500	9246 (2710)		230, 50/60
3329.510			115, 50/60
3329.540			400, 3~, 50 460, 3~, 60
3332.540	14842 (6350)	62 x 20 x 13 (1580 x 500 x 340)	400, 3~, 50 460, 3~, 60

Note: Imperial measurements are approximate, metric measurements are exact.

Rittal North America LLC

Woodfield Corporate Center • 425 North Martingale Road, Suite 400 • Schaumburg IL 60173

Toll-free: 800-477-4000 • Email: rittal@rittal.us • www.rittal.us