

## Anybus Communicator Common Ethernet to Common Ethernet ATEX

Item number: ABC4090EX-A

The Anybus Communicator Common Ethernet to Common Ethernet ATEX enables you to connect any device or equipment to PROFINET, EtherCAT, EtherNet/IP, and Modbus TCP control systems. Anybus Communicators ensure reliable, secure, and high-speed data transfers. The intuitive user interface makes them incredibly easy to use.



*A protocol converter that connects devices to Industrial Ethernet control systems*

### Features and benefits

#### ✓ Certified for hazardous locations

The Communicator is certified for ATEX Zone 2 and UL hazardous location Class 1 Division 2.

#### ✓ Instant data transfer

Instant data transfer lets you take advantage of high-speed industrial networks.

#### ✓ Intuitive user interface

Use the intuitive web-based user interface to easily configure the Communicator via the drag-and-drop functionality or to analyze live data and generate support packages.

#### ✓ Optimized hardware design

The Communicator has forward-facing ports and is designed for IP20 and DIN-rail mounting, enabling you to install it with ease, close to connected devices, thereby reducing wiring requirements.

#### ✓ 5-year warranty

Thanks to carefully selected industrial components the Communicator operates reliably in harsh environments, ensuring uptime and longevity. Our confidence in quality is reflected in a 5-year warranty.

#### ✓ High performance

Powered by the award-winning NP40 network processor, it enables instant transfer of up to 1500 bytes (network dependent) between networks, totaling 3000 bytes.

#### ✓ Endian conversion

The Communicator provides hardware-accelerated endian conversion (byte swap), saving processing time on the PLC.

#### ✓ Cybersecurity

Despite advanced security, human error often causes breaches. Our Communicator's physical security switch can lock configurations and block web interface access, enhancing security.

#### ✓ Diagnostics

The user interface displays real-time connection status and I/O data mapping for easy troubleshooting. Easily generate a support file containing all the necessary information.

#### ✓ Life cycle management

HMS maintains every part of the Communicator, including network updates, throughout the product's lifecycle.

# Anybus Communicator Common Ethernet to Common Ethernet ATEX



General	
Net Width (mm)	27
Net Height (mm)	144
Net Depth (mm)	98
Net Weight (g)	150
Packed Width (mm)	35
Packed Height (mm)	170
Packed Depth (mm)	115
Packed Weight (g)	185
Operating Temperature °C Max	70
Storage Temperature °C Min	-40
Storage Temperature °C Max	85
Power Connector	3-pin, 5.08 Phoenix plug connector
Reverse Polarity Protection	Yes
Short Circuit Protection	Yes
Isolation	TRUE
Mounting	DIN-rail (EN 50022 standard)
Housing Materials	PC ABS, UL 94 VO
Packaging Material	Cardboard
Warranty (years)	5

# Anybus Communicator Common Ethernet to Common Ethernet ATEX



## Identification and Status

Product ID	ABC4090EX-A
Model Code	40-ETH-ETH-B-EX
Country of Origin	Sweden
HS Code	8517620000
Dual Usage	No
Export Control Classification Number (ECCN)	5A991.b.1

## Physical Features

Push Buttons	Factory reset
Contains Battery	No

## EtherCAT Features

EtherCAT Bandwidth	10/100 Mbit down to 1ms cycle time
EtherCAT Input Data Size	1500 bytes
EtherCAT Output Data Size	1500 bytes

## EtherNet/IP Features

EtherNet/IP Bandwidth	10/100MBit down to 1ms cycle time
EtherNet/IP Input Data Size	1448 bytes
EtherNet/IP Output Data Size	1448 bytes

## Modbus-TCP Features

Modbus-TCP Supported Functionality	Modbus specification V1.1b3; 4 connections; Daisy chaining
Modbus-TCP Functions Supported	1, 2, 3, 4, 5, 6, 15, 16, 23, 43/14
Modbus-TCP Bandwidth	10/100 Mbit/s
Modbus-TCP Input Data Size	1500 bytes
Modbus-TCP Output Data Size	1500 bytes

# Anybus Communicator Common Ethernet to Common Ethernet ATEX



## PROFINET Features

<b>PROFINET Bandwidth</b>	10/100MBit down to 1ms cycle time
<b>PROFINET Input Data Size</b>	1024 bytes
<b>PROFINET Output Data Size</b>	1024 bytes

## Certifications and Standards

<b>Protection Class IP</b>	IP20
<b>CE</b>	Yes
<b>UL</b>	Yes
<b>ATEX</b>	Yes
<b>ATEX Information</b>	II 3 G Ex ec IIC T4 Gc, EN IEC 60079-0, 60079-7, IEC 60664-1
<b>EMC</b>	Yes
<b>Environment</b>	EN 55016-2-3 Class A, EN 55032 Class A, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-8
<b>WEEE Category</b>	IT and telecommunications equipment



## Use Case



The communicator can be used wherever there is a need to transfer data between control systems using different industrial protocols.