CHAINWAY®



C70

Thermometry Mobile Data Terminal























Android 4G Wi-Fi 1D Barcode Bluetooth

Camera

Chainway C70 is a high-performance intelligent handheld terminal which designed for temperature measurement. It is developed based on Android system, with high-performance processor, first-class configuration and fast operation, this device can be widely used in multiple temperature measurement scenarios. Temperature measurement module on top is more convenient for the user to operate, and helps the user to quickly realize information management and improve work efficiency.



Specification

Performance	
CPU	Octa-core 2.3 GHz
RAM+ROM	3GB+32GB / 4GB+64GB
Expansion	Supports up to 256GB Micro SD (TF) card
Operating System	Android 11; SafeUEM supported. Committed support for a future upgrade to Android 12, 13, and Android 14 pending feasibility
Communication	

	Teasibility		
Communica	Communication		
WLAN	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna		
	2G: GSM850/GSM900/DCS1800/PCS1900		
WWAN	3G: WCDMA; BI/B2/B4/B5/B8 CDMA2000 EVDO: BC0 TD-SCDMA: A/F		
	4G: B1/B2/B3/B4/B5/B7/B8/B12/B17/B20/B28A/B28B/ B34/B38/B39/B40/B41		
Bluetooth	Bluetooth 5.0		
GNSS	GPS/AGPS, GLONASS, BeiDou; internal antenna		

Physical Characteristics	
Dimensions	163.8 x 79.2 x 13.8 mm / 6.45 x 3.12 x 0.54 in.
Weight	242g / 8.5oz.
Display	5.2" IPS LTPS 1920 x 1080
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Expansion Slot	1 slot for Nano SIM card, 1 slot for Nano SIM or TF card
Interfaces	USB2.0 Type-C, OTG, supports TypeC headphones
Sensors	Light sensor, proximity sensor, gravity sensor
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; receiver
Keypad	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
	Main battery: Li-ion, rechargeable, 4000mAh
	Standby: over 300 hours
Power	Continuous use: over 12 hours (depending on user environment)
	Charging time: 2-3 hours (with standard adaptor and USB cable)

Developing Environment		
SDK	Software Development Kit	
Language	Java	
Tool	Eclipse / Android Studio	

User Environment	
Operating Temp.	-4°F to 122°F / -20°C to 50°C
Storage Temp.	-40°F to 158°F / -40°C to 70°C
Humidity	5%RH - 95%RH non condensing
Drop Specification	Multiple 1.8m / 5.9ft drops (at least 20 times) to the concrete across the operating temperature range
Tumble Specification	1000 x 0.5m/1.6ft falls at room temperature
Sealing	IP65 / IP67 per IEC sealing specifications
ESD	±15KV air discharge, ±6KV conductive discharge

Data Collection

Temperature Collection	
Measure Position	Human forehead / Object surface
Measure Method	Non-contact / Infrared
Measure Distance	1-3 cm
Measure Range	Human forehead: 32°C to 42.9°C; Object surface: -40°C to 115°C;
Measure Accuracy	Human forehead: ±0.2°C; Object surface: ±0.5°C;
Measure Duration	1 sec
Spectral Range	5.5 -15 μm
Resolution	0.02°C

^{*}The infrared module has 80 degrees limitation, the best measure angle should be in this range.

be in this range.	
Camera	
Rear Camera	13MP Autofocus with flash
Front Camera (optional)	5MP camera
NFC	
Frequency	13.56MHz
Protocol	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
Chips	M1 card (S50, S70), CPU card, NFC tags, etc.
Range	2-4cm

Barcode Scanning (Optional)	
2D Imager Scanner	Zebra SE4710 / Honeywell N6603
1D Symbologies	UPC/EAN, Code128, Code39, Code93, Code11, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, MSI, RSS, etc.
2D Symbologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal (KIX) etc

Accessories(See details in Accessory Guide)













ional) Holster(Optional)

AC Adaptor USB Cable Sim Tray Ejector Lanyard Cradle (Optional)

Notice: Product specifications are subject to change without prior notice. / Model: C70 / Update Date: 2024-06-28