



MC51

Built-in RFID Reader



5G



Android 14



Wi-Fi 6E



Bluetooth 5.2



UHF



1D Barcode



2D Barcode



Camera



GNSS

The Chainway MC51 built-in RFID reader is our latest 5G high-performance, large-screen handheld terminal. It integrates a self-developed UHF module based on the Impinj E Series chips and supports Impinj Gen2X, delivering superior reading capabilities. Built with advanced technology, it features a powerful processor, a 6-inch HD display, and exceptional 5G and Wi-Fi 6E connectivity, providing frontline workers with a high-performance mobile office solution. The device also supports multiple data collection functions, including barcode scanning, RFID, and NFC, making it ideal for retail, warehouse sorting, power inspections, fixed asset management, and other industrial applications.



Specification

Physical Characteristics	
Dimensions	161.0 x 77.8 x 15.5mm (Thickest Part: 29.2mm) / 6.34 x 3.06 x 0.61 in (Thickest Part: 1.15 in.)
Weight	323g / 11.39oz. (device with battery)
Keypad	Power key, 2 scan keys, volume (+/-) keys, 1 multifunctional key
Battery	5000mAh removable main battery, support QC3.0 and RTC; Support Battery Management System; Hot swap battery backup
Display	6-inch high definition display (18:9), 1440 x 720
Touch Panel	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
Sensor	G_sensor, proximity sensor, light sensor, geomagnetic sensor, gyroscope
Notification	Sound, LED indicator, vibrator
Audio	2 microphones, 1 for noise cancellation; 1 speaker; 1 receiver
Card slot	1 for SIM card, 1 for SIM or TF card, Supports eSIM (optional)
Interfaces	USB Type-C, USB 3.1, OTG

Performance	
CPU	Qualcomm Octa-core, 2.4GHz
RAM+ROM	UFS: 4GB + 64GB / 8GB + 256GB (optional)
Expansion	Supports up to 256GB TF card (Supports Extreme Micro SD Card 512GB)

Developing Environment	
Operating System	Android 14
SDK	Chainway Software Development Kit
Language	Java
Tool	Eclipse / Android Studio

User Environment	
Operating Temp.	-4°F to 122°F / -20°C to +50°C
Storage Temp.	-40°F to 158°F / -40°C to +70°C
Humidity	5% RH - 95% RH non condensing
Drop Specification	Multiple 1.5m / 4.92ft. drops to the concrete across the operating temperature range MIL-STD-810H (SGS Test): Multiple 1.5 m/4.92 ft. drops to concrete across the operating temperature range
Tumble Specification	1000 x 0.5m / 1.64ft. falls at room temperature
Sealing	IP67 per IEC sealing specifications
ESD	±15 KV air discharge, ±8 KV conductive discharge

Communication	
WLAN	Support 802.11 a/b/g/n/ac/ax-6E, 2.4G/5G dual-band, IPV4, IPV6; 2*2 MIMO antennas
	Fast roaming: PMKID caching, 802.11r, OKC
	Operating Channels: 2.4G (channel 1~13), 5G (channel 36, 40, 44, 48, 52, 56, 60, 64, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 149, 153, 157, 161, 165), Depends on local regulations
	Security and Encryption: WEP, WPA/WPA2-PSK(TKIP and AES), WAPI-PSK—EAP-TTLS, EAP-TLS, PEAP-MSCHAPv2, PEAP-LTS,PEAP-GTC, WPA3-Enterprise, WPA3-Enhanced Open, WPA3 Easy Connect, WPA3-Personal, etc.

WWAN (America)	2G: GSM/EDGE/GPRS(850/1900)
	3G: WCDMA(B2/B4/B5)
	4G: FDD-LTE B2/B4/B5/B7/B12/B13/B25/B26/B28; TDD-LTE B38/B41;
WWAN (Europe, Asia)	5G: N2/N3/N5/N7/N12/N13/N25/N26/N28/N38/N41/N77/N78
	2G: GSM / EDGE / GPRS (850/900/1800)
	3G: WCDMA (B1/B5/B8)
Vo-LTE	4G: FDD-LTE (B1/B3/B5/B7/B8/B20/B28A/B28B) TDD-LTE (B34/B38/B39/B40/B41)
	5G: N1/N3/N5/N7/N8/N20/N28/N38/N40/N41/N77/N78/N79
Bluetooth	Support Vo-LTE HD video voice call
Bluetooth	Bluetooth 5.2
GNSS	GPS/AGPS, GLONASS, BeiDou, Galileo, internal antenna

Data Collection	
Camera	
Rear Camera	16MP Autofocus with flash
Front Camera	5MP
UHF RFID	

Engine	Based on Impinj E Series chips
Frequency	865-868 MHz / 920-925 MHz / 902-928 MHz
Impinj Gen2X	Supported
Protocol	EPC C1 GEN2 / ISO18000-6C
Antenna	Circular Polarized Antenna
Power	+5dBm to +30dBm adjustable
Fastest Read Rate	750+ tags/sec
Max Read Range	5m

* Ranges are measured in the open outdoors and low interference environment, and rate is measured in a laboratory low interference environment, they are affected by tags and environment.
* Built-in UHF version does not support pistol

Barcode Scanning (Optional)	
2D Scanner	Zebra: SE4710; SE55; CM60
1D Symbolologies	UPC/EAN, Code128, Code39, Code93, Code11, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, Codabar, MSI, RSS, etc.
2D Symbolologies	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX),etc.

Optional Accessories	
USB Cable, Adapter, Charging Cradle, etc.	
*See details in accessory guide	

Notice: Product specifications are subject to change without prior notice. / Model: MC51 Built-in RFID Reader/ Update Date: 2025-10-21

CHAINWAY®

Shenzhen Chainway Information Technology Co., Ltd

Address: 9F, Building2, Phase 2, Gaoxinqi Industrial Park, Liuxian 1st Rd., Bao'an District, Shenzhen, Guangdong 518102, China

Tel: 0086-755-23223316

Fax: 0086-755-23223310

Email: sales@chainway.cn

Web: http://www.chainway.net