

NTS

No Touch Request to Exit Station

The NTS No Touch Request to Exit Station uses wireless sensors to reliably allow safe egress or to activate a device with the simple wave of a hand. Designed to reduce the risk of contamination for sensitive applications including: bathrooms, hospitals, labs, schools and offices.



NTS-1

NTS-2

NTS-3

Features

Standard Features

- Stainless steel with vandal resistant face plate
- Sensor detection range up to 4"
- Bi-color Halo LED status indicators
- Plate screened "Wave To Open"
- Time delay settable for 1 to 35 seconds

Options

- **NTS-1** with single gang wall plate (4.5"H x 2.75"W)
- **NTS-2** with double gang wall plate (4.5"H x 4.5"W)
- **NTS-3** with narrow stile wall plate (4.5"H x 1.75"W)

Accessories

(available separately):

- **SMB-01, SMB-01A** Single gang surface mounting box
- **SMB-3, SMB-3D** Narrow stile surface mounting box
- **30203** Single gang, weather resistant surface mount back box

Specifications

Certifications & Listings

- CE Certified

Electrical

- SPDT relay rated 2A at 30 VDC/VAC
- Operates on 12 VDC or 24 VDC

Operating Temperature

- -13 to + 131 F (-25 to 55 C)