

# APL Series Cylindrical Indicator Locks



## Specifications:

**Door Preparation** – Requires standard 2-1/8" (54mm) bore with through bolts.

**Backset** – 2-3/8" (60mm) or 2-3/4" (70mm)

**Door Thickness** – Fits 1-3/8" to 1-3/4", factory set for 1-3/4". 1-3/8" doors require the use of spacers.

**Latch** – Stainless Steel 1/2" (13mm) throw, UL Listed, spring latch

**Latch Front** – 1-1/8" x 2-1/4" for 2-3/4" (70mm) backset.

**Strike** – 4-7/8" (ANSI (124mm))

**Handing** – non-handed

**Packaging** – 6 per case


**Warranty** – Three Year Warranty

## Finishes:

Arrow Code	BHMA	U.S. Equiv.	Finish Description	
605	605	US3	Bright Brass	
613E	613E	US10BE	Dark Oxidized Satin Bronze Equivalent	
626	626	US26D	Satin Chromium Plated	
BSP	BSP	-	Black Suede Powder Coat	

## Design:

Sierra - ST



Experience a safer  
and more open world

## Professional Replacement Products


Eliminate potentially embarrassing situations and provide peace of mind with the APL Series Grade 1 cylindrical lock with status indicator. With a visual display of the occupancy status, the indicator notifies individuals if the door is locked or unlocked, providing an increased level of privacy.

## Certification & Compliance:

- Grade 1 Certified, ANSI/BHMA A156.2, Series 4000
- UL/cUL Listed for use on 3 hour, A label or lesser doors
- Lever conforms to ADA clear opening width requirements of ANSI A117.1
- Lever complies with California State Reference Code (Formerly Title 19, California State Fire Marshal Standard) with return to within 1/2" (13mm) of door face
- Patent Pending


# APL Series Cylindrical Indicator Locks

## Function:


ARROW CODE	FUNCTION	DESCRIPTION
APL02	Privacy	 <p>Latch operated by lever either side except when outside lever is locked by pushing inside button. Pushing inside button changes indicator display status outside. Outside lever unlocked by turning inside lever, using emergency coin turn, or closing door. Inside lever always operates latch.</p>

## Latches:

**Spring Latch  
Q73**  
2-3/4" Backset




**Spring Latch  
R22**  
2-3/8" Backset




## Strikes:

**#306 - Standard**




ANSI Strike

**#300**




T-Strike

**#302**



Full Lip Strike -  
Square Corner

**#303**



Full Lip Strike -  
Radius Corner

## Ordering Example:

APL      02      ST      626      306      Q73  
 |      |      |      |      |      |  
 Series    Function    Design    Finish    Strike    Latch

The ASSA ABLOY Group is the global leader in access solutions. Every day, we help billions of people experience a more open world.

