

HyperBOND FAST

RAPID-CURE EPOXY BASECOAT

FAST. STRONG. BUILT TO PERFORM.



RAPID CURE

Allows for quicker return-to-service and faster project turnaround.



MOISTURE TOLERANT

Installs over damp concrete once standing water is removed.



EXCELLENT ADHESION

Superior bond to concrete for long-lasting performance.



CHEMICAL & ABRASION RESISTANT

Withstands harsh chemicals, impact, and daily wear.



DURABLE FINISH

Smooth, self-leveling coat provides consistent build and system integrity.



PRODUCT OVERVIEW

HyperBOND Fast is a rapid-set, high-performance 100% solids epoxy engineered for superior adhesion, moisture tolerance, and accelerated return-to-service. Its water-insensitive formulation allows installation over damp concrete once standing water is removed, reducing prep constraints and enabling faster project timelines.

The smooth, self-priming viscosity supports efficient placement and consistent film build in time-sensitive conditions. When applied at specified mill thickness, HyperBOND Fast functions as a Class I or Class II vapor retarder, providing effective control of moisture vapor transmission while maintaining system integrity.

Ideal as an epoxy base coat where humidity or slab moisture is present and downtime must be minimized. Available in Grey and Tan.

IDEAL FOR:



KEY FEATURES



FAST-SET FORMULATION

Rapid cure for quicker return-to-service and project completion.



MOISTURE INSENSITIVE

Installs over damp concrete once standing water is removed.



EXCELLENT ADHESION

Bonds aggressively to properly prepared concrete surfaces.



REDUCED HUMIDITY SENSITIVITY

Performs reliably in a wide range of humidity conditions.



CHEMICAL RESISTANCE

Resists common chemicals, oils, and automotive fluids.



ABRASION RESISTANCE

Withstands heavy foot, vehicle, and equipment traffic.



ENHANCED DURABILITY

Delivers a tough, resilient surface built for long-term use.



HIGH COMPRESSIVE STRENGTH

Supports heavy loads and resists impact and wear.



BROADCAST COMPATIBLE

Works seamlessly with decorative flakes for high-performance, slip-resistant systems.



MOISTURE CONTROL

Helps manage moisture vapor transmission for a more reliable flooring system.



TIME-SAVING PERFORMANCE

Speeds up installation and gets spaces back in service sooner.



SYSTEM INTEGRITY

Self-priming and consistent film build for a strong, dependable foundation.



AVAILABLE COLORS

Grey and Tan to suit a variety of design and functional needs.