

HyperFLEX

FLEXIBLE EPOXY MEMBRANE

FLEXIBLE PROTECTION. STRONGER RESULTS.



CRACK-BRIDGING CAPABILITIES

Moves with the substrate to help prevent cracking



SUPERIOR SUBSTRATE PROTECTION

Advanced elastomeric technology



FAST DRY TIME

Enables quicker project turnaround and installation



STRONG BOND

Excellent adhesion to properly prepared concrete



PRODUCT OVERVIEW

HyperFLEX is a high-performance, flexible epoxy membrane engineered to provide exceptional crack-bridging capabilities and substrate protection. Formulated with advanced elastomeric technology, HyperFLEX delivers superior flexibility, allowing it to absorb movement in concrete and help prevent cracks from telegraphing through subsequent coatings.

Designed for professional installers, HyperFLEX features a rapid dry time, enabling faster project turnaround and making it ideal for 1-day and tight-schedule flooring systems. Its excellent adhesion promotes strong bonding to properly prepared concrete, creating a durable, resilient basecoat.

HyperFLEX enhances floor longevity by reducing coating failures associated with substrate movement, minor cracking, and thermal expansion. Can be field pigmented using E-Poly universal colorants.

IDEAL FOR:




INDUSTRIAL FACILITIES



COMMERCIAL SPACES



PARKING GARAGES



DISTRIBUTION CENTERS



KEY FEATURES



LOW VOC FORMULATION

Low odor, user-friendly, and compliant.



LOW ODOR

Minimal odor for a better working experience.



FAST CURE & FAST RETURN-TO-SERVICE

Rapid dry time gets you back on schedule.



HIGH FLEXIBILITY

Accommodates movement and reduces stress on coatings.



COLD-TEMPERATURE CURE

Cures effectively in cooler conditions.



SUPERIOR IMPACT RESISTANCE

Withstands heavy impacts and daily wear.



SUPERIOR TENSILE & TEAR STRENGTH

Durable under stress and pulls.



CRACK-BRIDGING CAPABILITIES

Helps prevent cracks from telegraphing through.



STRONG ADHESION

Excellent bond to properly prepared substrates.



BROADCAST COMPATIBLE

Ideal for decorative flakes, quartz, and aggregates.



FLEXIBLE PROTECTION

Moves with the substrate to help prevent cracking.



SAVE TIME

Rapid dry time for faster project completion.



STRONG BOND

Excellent adhesion for long-lasting results.



PROFESSIONAL RESULTS

Reliable performance you can count on.