



CB200 Acrylic Adhesive SAFETY DATA SHEET

ACCORDING TO EC-REGULATIONS 1907/2006 (REACH), 1272/2008 (CLP) & 2015/830








1. SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier	
Product Name	CB200 Acrylic Adhesive.
CAS No.	Mixture.
EINECS No.	Mixture.
REACH Registration No.	None assigned.
1.2 Relevant identified uses of the substance or mixture and uses advised against	
Identified use(s)	Two component acrylic adhesive.
Uses advised against	None known.
1.3 Details of the supplier of the Safety Data Sheet	
Company Identification	Click Bond, Inc. 2151 Lockheed Way Carson City, NV 89706 USA
Telephone	+1 (775) 885 8000
E-Mail (competent person)	Glenn.Hutt@clickbond.com
1.4 Emergency telephone number	
Company	+1 (813) 248 0585
National Poisons Information Service (Birmingham Centre) , United Kingdom	111

2. SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture	
Regulation (EC) No. 1272/2008 (CLP)	
Adhesive	Flam. Liq. 2; Highly flammable liquid and vapour. Acute Tox. 4; Harmful if swallowed. Skin Corr. 1A; Causes severe skin burns and eye damage. Eye Dam. 1; Causes serious eye damage. Skin Sens. 1; May cause an allergic skin reaction. Carc. 2; Suspected of causing cancer. STOT SE 3; May cause respiratory irritation. Aquatic Chronic 3; Harmful to aquatic life with long lasting effects.
Accelerator	Org. Perox. E; Heating may cause a fire. Skin Irrit. 2; Causes skin irritation. Eye Irrit. 2; Causes serious eye irritation. Skin Sens. 1; May cause an allergic skin reaction. Aquatic Acute 1; Very toxic to aquatic life. Aquatic Chronic 1; Very toxic to aquatic life with long lasting effects. EUH205: Contains epoxy constituents. May produce an allergic reaction.

CB200 Acrylic Adhesive

2.2 Label elements	
Product name	According to Regulation (EC) No. 1272/2008 (CLP) CB200 Acrylic Adhesive.
Adhesive	
Contains	Methyl methacrylate, Methacrylic acid, N,N-dimethylaniline, 1,1'-(p-tolylimino) dipropan-2-ol
Hazard pictogram(s)	  GHS02 GHS05   GHS07 GHS08
Signal word(s)	Danger.
Hazard statement(s)	H314: Causes severe skin burns and eye damage. H317: May cause an allergic skin reaction. H351: Suspected of causing cancer. H412: Harmful to aquatic life with long lasting effects.
Precautionary statement(s)	P201: Obtain special instructions before use. P260: Do not breathe vapour. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P308+P311: IF exposed or concerned: Call a POISON CENTER/doctor. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P405: Store locked up.
Accelerator	
Contains	Epoxy resin (number average molecular weight ≤ 700), Dibenzoyl peroxide.
Hazard pictogram(s)	   GHS02 GHS07 GHS09
Signal word(s)	Warning.
Hazard statement(s)	H317: May cause an allergic skin reaction.
Precautionary statement(s)	P261: Avoid breathing vapours. P272: Contaminated work clothing should not be allowed out of the workplace. P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+P352: IF ON SKIN: Wash with plenty of water. P333+P313: If skin irritation or rash occurs: Get medical advice/attention.



CB200 Acrylic Adhesive

P362+P364: Take off contaminated clothing and wash it before reuse.

2.3 Other hazards

According to REACH Annex XIII, Not classified as PBT or vPvB.

2.4 Additional Information

For full text of H/P Statements see section 16.

3. SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

EC Classification No. 1272/2008

Adhesive

Hazardous Ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Methyl methacrylate	50-55	80-62-6	201-297-1	01-2119452498-28-0000	GHS02, Flam. Liq. 2; H225, GHS07, Skin Irrit. 2; H315, Skin Sens. 1; H317, STOT SE 3; H335
Methacrylic acid	5-10	79-41-4	201-204-4	01-2119463884-26-0000	GHS05, Skin Corr. 1A; H314, Eye Dam. 1; H318, GHS06, Acute Tox. 3; H311, GHS07, Acute Tox. 4; H302, H332, STOT SE 3; H335
2-propenoic acid, 2-methyl-, 2-hydroxyethyl ester, phosphate	1-5	52628-03-2	258-053-2	01-2119980575-25-0000	GHS05, Skin Corr. 1A; H314, Eye Dam. 1; H318, GHS07, Skin Sens. 1; H317
N,N-dimethylaniline	1-5	121-69-7	204-493-5	01-2119935241-47-0000	GHS06, Acute Tox. 3; H301, H311, H331, GHS08, Carc. 2; H351, GHS09, Aquatic Chronic 2; H411
1,1'-(p-tolylimino) dipropan-2-ol	1-5	38668-48-3	254-075-1	01-2119980937-17-0000	GHS05, Eye Dam. 1; H318, GHS06, Acute Tox. 2; H300, Aquatic Chronic 3; H412
Zinc oxide	<2	1314-13-2	215-222-5	01-2119463881-32-0000	GHS09, Aquatic Acute 1; H400, Aquatic Chronic 1; H410
2-hydroxyethyl methacrylate	<1	868-77-9	212-782-2	01-2119490169-29-0000	GHS07, Skin Irrit. 2; H315, Skin Sens. 1; H317, Eye Irrit. 2; H319

CB200 Acrylic Adhesive

Accelerator

Hazardous Ingredient(s)	%W/W	CAS No.	EC No.	REACH Registration No.	Hazard pictogram(s) and Hazard statement(s)
Epoxy resin (number average molecular weight \leq 700)	40-45	25068-38-6	500-033-5	01-2119456619-26-0000	GHS07, Skin Irrit. 2; H315, Skin Sens. 1; H317, Eye Irrit. 2; H319, GHS09, Aquatic Chronic 2; H411
Benzoic acid, C9-11-branched alkyl esters	20-25	131298-44-7	421-090-1	01-0000016763-66-0000	GHS07, Acute Tox. 4; H332
Dibenzoyl peroxide	20-25	94-36-0	202-327-6	01-2119511472-50-0000	GHS02, Org. Perox. B; H241, GHS07, Eye Irrit. 2; H319, Skin Sens. 1; H317, GHS09, Aquatic Acute 1; H400, Aquatic Chronic 1; H410

3.3 Additional Information

For full text of H/P Statements see section 16.

4. SECTION 4: FIRST AID MEASURES



4.1 Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.

Skin Contact

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.

Eye Contact

Adhesive:

If eye contact with adhesive, rinse eyes for at least 15-30 minutes. Transport to hospital or eye specialist while continuing rinsing the eyes during transportation.

Accelerator:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER/doctor.

4.2 Most important symptoms and effects, both acute and delayed

May cause allergic contact eczema. Already sensitized persons to epoxy may react on very small doses.

Adhesive:

Causes burns to skin, eyes, respiratory system and gastrointestinal tract.

4.3 Indication of any immediate medical attention and special treatment needed

IF exposed or concerned: Get medical advice/attention.



CB200 Acrylic Adhesive

5. SECTION 5: FIRE-FIGHTING MEASURES

- 5.1 Extinguishing Media**
Suitable Extinguishing Media In case of fire: Use water spray, foam, dry powder or CO₂ to extinguish.
Unsuitable Extinguishing Media None known.
- 5.2 Special hazards arising from the substance or mixture**
Adhesive: Highly flammable liquid and vapour.
Accelerator: Heating may cause a fire.
Decomposes in a fire giving off toxic fumes: Oxides of nitrogen, Carbon monoxide, Carbon dioxide. Vapours are heavier than air and may travel considerable distances to a source of ignition and flashback.
- 5.3 Advice for fire-fighters** Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Water spray should be used to cool containers.

6. SECTION 6: ACCIDENTAL RELEASE MEASURES

- 6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation. Eliminate sources of ignition. Do not breathe vapour. Wear protective gloves/ protective clothing/eye protection/face protection. Use only non-sparking tools. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash hands thoroughly after handling.
- 6.2 Environmental precautions** Avoid release to the environment.
- 6.3 Methods and material for containment and cleaning up** Cover spills with inert absorbent material. Collect spillage. Transfer to a container for disposal.
- 6.4 Reference to other sections** See Also Section: 8, 13

7. SECTION 7: HANDLING AND STORAGE

- 7.1 Precautions for safe handling** Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Do not breathe vapour. Wear protective gloves/ protective clothing/eye protection/face protection. Take off contaminated clothing and wash it before reuse. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Already sensitized persons to epoxy should not work with the product.
- 7.2 Conditions for safe storage, including any incompatibilities**
Storage temperature Store in a well-ventilated place. Keep cool. Protect from sunlight. Keep container tightly closed. Store locked up.
Storage life Stable under normal conditions.
Incompatible materials Stable under normal conditions.
Inorganic acids, organic acids, caustics, oxidising agents, peroxides, amines, water, hydroxyl, or active hydrogen compounds.
Accelerator incompatible with clothing/organic materials/ combustible materials.
- 7.3 Specific end use(s)** Two component acrylic adhesive.

CB200 Acrylic Adhesive

8. SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

Adhesive

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Methyl methacrylate	80-62-6	50	208	100	416	WEL
Methacrylic acid	79-41-4	20	72	40	143	WEL
N,N-dimethylaniline	121-69-7	5	25	10	50	WEL

Accelerator

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Dibenzoyl peroxide	94-36-0	-	5	-	-	WEL

Source: WEL: Workplace Exposure Limit (UK HSE EH40)

8.1.2 Biological limit value

Not established.

8.1.3 PNECs and DNELs

Not established.

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Provide adequate ventilation. Local exhaust recommended.

8.2.2 Personal protection equipment

Eye/face protection



Wear protective eye glasses for protection against liquid splashes.

Skin protection (Hand protection/ Other)



Where hand contact with the product may occur, the use of gloves (approved according to the EN374 standard) made from the following materials may provide suitable chemical protection: Nitrile rubber.

For short-term/splash protection we recommend nitrile disposable gloves in the 0,20 – 0,35 mm thickness range with a minimum of >30min break-through times.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for >480 minutes, such as 2,7mm thickness North Silver Shield.

Lower breakthrough time may be acceptable if appropriate glove maintenance and replacement regimes are rigorously followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Suitability and durability of a glove is dependent on usage (= frequency and duration of contact), chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands.

CB200 Acrylic Adhesive

Respiratory protection



Thermal hazards

8.2.3 Environmental exposure controls

After using gloves, hands should be washed and dried thoroughly.

Wear suitable respiratory protective equipment if exposure to levels above the occupational exposure limit is likely.

Wear: A respirator fitted with the following cartridge: Organic vapour filter; Gas filtering respirator (DIN EN 14387).

Not applicable.

Avoid release to the environment.

9. SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties	Adhesive	Accelerator
Appearance	Liquid.	Paste.
Colour	White/Off-white.	White/Off-white.
Odour	Sweet-smelling.	Odourless.
Odour Threshold	Not determined.	Not determined.
pH	Not available.	Not available.
Melting Point/Freezing Point	Not available.	Not available.
Initial boiling point and boiling range	Not available.	Not available.
Flash point	18°C [Closed cup]	>93°C
Evaporation rate	No data.	Not available.
Flammability (solid, gas)	Not applicable.	Not applicable.
Upper/lower flammability or explosive limits	Not available.	Not applicable.
Vapour pressure	Not available.	Not available.
Vapour density	No data.	No data.
Relative density	1.02 - 1.04 @ 20°C	1.2 @ 20°C
Solubility (Water)	Insoluble.	Insoluble.
Partition coefficient: n-octanol/water	Not available.	Not available.
Auto-ignition temperature	Not available.	Not available.
Decomposition Temperature	Not available.	Not available.
Viscosity	15k - 55k mPa*s @ 25°C	Not available.
Explosive properties	Not explosive.	Not explosive.
Oxidising properties	Not oxidising.	Not oxidising.
9.2 Other information	VOC Content: <1%	VOC Content: <1%

10. SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity	Stable under normal conditions.
10.2 Chemical stability	Stable under normal conditions.
10.3 Possibility of hazardous reactions	No hazardous reactions known if used for its intended purpose.
10.4 Conditions to avoid	Heat and direct sunlight.
10.5 Incompatible materials	Inorganic acids, organic acids, caustics, oxidising agents, peroxides, amines, water, hydroxyl, or active hydrogen compounds. Accelerator incompatible with clothing/organic materials/combustible materials.
10.6 Hazardous Decomposition Product(s)	No hazardous decomposition products known.



CB200 Acrylic Adhesive

11. SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity	
Oral	Adhesive Harmful if swallowed. Calculated acute toxicity estimate (ATE): 1506.77 mg/kg
Dermal	Adhesive Low acute toxicity. Calculated acute toxicity estimate (ATE): 4717.03 mg/kg
Inhalation	Adhesive Low acute toxicity. Calculated acute toxicity estimate (ATE): 167.17 mg/l
Skin corrosion/irritation	Adhesive Causes severe skin burns. No data.
Serious eye damage/irritation	Accelerator Causes skin irritation. No data. Adhesive Causes serious eye damage. No data. Accelerator Causes serious eye irritation. No data.
Respiratory or skin sensitisation	May cause an allergic skin reaction. No data.
Germ cell mutagenicity	There is no evidence of mutagenic potential.
Carcinogenicity	Adhesive Suspected of causing cancer. No data.
Reproductive toxicity	Not classified.
STOT - single exposure	Adhesive May cause respiratory irritation. No data.
STOT - repeated exposure	None anticipated.
Aspiration hazard	Not classified.
11.2 Other information	None.

12. SECTION 12: ECOLOGICAL INFORMATION


12.1 Toxicity	Adhesive Harmful to aquatic life with long lasting effects. No data. Accelerator Very toxic to aquatic life with long lasting effects. No data.
12.2 Persistence and degradability	Part of the components are biodegradable.
12.3 Bioaccumulative potential	The product has low potential for bioaccumulation.
12.4 Mobility in soil	Practically insoluble. The product is predicted to have low mobility in soil.
12.5 Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
12.6 Other adverse effects	None anticipated.

13. SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods	Do not allow to enter drains, sewers or watercourses. Dispose of this material and its container as hazardous waste. Low hazard once fully cured. Dispose of contents/container to: Suitable refuse site.
13.2 Additional Information	Disposal should be in accordance with local, state or national legislation.

CB200 Acrylic Adhesive

14. SECTION 14: TRANSPORT INFORMATION

14.1 UN number	ADR UN No.	UN3269
14.2 UN Proper Shipping Name	Proper Shipping Name (ADR)	POLYESTER RESIN KIT.
14.3 Transport hazard class(es)		
14.3.1	ADR/RID Class	3
14.3.2	IMDG Class	3
14.3.3	IMDG EMS	Not available
14.3.4	ICAO/IATA	
	Excepted Quantities	E0
	Passenger and Cargo Aircraft Limited Quantities	Y370
	Packing Instructions	
	Passenger and Cargo Aircraft Limited Quantities	1kg
	Max net Qty	
	Passenger and Cargo Aircraft Packing Instructions	370
	Passenger and Cargo Aircraft Max net Qty	5Kg
	Cargo Aircraft Packing Instructions	370
	Cargo Aircraft Max net Qty	5kg
	Special Provisions	A66
	Emergency Response Guidebook (ERG) Code	3L
	ADR Classification Code	F3
	ADR HIN	Not applicable
	ADR Transport Category	2
	Tunnel Restriction Code	E
	Emergency Action Code	•2YE
	Advice on Additional Personal Protection (APP)	Not applicable
14.4 Packing Group		
14.4.1	Packing group	II
14.4.2	Labels	3
		
14.4.3	Special Provisions	236 340
14.4.4	Limited Quantities	5 L
14.4.5	Excepted Quantities	E0
14.4.6	Mixed Packing Instructions for Packages	P302 R001
14.4.7	Special Packing Provisions for Packages	Not applicable.
14.4.8	Mixed Packing Instructions for Packages	Not applicable.
14.5 Environmental hazards		Classified as a Marine Pollutant. (Accelerator)
14.6 Special precautions for user		None known.
14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code		Not applicable.
14.7.1	Packing Instructions for Portable Tanks	Not applicable.
14.7.2	Special Provisions for Portable Tanks	Not applicable.
14.7.3	Tank Code for Tanks	Not applicable.
14.7.4	Special Provisions for Tanks	Not applicable.
14.7.5	Vehicle for Tank Carriage	Not applicable.
14.7.6	Special Provisions for Carriage - Packages	Not applicable.
14.7.7	Special Provisions for Carriage - Bulk	Not applicable.
14.7.8	Special Provisions for Carriage - Loading, Unloading and Handling	Not applicable.
14.7.9	Special Provisions for Carriage - Operation	S2 S20



CB200 Acrylic Adhesive

15. SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture	
15.1.1 EU regulations	
Authorisations and/or restrictions on use	
Candidate List of Substances of Very High Concern for Authorisation	All chemicals are not listed.
REACH: ANNEX XIV List of substances subject to authorisation	All chemicals are not listed.
REACH: ANNEX XVII Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles	Adhesive: Listed Methyl methacrylate (CAS No.: 80-62-6)
Community Rolling Action Plan (CoRAP)	Adhesive: Listed Methyl methacrylate (CAS No.: 80-62-6) Zinc oxide (CAS No.: 1314-13-2) 2-hydroxyethyl methacrylate (CAS No.: 868-77-9)
	Accelerator: Listed Epoxy resin (number average molecular weight ≤ 700) (CAS No.: 25068-38-6) None known.
15.1.2 National regulations	None known.
15.2 Chemical Safety Assessment	Not applicable.

16. SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 2-13, 15, 16

LEGEND

LTEL	Long Term Exposure Limit
STEL	Short Term Exposure Limit
DNEL	Derived No Effect Level
PNEC	Predicted No Effect Concentration
STOT	Specific Target Organ Toxicity
PBT	Persistent, Bioaccumulative and Toxic
vPvB	very Persistent and very Bioaccumulative
Flam. Liq. 2	Flammable liquids Category 2
Org. Perox. B	Organic peroxides Type B
Org. Perox. E	Organic peroxides Type E
Acute Tox. 2	Acute toxicity Category 2
Acute Tox. 3	Acute toxicity Category 3
Acute Tox. 4	Acute toxicity Category 4
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2	Serious eye damage/eye irritation Category 2
Skin Sens. 1	Respiratory or skin sensitisation Category 1
Carc. 2	Carcinogenicity Category 2
STOT SE 3	Specific target organ toxicity - single exposure Category 3
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Category 3

CB200 Acrylic Adhesive**Hazard Statement(s) and Precautionary Statement(s)**

H225	Highly flammable liquid and vapour.
H241	Heating may cause a fire or explosion.
H242	Heating may cause a fire.
H300	Fatal if swallowed.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P234	Keep only in original container.
P242	Use only non-sparking tools.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P310	Immediately call a POISON CENTER/doctor.
P312	Call a POISON CENTER/doctor if you feel unwell.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use water spray, foam, dry powder or CO2 to extinguish.
P391	Collect spillage.
P403+P235	Store in a well-ventilated place. Keep cool.
P410	Protect from sunlight.
P501	Dispose of contents/container to: Suitable refuse site.

Hazard Pictogram(s)

GHS02



GHS05



CB200 Acrylic Adhesive

GHS06



GHS07



GHS08



GHS09

**Disclaimers**

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose.

Click Bond, Inc. gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law.

Click Bond, Inc. accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.

Annex to the extended Safety Data Sheet (eSDS)

Not applicable.