

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name:	DAPCO™ 18-4F Firewall Sealant, Part A
Product Description:	Mixture of polysiloxanes and fillers
Synonyms:	None
Chemical Family:	Silicone
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Intended/Recommended Use:	Engineered material sealant

CYTEC INDUSTRIES INC., FIVE GARRET MOUNTAIN PLAZA, WOODLAND PARK, NEW JERSEY 07424, USA
For Product and all Non-Emergency Information call 1-800/652-6013. Outside the USA and Canada call 1-973/357-3193.

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

Asia Pacific:

Australia - +61-3-9663-2130 or 1800-033-111 (IXOM)

China (PRC) - +86 0532 83889090 (NRCC)

New Guinea - +61-3-9663-2130 or 1800-033-111

New Zealand - +61-3-9663-2130 or 0800-734-607 (IXOM)

India, Japan, Korea, Malaysia, Thailand - +65 3158 1074 (Carechem24 Singapore)

India (Hindi Speaking Only) - +65 3158 1198 or 000800 100 7479 (Carechem24 Singapore)

Canada: +1-905-356-8310 (Cytec Welland, Canada plant)

Europe/Africa/Middle East (Carechem24 UK):

Europe, Middle East, Africa, Israel - +44 (0) 1235 239 670

(Arabic speaking countries) - +44 (0) 1235 239 671

Latin America:

Brazil - 0800 7077 022 (SUATRANS)

Chile - +56-2-2-247-3600 (CITUC QUIMICO)

All Others - +52-376-73 74122 (Cytec Atequiza, Mexico plant)

USA: +1-703-527-3887 or 1-800-424-9300 (CHEMTREC #CCN6083)

The ® indicates a Registered Trademark in the United States and the ™ indicates a trademark in the United States. The mark may also be registered, subject of an application for registration, or a trademark in other countries.

2. HAZARDS IDENTIFICATION

GHS Classification

Carcinogenicity Hazard Category 1A

Specific Target Organ Toxicity - Repeated Exposure Hazard Category 1

Skin Corrosion / Irritation Hazard Category 2

Serious Eye Damage / Eye Irritation Hazard Category 1

LABEL ELEMENTS



Signal Word

Danger

Hazard Statements

May cause cancer

Causes damage to organs through prolonged or repeated exposure

Causes skin irritation

Causes serious eye damage

Precautionary Statements

Obtain special instructions before use.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not breathe dust/fume/gas/mist/vapours/spray.

Wash face, hands and any exposed skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

IF ON SKIN: Wash with plenty of soap and water.

Specific treatment (see supplemental first aid instructions on this label).

Take off all contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Store locked up.

Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance, Mixture or Article? Mixture

HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification	Carcinogen
Silica, quartz 14808-60-7	20-30	Carc. 1A (H350) STOT RE 1 (H372)	IARC 1 NTP ACGIH A2
Calcium carbonate 471-34-1	7-13	Eye Dam. 1 (H318) Skin Irrit. 2 (H315)	-
Diatomaceous earth 68855-54-9	1-2	-	-
Carbon Fiber 7440-44-0	1-2	Not Classified	-
Silica, quartz 14808-60-7	7-13	STOT RE 2 (H373)	IARC 1 NTP ACGIH A2
Silicon dioxide, amorphous 112945-52-5	1-5	Not Classified	-

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical attention immediately.

Skin Contact:

Remove contaminated clothing and shoes without delay. Wash immediately with plenty of water. Do not reuse contaminated clothing without laundering. Get medical attention if pain or irritation persists after washing or if signs and symptoms of overexposure appear.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Inhalation:

Remove to fresh air. If breathing is difficult, give oxygen. Obtain medical advice if there are persistent symptoms.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

None known

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDS

Notes To Physician:

Formaldehyde is not a component of this product, however, heating to temperatures above 150 C in the presence of air may result in the release of formaldehyde. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen. Formaldehyde is irritating to the eyes, nose, throat and skin and is a dermal sensitizer.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray or fog, carbon dioxide or dry chemical.

Extinguishing Media to Avoid:

full water jet

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus.

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure. Refer to Section 8 (Exposure Controls/Personal Protection) for appropriate personal protective equipment.

Methods For Cleaning Up:

Sweep up into containers for disposal. Flush spill area with water.

References to other sections:

See Sections 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

Precautions: Wash hands thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/clothing and eye/face protection. Do not eat, drink or smoke when using this product. Do not breathe dust.

Special Handling Statements: Heating to temperatures above 150 C (302 F) in the presence of air may result in the release of formaldehyde. Formaldehyde is a known animal carcinogen and is considered to be probably carcinogenic to humans by the International Agency for Research on Cancer and the National Toxicology Program. Formaldehyde is irritating to the eyes, nose, throat and skin and is a dermal sensitizer. The permissible exposure limit for formaldehyde should not be exceeded.

STORAGE

Store in accordance with local, state, and federal regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Utilize a closed system process where feasible. Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure when spraying or curing at elevated temperatures.

Respiratory Protection:

Where exposures are below the established exposure limit, no respiratory protection is required. Where exposures exceed the established exposure limit, use respiratory protection recommended for the material and level of exposure. A full facepiece respirator also provides eye and face protection. Cutting, grinding or sanding of parts fabricated after curing may create respirable dust particles. Respiratory protection appropriate for this dust may be required. Refer to components listed above for potential hazardous components in the dust.

Eye Protection:

Prevent eye and skin contact. Provide eye wash fountain and safety shower in close proximity to points of potential exposure. Wear eye/face protection such as chemical splash proof goggles or face shield.

Skin Protection:

Prevent contamination of skin or clothing when removing protective equipment. Barrier creams may be used in conjunction with the gloves to provide additional skin protection. Wear impermeable gloves and suitable protective clothing.

Hand Protection:

Wear impermeable gloves. Consider the porosity and elasticity data of the glove manufacturer and the specific conditions in the work place.

Additional Advice:

Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

Exposure Limit(s)

The below constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

112945-52-5 Silicon dioxide, amorphous

OSHA (PEL): 20 mppcf
 ACGIH (TLV): Not established
 Other Value: Not established

14808-60-7 Silica, quartz

OSHA (PEL): (30)/(%SiO₂ + 2) mg/m³ TWA total dust
 (250)/(%SiO₂ + 5) mppcf TWA respirable fraction
 (10)/(%SiO₂ + 2) mg/m³ TWA respirable fraction
 ACGIH (TLV): 0.025 mg/m³ respirable fraction (TWA)
 Other Value: Not established

14808-60-7 Silica, quartz

OSHA (PEL): 0.1 mg/m³ (respirable dust)
 (250)/(%SiO₂ + 5) mppcf TWA (respirable)
 (10)/(%SiO₂ + 2) mg/m³ TWA (respirable)
 (30)/(%SiO₂ + 2) mg/m³ TWA (total dust)
 ACGIH (TLV): 0.025 mg/m³ respirable fraction (TWA)
 Other Value: Not established

471-34-1 Calcium carbonate

OSHA (PEL): 15 mg/m³ total dust (TWA)
 5 mg/m³ respirable fraction (TWA)
 ACGIH (TLV): Not established
 Other Value: Not established

7440-44-0 Carbon Fiber

OSHA (PEL): Not established
 ACGIH (TLV): Not established
 Other Value: 3 fibers/cc (Cytec)

9. PHYSICAL AND CHEMICAL PROPERTIES

Color: green
 Appearance: paste
 Odor: slight characteristic
 Boiling Point: Not applicable
 Melting Point: Not applicable
 Vapor Pressure: Not available
 Specific Gravity/Density: 1.3
 Vapor Density: Not applicable
 Percent Volatile (% by wt.): Not available
 pH: Not applicable
 Saturation In Air (% By Vol.): Not applicable
 Evaporation Rate: Not applicable
 Solubility In Water: Not available
 Volatile Organic Content: Not applicable
 Flash Point: Not applicable
 Flammability (solid, gas): Not available
 Flammable Limits (% By Vol): Not applicable
 Autoignition (Self) Temperature: Not applicable
 Decomposition Temperature: Not available
 Partition coefficient (n-octanol/water): Not applicable
 Odor Threshold: Not available
 Viscosity (Kinematic): Not available

DUST HAZARD INFORMATION

Particle Size (microns): Not available

Kst (bar-m/sec):	Not available
Maximum Explosion Pressure (Pmax):	Not available
Dust Class:	Not available
Minimum Ignition Energy (MIE) (mJ):	Not available
Minimum Ignition Temperature (MIT) (°C):	Not available
Minimum Explosive Concentration (MEC) (g/m³):	Not available
Limiting Oxygen Concentration (LOC) (%):	Not available

10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions To Avoid:	None known
Polymerization:	Will not occur
Conditions To Avoid:	None known
Materials To Avoid:	Oxidizing agents fluorine Alum, ammonium salts, mercury and hydrogen acids
Hazardous Decomposition Products:	chlorine Formaldehyde oxides of carbon silicon dioxide When heated to decomposition, it emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

PRODUCT TOXICITY INFORMATION

Likely Routes of Exposure: Eyes, Skin, Respiratory System.

ACUTE TOXICITY DATA

oral	rat	Acute LD50	>2,000 mg/kg
dermal	rabbit	Acute LD50	>2,000 mg/kg
inhalation	rat	Acute LC50 4 hr	No data

LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	skin	Irritating
Acute Irritation	eye	Causes serious damage

ALLERGIC SENSITIZATION

Sensitization	skin	Not sensitizing
Sensitization	respiratory	No data

GENOTOXICITY

Assays for Gene Mutations

Ames Salmonella Assay	No data
-----------------------	---------

OTHER INFORMATION

The product toxicity information above has been estimated.

HAZARDOUS INGREDIENT TOXICITY DATA

Silica, quartz dust may cause mechanical irritation of the eyes. Prolonged or repeated contact may have a drying effect on the skin and may also cause irritation (skin abrasion). Exposure to dust generated during handling or use may irritate the nose, throat and upper respiratory tract. Silica, quartz is not expected to produce dermal sensitization. The chronic health effects are associated with respirable particles of 3-4 microns over extended periods of time. Currently, there is limited understanding of the mechanisms of quartz toxicity, including its mechanism for lung carcinogenicity. Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lung, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP based on human evidence.

Calcium carbonate has an acute oral (rat) LD50 of 6.5 g/kg. Direct contact will cause moderate skin and severe eye irritation. Inhalation of dust can cause mild respiratory irritation.

Overexposure to diatomaceous earth by inhalation, skin, oral, or dermal route is not expected to cause adverse effects. It is considered a nuisance dust.

Carbon fibers may cause mechanical irritation of the eyes, skin, nose and throat. Airborne carbon fibers are not considered respirable. A typical carbon fiber may be characterized as having a diameter of 5-7 microns and a length greater than 100 microns. Fibers with diameters greater than 3.5 microns are not considered respirable.

Quartz silica (respirable fraction) can cause reduced pulmonary function when inhaled. Exposure to respirable quartz silica can cause delayed (chronic) fibrosis and other lung injury. Chronic inhalation exposure showed that quartz silica can cause lung cancer in rats but not in mice. There is also limited human evidence which shows an association of lung cancer with occupational exposure to quartz silica. This material is reported to have shown positive results in in vitro mutagenicity tests with human cell cultures. Studies have shown that tobacco smoking and high quartz silica exposure exhibit a synergistic effect for lung cancer. Silica, crystalline is a chemical known to the State of California to cause cancer.

Silicon Dioxide has acute oral (rat) LD50 values ranging from 3160 mg/kg to >7500 mg/kg. The LC50 (rat) following a 4-hour inhalation study is >0.25 mg/L (maximum attainable concentration). Chronic and sub-chronic inhalation tests with laboratory animals produced lung damage and death after the lung clearance mechanisms were overloaded. Amorphous silica does not cause the lung diseases crystalline silica is known to cause.

California Proposition 65 Warning (applicable in California only) - This product contains (a) chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

This material is not classified as dangerous for the environment.

The ecological assessment for this material is based on an evaluation of its components.

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Algae	Toxicity to Fish	Toxicity to Water Flea
Silica, quartz 14808-60-7	Not available	Not available	Not available
Calcium carbonate 471-34-1	Not available	Not available	Not available
Diatomaceous earth 68855-54-9	Not available	Not available	Not available
Carbon Fiber 7440-44-0	Not available	Not available	Not available
Silica, quartz 14808-60-7	Not available	Not available	Not available
Silicon dioxide, amorphous 112945-52-5	EC50 = 440 mg/L - Pseudokirchneriella subcapitata (72h)	LC50 = 5000 mg/L - Brachydanio rerio (96h) static	EC50 = 7600 mg/L - Ceriodaphnia dubia (48h)

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this MSDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this MSDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? Not applicable/Not regulated

TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

IMO

Dangerous Goods? Not applicable/Not regulated

15. REGULATORY INFORMATION**Inventory Information**

United States (USA): All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

Canada: All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

European Economic Area (including EU): Cytec has appointed an Only Representative to relieve our customers from their registration requirements under the REACH Regulation (EC) No. 1907/2006. Please contact us if you wish to benefit from the OR arrangement.

Australia: All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory.

Philippines: All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

Switzerland: All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 16-17).

Taiwan: All components of this product are included on the Taiwan Chemical Substance Inventory (TCSI) or are not required to be listed on the Taiwan inventory.

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CLASSIFICATION UNDER SECTION 311 OF SARA

- Acute
- Chronic

16. OTHER INFORMATION**NFPA Hazard Rating (National Fire Protection Association)**

Health: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 0 - Materials that in themselves are normally stable, even under fire exposure conditions.

Reasons For Issue: Revised Section 1
Revised Section 3
Revised Section 9
Revised Section 11
Revised Section 16

Date Prepared: 02/19/2016

Date of last significant revision: 02/16/2016

Component Hazard Phrases

Silica, quartz

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

Calcium carbonate

H315 - Causes skin irritation.

H318 - Causes serious eye damage.

Silica, quartz

H373 - May cause damage to organs through prolonged or repeated exposure.

Prepared By: Legal & Compliance Services; E-mail: custinfo@cytec.com

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.



SDS: 0009051
Date Prepared: 02/19/2016

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name: DAPCO™ 18-4F Silicone Firewall Sealant, Part B
Product Description: Polysiloxane mixture
Synonyms: None
Chemical Family: Polysiloxane Mixture
Molecular Formula: Mixture
Molecular Weight: Mixture
Intended/Recommended Use: Engineered material sealant

CYTEC INDUSTRIES INC., FIVE GARRET MOUNTAIN PLAZA, WOODLAND PARK, NEW JERSEY 07424, USA
For Product and all Non-Emergency Information call 1-800/652-6013. Outside the USA and Canada call 1-973/357-3193.

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call:

Asia Pacific:

Australia - +61-3-9663-2130 or 1800-033-111 (IXOM)

China (PRC) - +86 0532 83889090 (NRCC)

New Guinea - +61-3-9663-2130 or 1800-033-111

New Zealand - +61-3-9663-2130 or 0800-734-607 (IXOM)

India, Japan, Korea, Malaysia, Thailand - +65 3158 1074 (Carechem24 Singapore)

India (Hindi Speaking Only) - +65 3158 1198 or 000800 100 7479 (Carechem24 Singapore)

Canada: +1-905-356-8310 (Cytec Welland, Canada plant)

Europe/Africa/Middle East (Carechem24 UK):

Europe, Middle East, Africa, Israel - +44 (0) 1235 239 670

(Arabic speaking countries) - +44 (0) 1235 239 671

Latin America:

Brazil - 0800 7077 022 (SUATRANS)

Chile - +56-2-2-247-3600 (CITUC QUIMICO)

All Others - +52-376-73 74122 (Cytec Atequiza, Mexico plant)

USA: +1-703-527-3887 or 1-800-424-9300 (CHEMTREC #CCN6083)

The ® indicates a Registered Trademark in the United States and the ™ indicates a trademark in the United States. The mark may also be registered, subject of an application for registration, or a trademark in other countries.

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable Liquid Hazard Category 4

Carcinogenicity Hazard Category 1A

Reproductive Toxicant Category 2

Specific Target Organ Toxicity - Repeated Exposure Hazard Category 1

LABEL ELEMENTS



Signal Word

Danger

Hazard Statements

Combustible liquid
May cause cancer
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Wear protective gloves/protective clothing/eye protection/face protection.
Obtain special instructions before use.
Do not breathe dust/fume/gas/mist/vapours/spray.
Wash face, hands and any exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
In case of fire: Use CO2, dry chemical, or foam for extinction.
IF exposed or concerned: Get medical advice/attention.
Get medical advice/attention if you feel unwell.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Not applicable

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification	Carcinogen
Silica, quartz 14808-60-7	5 - 10	Carc. 1A (H350) STOT RE 1 (H372)	IARC 1 NTP ACGIH A2
Toluene 108-88-3	0.1 - 0.5	Flam. Liq. 2 (H225) Repr. 2 (H361) STOT RE 2 (H373) STOT SE 3 (H336) Skin Irrit. 2 (H315) Eye Irrit. 2B (H320) Asp. Tox. 1 (H304) Aquatic Acute 2 (H401) Aquatic Chronic 3 (H412)	-

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes.

Skin Contact:

Wash immediately with plenty of water and soap.

Ingestion:

If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

Inhalation:

Material is not expected to be harmful if inhaled. Remove to fresh air.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

None known

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDS

Notes To Physician:

Formaldehyde is not a component of this product, however, heating to temperatures above 150 C in the presence of air may result in the release of formaldehyde. The International Agency for Research on Cancer (IARC) has classified formaldehyde as a Group 1 (known) human carcinogen. Formaldehyde is irritating to the eyes, nose, throat and skin and is a dermal sensitizer.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray, carbon dioxide or dry chemical.

Extinguishing Media to Avoid:

full water jet

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus.

Special Hazards:

Keep containers cool by spraying with water if exposed to fire.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is known, wear approved respirator suitable for level of exposure. Where exposure level is not known, wear approved, positive pressure, self-contained respirator. In addition to the protective clothing/equipment in Section 8 (Exposure Controls/Personal Protection), wear impermeable boots.

Methods For Cleaning Up:

Cover spills with some inert absorbent material; sweep up and place in a waste disposal container. Flush spill area with water.

References to other sections:

See Sections 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

7. HANDLING AND STORAGE

Precautions: Keep away from heat, sparks and open flame. - No smoking. Wear protective gloves and eye/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe vapors or spray mist.

Special Handling Statements: Heating to temperatures above 150 C (302 F) in the presence of air may result in the release of formaldehyde. Formaldehyde is a known animal carcinogen and is considered to be probably carcinogenic to humans by the International Agency for Research on Cancer and the National Toxicology Program. Formaldehyde is irritating to the eyes, nose, throat and skin and is a dermal sensitizer. The permissible exposure limit for formaldehyde should not be exceeded.

STORAGE

None

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Engineering controls are not usually necessary if good hygiene practices are followed.

Respiratory Protection:

Where exposures are below the established exposure limit, no respiratory protection is required. Where exposures exceed the established exposure limit, use respiratory protection recommended for the material and level of exposure.

Eye Protection:

Wear eye/face protection such as chemical splash proof goggles or face shield.

Skin Protection:

Avoid skin contact. Wear impermeable gloves and suitable protective clothing.

Hand Protection:

Wear impermeable gloves. Consider the porosity and elasticity data of the glove manufacturer and the specific conditions in the work place.

Additional Advice:

Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. It is recommended that a shower be taken after completion of workshift especially if significant contact has occurred. Work clothing should then be laundered prior to reuse. Street clothing should be stored separately from work clothing and protective equipment. Work clothing and shoes should not be taken home.

Exposure Limit(s)

The below constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

No values have been established.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	blue
Appearance:	liquid
Odor:	mild
Boiling Point:	Not available
Melting Point:	Not applicable

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure:	Not available
Specific Gravity/Density:	1.1
Vapor Density:	Not applicable
Percent Volatile (% by wt.):	Not available
pH:	Not available
Saturation In Air (% By Vol.):	Not available
Evaporation Rate:	Not available
Solubility In Water:	Not available
Volatile Organic Content:	Not available
Flash Point:	>82.8 °C 181 °F Closed Cup
Flammability (solid, gas):	Not available
Flammable Limits (% By Vol):	Not applicable
Autoignition (Self) Temperature:	Not applicable
Decomposition Temperature:	Not available
Partition coefficient (n-octanol/water):	Not applicable
Odor Threshold:	Not available
Viscosity (Kinematic):	Not applicable

DUST HAZARD INFORMATION

Particle Size (microns):	Not applicable
Kst (bar-m/sec):	Not applicable
Maximum Explosion Pressure (Pmax):	Not applicable
Dust Class:	Not applicable
Minimum Ignition Energy (MIE) (mJ):	Not applicable
Minimum Ignition Temperature (MIT) (°C):	Not applicable
Minimum Explosive Concentration (MEC) (g/m³):	Not applicable
Limiting Oxygen Concentration (LOC) (%):	Not applicable

10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions To Avoid:	None known
Polymerization:	Will not occur
Conditions To Avoid:	None known
Materials To Avoid:	Oxidizing agents Acids Bases
Hazardous Decomposition Products:	Formaldehyde oxides of carbon Oxides of nitrogen hydrogen silicon dioxide

11. TOXICOLOGICAL INFORMATION

PRODUCT TOXICITY INFORMATION

Likely Routes of Exposure: Eyes, Skin, Oral.

ACUTE TOXICITY DATA

oral	rat	Acute LD50	>2000 mg/kg
dermal	rabbit	Acute LD50	>2000 mg/kg
inhalation	rat	Acute LC50 4 hr	>5.0 mg/l (Dust/Mist)

LOCAL EFFECTS ON SKIN AND EYE

Acute Irritation	skin	Not irritating
Acute Irritation	eye	Not irritating

ALLERGIC SENSITIZATION

Sensitization	skin	Not sensitizing
Sensitization	respiratory	No data

GENOTOXICITY**Assays for Gene Mutations**

Ames Salmonella Assay	No data
-----------------------	---------

OTHER INFORMATION

The product toxicity information above has been estimated.

HAZARDOUS INGREDIENT TOXICITY DATA

Silica, quartz dust may cause mechanical irritation of the eyes. Prolonged or repeated contact may have a drying effect on the skin and may also cause irritation (skin abrasion). Exposure to dust generated during handling or use may irritate the nose, throat and upper respiratory tract. Silica, quartz is not expected to produce dermal sensitization. The chronic health effects are associated with respirable particles of 3-4 microns over extended periods of time. Currently, there is limited understanding of the mechanisms of quartz toxicity, including its mechanism for lung carcinogenicity. Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lung, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP based on human evidence.

Toluene has acute oral (rat) and dermal (rabbit) LD50 values of 4,328 mg/kg and 12124 mg/kg, respectively. The acute 4-hour inhalation (rat, female) LC50 value is 5,060 ppm (19.07 mg/L). Toluene is a severe eye and moderate skin irritant. Inhalation overexposure to toluene vapor can cause headache, fatigue, nausea, and central nervous system depression. Sustained inhalation of high levels of toluene has been shown to cause reversible kidney and liver damage. Subchronic inhalation of toluene vapors have caused permanent hearing loss, decreased learning capabilities and damage to the eyes in laboratory animal tests. Deliberate inhalation of high concentrations of toluene vapor by pregnant women has been shown to adversely affect the fetus. These fetotoxic effects include intrauterine growth retardation and delayed postnatal development. The fetotoxic effects of toluene seen in laboratory animals are similar to those seen in humans. Ingestion of toluene in laboratory animals caused mild gastritis and harmful effects on the respiratory system, kidneys, liver and heart. Ingestion in laboratory animals also caused harmful effects on the central nervous system and death. It has also been reported that subchronic ingestion of toluene caused brain and bladder damage in laboratory animals. Due to synergistic effects, the toxicity of toluene may be enhanced by exposure to n-hexane, benzene, xylene, acetylsalicylic acid and chlorinated hydrocarbons. The literature reports that toluene is an aspiration hazard, that acute oral exposure resulted in reversible visual dysfunction, and that chronic exposure has caused altered immune function in animals. Toluene is a chemical known to the State of California to cause reproductive toxicity.

California Proposition 65 Warning (applicable in California only) - This product contains (a) chemical(s) known to the State of California to cause cancer and birth defects or other reproductive harm.

12. ECOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

This material is not classified as dangerous for the environment.
The ecological assessment for this material is based on an evaluation of its components.

RESULTS OF PBT AND vPvB ASSESSMENT

Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Algae	Toxicity to Fish	Toxicity to Water Flea
Silica, quartz 14808-60-7	Not available	Not available	Not available
Toluene 108-88-3	EC50 = 12.5 mg/L - Green Algae (72h)	LC50 11-70.3 mg/L - Various Fish Species (96h) static LC50 5.8-28.2 mg/L - Various Fish Species (96h) semi-static LC50 5.89-19.05 mg/L - Various Fish Species (96h) flow-through NOEC = 1.39 mg/L - Coho Salmon (40 Day) flow-through	EC50 5.46 - 11.5 mg/L - Daphnia magna (48h) Static EC50 = 3.78 mg/L (measured) - Ceriodaphnia dubia (48h) Daily renewal NOEC = 0.74 - Ceriodaphnia dubia (7 Day) Daily Renewal

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this MSDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this MSDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? X

Proper Shipping Name: Combustible liquid, n.o.s.

Hazard Class: Combustible liquid

Packing Group: III

UN/ID Number: NA1993

Technical Name (N.O.S.): Toluene

Comments: Combustible liquids are not regulated in non-bulk packagings unless the combustible liquid is a hazardous substance, a hazardous waste, or a marine pollutant.

TRANSPORT CANADA

Dangerous Goods? Not applicable/Not regulated

ICAO / IATA

Dangerous Goods? Not applicable/Not regulated

IMO

Dangerous Goods? Not applicable/Not regulated

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

Canada: All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

European Economic Area (including EU): Cytec has appointed an Only Representative to relieve our customers from their registration requirements under the REACH Regulation (EC) No. 1907/2006. Please contact us if you wish to benefit from the OR arrangement.

Australia: All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory.

Philippines: All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

Switzerland: All components of this product are exempt from the new substance notification requirements for Switzerland (SR 813.11 art. 16-17).

Taiwan: All components of this product are included on the Taiwan Chemical Substance Inventory (TCSI) or are not required to be listed on the Taiwan inventory.

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

This product does not contain any components regulated under these sections of the EPA

PRODUCT HAZARD CLASSIFICATION UNDER SECTION 311 OF SARA

- Chronic

16. OTHER INFORMATION

NFPA Hazard Rating (National Fire Protection Association)

Health: 1 - Materials that, under emergency conditions, can cause significant irritation.

Fire: 1 - Materials that must be preheated before ignition can occur.

Instability: 0 - Materials that in themselves are normally stable, even under fire exposure conditions.

Reasons For Issue: New Product

Date Prepared: 02/19/2016

Date of last significant revision: 02/16/2016

Component Hazard Phrases

Silica, quartz

H350 - May cause cancer.

H372 - Causes damage to organs through prolonged or repeated exposure.

Toluene

H225 - Highly flammable liquid and vapor.

H361 - Suspected of damaging fertility or the unborn child.

H373 - May cause damage to organs through prolonged or repeated exposure.

H336 - May cause drowsiness or dizziness.

H315 - Causes skin irritation.

H320 - Causes eye irritation.

H304 - May be fatal if swallowed and enters airways.

H401 - Toxic to aquatic life.

H412 - Harmful to aquatic life with long lasting effects.

Prepared By: Legal & Compliance Services; E-mail: custinfo@cytec.com

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.
