

## SAFETY DATA SHEET

### Eclipse High Solids Polyurethane Enamel ECL-G-10

#### Section 1. Identification

**GHS product identifier** : Eclipse High Solids Polyurethane Enamel ECL-G-10  
**Other means of identification** : ECL-G-10\_WHITE BAC 7067 #715002B

**Relevant identified uses of the substance or mixture and uses advised against**  
: FOR INDUSTRIAL USE ONLY

**Supplier/Manufacturer** : Akzo Nobel Coatings, Inc.  
1 East Water Street  
Waukegan, IL 60085  
USA  
Tel. 1 847 623 4200  
Email: customer.  
service@akzonobel.com

**Canadian Supplier** : Akzo Nobel Coatings Ltd.  
110 Woodbine Downs Blvd.  
Unit #4 Etobicoke, Ontario  
Canada M9W 5S6  
+1 (800) 618-1010

**Emergency telephone number** : CHEMTREC +1 (800) 424-9300 (Inside the US)  
CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

**Date of issue / Date of revision** : 4 March 2019

**Safety Data Sheet Version** : 2.06

**Date of printing** : 4 March 2019

Akzo Nobel Coatings Inc. encourages and expects you to read and understand this entire MSDS, as there is important information throughout the document. Further, Akzo Nobel Coatings Inc. expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information contained in this MSDS and any other information regarding hazards and safety; 2) Furnish this same information to each of its customers for the product; 3) Request its customers to notify their employees, customers, and other users of the product of this information; and 4) Notify its employees, agents, contractors, and others that the precautions identified for this product and any other products with which mixtures may be created are transferable and cumulative to the mixture.

#### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 3  
CARCINOGENICITY - Category 2

#### GHS label elements

## Section 2. Hazards identification

Hazard pictograms :



Signal word :

Warning

Hazard statements :

Flammable liquid and vapor.  
Suspected of causing cancer.

### Precautionary statements

Prevention :

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Ground/bond container and receiving equipment. Keep container tightly closed.

Response :

IF exposed or concerned: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Storage :

Store locked up. Store in a well-ventilated place. Keep cool.

Disposal :

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified :

None known.

## Section 3. Composition/information on ingredients

Substance/mixture :

Mixture

Ingredient name	%	CAS number
titanium dioxide	35 - 40	13463-67-7
heptan-2-one	20 - 25	110-43-0
n-butyl acetate	1 - 5	123-86-4
silicon dioxide	1 - 5	7631-86-9
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	1 - 5	41556-26-7
aluminium hydroxide	1 - 5	21645-51-2
ethylbenzene	0 - 1	100-41-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : No known significant effects or critical hazards.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : No specific data.
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides  
metal oxide/oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## Section 6. Accidental release measures

- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
titanium dioxide	<b>OSHA PEL (United States, 2/2013).</b> TWA: 15 mg/m <sup>3</sup> 8 hours. Form: Total dust
heptan-2-one	<b>ACGIH TLV (United States, 3/2015).</b> TWA: 10 mg/m <sup>3</sup> 8 hours. <b>ACGIH TLV (United States, 3/2015).</b> TWA: 233 mg/m <sup>3</sup> 8 hours. TWA: 50 ppm 8 hours. <b>NIOSH REL (United States, 10/2013).</b>

## Section 8. Exposure controls/personal protection

n-butyl acetate	<p>TWA: 465 mg/m<sup>3</sup> 10 hours. TWA: 100 ppm 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 465 mg/m<sup>3</sup> 8 hours. TWA: 100 ppm 8 hours. <b>ACGIH TLV (United States, 3/2015).</b> STEL: 200 ppm 15 minutes. TWA: 150 ppm 8 hours. <b>NIOSH REL (United States, 10/2013).</b> STEL: 950 mg/m<sup>3</sup> 15 minutes. STEL: 200 ppm 15 minutes. TWA: 710 mg/m<sup>3</sup> 10 hours. TWA: 150 ppm 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 710 mg/m<sup>3</sup> 8 hours. TWA: 150 ppm 8 hours.</p>
silicon dioxide	<p><b>NIOSH REL (United States, 10/2013).</b> TWA: 6 mg/m<sup>3</sup> 10 hours.</p>
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate aluminium hydroxide	<p>None. <b>ACGIH TLV (United States, 3/2015).</b> TWA: 1 mg/m<sup>3</sup> 8 hours. Form: Respirable fraction</p>
ethylbenzene	<p><b>ACGIH TLV (United States, 3/2015).</b> TWA: 20 ppm 8 hours. <b>NIOSH REL (United States, 10/2013).</b> STEL: 545 mg/m<sup>3</sup> 15 minutes. STEL: 125 ppm 15 minutes. TWA: 435 mg/m<sup>3</sup> 10 hours. TWA: 100 ppm 10 hours. <b>OSHA PEL (United States, 2/2013).</b> TWA: 435 mg/m<sup>3</sup> 8 hours. TWA: 100 ppm 8 hours.</p>

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

## Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

	<b>Physical state</b>	: Liquid.
	<b>Color</b>	: White.
<b>Odor</b>		: Solvent.
<b>Odor threshold</b>		: Not available.
<b>pH</b>		: Not available.
<b>Melting/freezing point</b>		: Not available.
<b>Boiling point</b>		: 126°C (258.8°F)
<b>boiling range</b>		: Not available.
<b>Flash point</b>		: Closed cup: 25°C (77°F)
<b>Evaporation rate</b>		: Not available.
<b>Flammability (solid, gas)</b>		: Not available.
<b>Upper/lower flammability or explosive limits</b>		
	<b>Upper:</b>	: Not determined.
	<b>Lower:</b>	: Not determined.
<b>Vapor pressure</b>		: Not available.
<b>Vapor density</b>		: Not available.
<b>Relative density</b>		: 1.41
<b>Density</b>		: 11.77 lbs/gal      1.41 g/cm <sup>3</sup>

## Section 9. Physical and chemical properties

<b>Solubility</b>	: Not available.
<b>Solubility in water</b>	: Not available.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Kinematic (room temperature): 1.91 cm <sup>2</sup> /s (191 cSt)
<b>Weight Volatiles</b>	: 28.94% (w/w)
<b>Volume Volatiles</b>	: 49.21 % (v/v)
<b>Weight Solids</b>	: 71.06 % (w/w)
<b>Volume Solids</b>	: 50.79 % (v/v)
<b>Regulatory VOC</b>	: 3.4 lbs/gal 408 g/l minus water and exempt solvents
<b>VOC Actual</b>	: 3.4 lbs/gal 408 g/l

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	: Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
heptan-2-one	LD50 Oral	Rat	1600 mg/kg	-
	LC50 Inhalation Vapor	Rat	390 ppm	4 hours
n-butyl acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
ethylbenzene	LD50 Dermal	Rabbit	>5000 mg/kg	-
	LD50 Oral	Rat	3500 mg/kg	-

#### Irritation/Corrosion



## Section 11. Toxicological information

Product/ingredient name	Result	Species	Score	Exposure	Observation
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
heptan-2-one	Skin - Mild irritant	Rabbit	-	24 hours 14 milligrams	-
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
silicon dioxide	Eyes - Mild irritant	Rabbit	-	24 hours 25 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not available.

### Classification

Product/ingredient name	OSHA	IARC	NTP
titanium dioxide	-	2B	-
silicon dioxide	-	3	-
ethylbenzene	-	2B	-

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

Not available.

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Name	Result
ethylbenzene	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure : Not available.

## Section 11. Toxicological information

### Potential acute health effects

- Eye contact** : No known significant effects or critical hazards.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : No known significant effects or critical hazards.  
**Ingestion** : No known significant effects or critical hazards.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : No specific data.  
**Inhalation** : No specific data.  
**Skin contact** : No specific data.  
**Ingestion** : No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### Long term exposure

- Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### Potential chronic health effects

Not available.

- General** : No known significant effects or critical hazards.  
**Carcinogenicity** : Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.  
**Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	2144.1 mg/kg

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
heptan-2-one	Acute LC50 131000 to 137000 µg/l Fresh water	Fish - Pimephales promelas	96 hours
n-butyl acetate	Acute LC50 62000 µg/l	Fish - Danio rerio	96 hours
ethylbenzene	Acute EC50 4600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 3600 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	96 hours
	Acute EC50 2930 to 4400 µg/l Fresh water	Daphnia - Daphnia magna - Neonate	48 hours
	Acute LC50 40000 µg/l Marine water	Crustaceans - Cancer magister - Zoea	48 hours
	Acute LC50 4200 µg/l Fresh water	Fish - Oncorhynchus mykiss	96 hours

### Persistence and degradability

Not available.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
heptan-2-one	2.26	-	low
n-butyl acetate	2.3	-	low
ethylbenzene	3.6	-	low

### Mobility in soil

Soil/water partition coefficient (K<sub>oc</sub>) : Not available.

Other adverse effects : No known significant effects or critical hazards.








## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

**Special precautions for user** : Please Note: The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	UN1263	UN1263	UN1263	UN1263	UN1263
UN proper shipping name	PAINT	PAINT	PAINT	PAINT	PAINT
Transport hazard class(es)	3 	3  	3 	3  	3 
Packing group	III	III	III	III	III
Environmental hazards	No.	Yes.	No.	Yes.	No.

## Section 15. Regulatory information

### U.S. Federal regulations

**United States inventory (TSCA 8b):** All components are listed or exempted.

### SARA 311/312

**Classification** : Fire hazard  
Delayed (chronic) health hazard

### SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	ethylbenzene	100-41-4	0.1 - 1

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### California Prop. 65

## Section 15. Regulatory information

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

**WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
ethylbenzene	Yes.	No.	No.	No.
Quartz (SiO <sub>2</sub> )	Yes.	No.	No.	No.
toluene	No.	Yes.	No.	7000 µg/day (ingestion) 13000 µg/day (inhalation)

### International lists

#### National inventory

- Australia** : All components are listed or exempted.
- Canada** : At least one component is not listed in DSL but all such components are listed in NDSL.
- China** : All components are listed or exempted.
- Europe** : At least one component is not listed in EINECS but all such components are listed in ELINCS.  
Please contact your supplier for information on the inventory status of this material.
- Japan** : **Japan inventory (ENCS):** All components are listed or exempted.  
**Japan inventory (ISHL):** At least one component is not listed.
- Malaysia** : At least one component is not listed.
- New Zealand** : All components are listed or exempted.
- Philippines** : All components are listed or exempted.
- Republic of Korea** : All components are listed or exempted.
- Taiwan** : All components are listed or exempted.
- Turkey** : At least one component is not listed.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	*	2
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)

## Section 16. Other information



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

**Date of issue/Date of revision** : 4 March 2019

**Version** : 2.06

**MSDS #** : 004768 0005 003079F920

### Key to abbreviations

: ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

## SAFETY DATA SHEET

### Eclipse High Solids Polyurethane Enamel PC-233

#### Section 1. Identification

**GHS product identifier** : Eclipse High Solids Polyurethane Enamel PC-233  
**Other means of identification** : PC-233\_Curing Solution

**Relevant identified uses of the substance or mixture and uses advised against**  
: FOR INDUSTRIAL USE ONLY

**Supplier/Manufacturer** : Akzo Nobel Coatings, Inc.  
1 East Water Street  
Waukegan, IL 60085  
USA  
Tel. 1 847 623 4200  
Email: customer.  
service@akzonobel.com

**Canadian Supplier** : Akzo Nobel Coatings Ltd.  
110 Woodbine Downs Blvd.  
Unit #4 Etobicoke, Ontario  
Canada M9W 5S6  
+1 (800) 618-1010

**Emergency telephone number** : CHEMTREC +1 (800) 424-9300 (Inside the US)  
CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

**Date of issue / Date of revision** : 8 January 2020

**Safety Data Sheet Version** : 4.05

**Date of printing** : 8 January 2020

Akzo Nobel Coatings Inc. encourages and expects you to read and understand this entire MSDS, as there is important information throughout the document. Further, Akzo Nobel Coatings Inc. expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information contained in this MSDS and any other information regarding hazards and safety; 2) Furnish this same information to each of its customers for the product; 3) Request its customers to notify their employees, customers, and other users of the product of this information; and 4) Notify its employees, agents, contractors, and others that the precautions identified for this product and any other products with which mixtures may be created are transferable and cumulative to the mixture.

#### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

**Classification of the substance or mixture** : SKIN IRRITATION - Category 2  
EYE IRRITATION - Category 2A

#### GHS label elements

## Section 2. Hazards identification

Hazard pictograms :



**Signal word** : Warning  
**Hazard statements** : Causes serious eye irritation.  
 Causes skin irritation.

### Precautionary statements

**Prevention** : Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling.

**Response** : IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

**Storage** : Not applicable.

**Disposal** : Not applicable.

**Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
Hexamethylene diisocyanate, oligomers	95 - 100	28182-81-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

**Occupational exposure limits, if available, are listed in Section 8.**

## Section 4. First aid measures

### Description of necessary first aid measures

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.



## Section 4. First aid measures

- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:  
irritation  
redness
- Ingestion** : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire.
- Unsuitable extinguishing media** : None known.

## Section 5. Fire-fighting measures

- Specific hazards arising from the chemical** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides
- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

**Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

**Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

**Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Hexamethylene diisocyanate, oligomers	None.

**Appropriate engineering controls** : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### Skin protection

## Section 8. Exposure controls/personal protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	: Liquid.	
<b>Color</b>	: Colorless.	
<b>Odor</b>	: Mild.	
<b>Odor threshold</b>	: Not available.	
<b>pH</b>	: Not available.	
<b>Melting/freezing point</b>	: Not available.	
<b>Boiling point</b>	: 45°C (113°F)	
<b>boiling range</b>	: Not available.	
<b>Flash point</b>	: Closed cup: 166°C (330.8°F)	
<b>Evaporation rate</b>	: Not available.	
<b>Flammability (solid, gas)</b>	: Not available.	
<b>Upper/lower flammability or explosive limits</b>		
	<b>Upper:</b>	: Not determined.
	<b>Lower:</b>	: Not determined.
<b>Vapor pressure</b>	: Not available.	
<b>Vapor density</b>	: Not available.	
<b>Relative density</b>	: 1.16	
<b>Density</b>	: 9.68 lbs/gal	1.16 g/cm <sup>3</sup>
<b>Solubility</b>	: Not available.	
<b>Solubility in water</b>	: Not available.	
<b>Partition coefficient: n-octanol/water</b>	: Not available.	
<b>Auto-ignition temperature</b>	: Not available.	
<b>Decomposition temperature</b>	: Not available.	
<b>Viscosity</b>	: Kinematic (room temperature): 4.74 cm <sup>2</sup> /s (474 cSt)	

## Section 9. Physical and chemical properties

<b>Weight Volatiles</b>	:	0% (w/w)			
<b>Volume Volatiles</b>	:	0.00	%(v/v)		
<b>Weight Solids</b>	:	100.00	%(w/w)		
<b>Volume Solids</b>	:	100	%(v/v)		
<b>Regulatory VOC</b>	:	0.0	lbs/gal	0	g/l minus water and exempt solvents
<b>VOC Actual</b>	:	0.0	lbs/gal	0	g/l

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

**Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : No specific data.

**Incompatible materials** : No specific data.

**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Not available.

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Hexamethylene diisocyanate, oligomers	Eyes - Moderate irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	500 milligrams	-

#### Sensitization

Not available.

#### Mutagenicity

Not available.

#### Carcinogenicity

Not available.

#### Reproductive toxicity

Not available.

#### Teratogenicity

## Section 11. Toxicological information

Not available.

### **Specific target organ toxicity (single exposure)**

Not available.

### **Specific target organ toxicity (repeated exposure)**

Not available.

### **Aspiration hazard**

Not available.

**Information on the likely routes of exposure** : Not available.

### **Potential acute health effects**

**Eye contact** : Causes serious eye irritation.  
**Inhalation** : No known significant effects or critical hazards.  
**Skin contact** : Causes skin irritation.  
**Ingestion** : No known significant effects or critical hazards.

### **Symptoms related to the physical, chemical and toxicological characteristics**

**Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness  
**Inhalation** : No specific data.  
**Skin contact** : Adverse symptoms may include the following:  
irritation  
redness  
**Ingestion** : No specific data.

### **Delayed and immediate effects and also chronic effects from short and long term exposure**

#### **Short term exposure**

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

#### **Long term exposure**

**Potential immediate effects** : Not available.  
**Potential delayed effects** : Not available.

### **Potential chronic health effects**

Not available.

**General** : No known significant effects or critical hazards.  
**Carcinogenicity** : No known significant effects or critical hazards.  
**Mutagenicity** : No known significant effects or critical hazards.  
**Teratogenicity** : No known significant effects or critical hazards.

## Section 11. Toxicological information

- Developmental effects** : No known significant effects or critical hazards.  
**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Not available.

## Section 12. Ecological information

### Toxicity

Not available.

### Persistence and degradability

Not available.

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Hexamethylene diisocyanate, oligomers	5.54	367.7	low

### Mobility in soil

- Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

- Other adverse effects** : No known significant effects or critical hazards.

## Section 13. Disposal considerations

- Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

**Special precautions for user** : Please Note: The information provided in section 14 is based on a bulk package shipment via ground transport in North America. All shippers are responsible for ensuring the proper transportation classification and package/container requirements are followed for the relevant mode of transport.

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.

## Section 15. Regulatory information

### U.S. Federal regulations

**United States inventory (TSCA 8b):** All components are listed or exempted.

### SARA 311/312

**Classification** : Immediate (acute) health hazard

### International lists

#### National inventory

- Australia** : All components are listed or exempted.
- Canada** : All components are listed or exempted.
- China** : All components are listed or exempted.
- Europe** : All components are listed or exempted.
- Japan** : **Japan inventory (ENCS):** All components are listed or exempted.  
**Japan inventory (ISHL):** At least one component is not listed.
- Malaysia** : All components are listed or exempted.
- New Zealand** : All components are listed or exempted.



## Section 15. Regulatory information

<b>Philippines</b>	: All components are listed or exempted.
<b>Republic of Korea</b>	: All components are listed or exempted.
<b>Taiwan</b>	: All components are listed or exempted.
<b>Turkey</b>	: All components are listed or exempted.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

<b>Date of issue/Date of revision</b>	: 8 January 2020
<b>Version</b>	: 4.05
<b>MSDS #</b>	: 007899                      0007                      00283A2820

<b>Key to abbreviations</b>	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as
-----------------------------	---

## Section 16. Other information

modified by the Protocol of 1978. ("Marpol" = marine pollution)  
UN = United Nations

### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.